

UTC-315x

15.6" Ubiquitous Touch Computer UTC-315D with Intel® BayTrail J1900

Preliminary



Features

- Low Power & Fanless design
- Built in Intel BayTrail J1900 (UTC-315D)
- Providing Natural Viewing Experience with 16:9 15.6" Display
- Front panel complies with IP65 protection standard
- Landscape & Portrait screen mode support by different applications
- VESA 75 mm standard mounting holes for varied mounting demands
- Attachable frame design , flexible for panel mount applications



Introduction

UTC-315x is the multi-purpose all-in-one computing system which equipped with wide format, touch based LCD panel. It is easy to integrate key peripherals and display systems for diversified self-service and interactive signage deploy in different application areas. With the removable frame , the system also could fulfill industries or control system applications with panel mounting design. UTC series touch panel computers are the best investments to enhance user satisfaction, further brand equity, and maximize business profits.


Specifications

Processor System	CPU	Intel® BayTrail J1900
	Basic Frequency	2.0 GHz (Quad-Core)
	L2 Cache	2MB
	Memory	1 x SO-DIMM DDR3L 1333 MHz up to 8 GB
	HDD	1 x 2.5 internal SATA HDD bay
	Network	2 x Gigabit Ethernet ports (RJ-45)
	I/O ports	1 x RS-232 COM , 1 x RS-232 / 422 / 485
		5 x USB 2.0 / 1 x USB 3.0
		2 x Gigabit Ethernet (RJ-45)
		1 x HDMI
OS support	Audio Line-out x 1, Mic-in x 1	
	RJ-11 (option)	
	Stereo Speaker	1W x 2
	BUS expansion	Full-size MiniPCIe/mSATA
	Mounting	VESA 75 x 75
	Dimension(WxHxD)	402 x 260 x 39.7 mm
	Weight	< 4 kg (8.8 lb)
	Windows Embedded Standard 7	
	Windows Embedded Standard 8	
	Embedded Linux 3.0	
Environmental Specifications	Operating Temperature	0 ~ 40° C (32 ~ 104° F)
	Relative Humidity	10 ~ 95% @ 40° C non-condensing
	Vibration	0.5G
	Shock	10 G peak acceleration (11 msec. duration)
	EMC/ Safety	CE, FCC, UL, CCC CB, BSMI
	Front Panel Protection	IP65/ NEMA4 Compliant
Power Supply	Input Rating	12 V/7 A (84W ITE Adapter)
	Power consumption	Typical 32W Max. 70W
LCD Display	Size	15.6" TFT LCD
	Max Resolution	1366 x 768
	Max Color	262K
	Pixel Pitch (um)	252 (H) x 252 (V)
	Brightness (cd/m2)	200 (Typical)
Touch Screen	View Angle	90°/60°
	Type	Analog Resistive 5-wires (Res. Flat Glass) / Projected Capacitive Touch Panel (Pcap. Flat Glass)
	Light Transmission	Res. Touch : 80% ± 5% / P-Cap Touch : 90% ± 2%
Controller	COM interface / USB interface	

UTC-315D

Dimensions

Unit: mm (inch)



Ordering Information

Part No.	Description
UTC-315D-RE	15.6" Intel® Celeron J1900 Based fanless UTC with Resi.T/S, 4 GB RAM
UTC-315D-PE	15.6" Intel® Celeron J1900 Based fanless UTC with PCT.T/S, 4 GB RAM


Peripherals for UTC-300 series

Part No.	Description
UTC-300P-C01E	5M Camera Module for UTC-3XX
UTC-300P-M01E	Magnet Strip Reader for UTC-3XX
UTC-300P-R01E	RFID Reader for UTC-3XX
UTC-300P-S01E	Smart Card Reader for UTC-3XX
UTC-300P-B01E	1D Barcode Reader for UTC-3XX
UTC-300P-B02E	2D Barcode Reader for UTC-3XX

Installation Accessory

Part No.	Description
UTC-300P-D01E	Desk Stand for UTC-3xx
UTC-WALL-MOUNT1E	Wall Mount kit for UTC-515/520
UTC-WALL-MOUNT3E	Wall Mount Kit for UTC-515/520
UTC-T01-STANDE	Triangle shape floor stand
UTC-H01-STANDE	H-shaped floor stand

Fully- Integrated I/O



A. Com1
B. Com2
C. Line-out
D. Mic in
E. LAN ports x 2

F. HDMI
G. USB 2.0 x 5 / USB 3.0 x 1
H. Power button
I. DC input (12 V_{DC})

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660