

# **AVerMedia**

# CL314H1

# 1080p60 HDMI 4-Channel Low Profile Video Capture Card



#### **Features**

- Maximum input resolution up to 4096x2160/30fps
- Maximum capturing and recording Up to 4096x2160/30fps
- Low-profile PCI Express form factor
- Reduce the capture latency to shorten the time required for a full frame of image to be captured
- Support hardware up/down scaling, deinterlacing, and color space convert
- Support 10-bit color depth

### Introduction

AVerMedia CL314H1, the 1080p60 HDMI 4-Channel low profile video capture card, is equipped by four HDMI channels with the embedded audio input and supports astounding uncompressed real-time video capturing up to 1920 x 1080 60fps full HD resolution.

At the frame rate of 60 fps, CL314H1 can improve the quality of a wide range of media recorded for businesses, universities, broadcasting, and manufacturing facilities, which can eventually provide a more lifelike and smooth video playback experience.

#### **Low Profile Form Factor**

Suitable for small-footprint embedded platform, the compact low profile form factor design provides a better use of internal space and reduces cable routing. It increases the use of interior space for a more flexible heat spreading solution.

#### **Hardware Video Processing**

CL314H1 has built-in AVerMedia Video Engine technology which implements most useful video enhancing features to significantly reduce the efforts of CPU and the software development. In other words, this can help our clients to achieve the better cost saving of the hardware platform and the development resource.

#### Support up to 4:4:4 10-bit RGB and YUV

The 10-bit color depth support is especially useful in the medical imaging applications where images with the slightest color variation may indicate different conditions or stages of diseases. This in turn may assist doctors in accurately diagnosing patient conditions.

### Versatile SDK

AVerMedia software development kit (SDK) is a set of development tools that allows software engineers to seamlessly integrate video capture modules into application specific systems.

AVerMedia SDK constantly updates the latest industrial standards, protocols, and media formats for optimal compatibility and to support cutting-edge technologies. AVerMedia SDK also supports various programming languages for quick and easy application, providing sample source codes.

Along with AVerMedia SDK, CL314H1 can be easily integrated into the different vertical applications that require superb video quality, such as education, broadcasting, and surveillance, etc.



# CL314H1

# 1080p60 HDMI 4-Channel Low Profile Video Capture Card

## Main/Daughter Board Design

Our CL314H1 low-profile ready capture card come with a smaller bracket as well, so you can choose to install it on a regular or low-profile system.

### With standard full height bracket



### With low-profile bracket



## **Specifications**

| Host Interface               | PCIe Gen2 x 4  |
|------------------------------|--|
| Audio Interface              | HDMI embedded PCM  |
| Audio Format                 | Embedded HDMI, PCM   |
| Audio Sampling Rate          | 32/44.1/48KHz  |
| Connector Type               | HDMI Type A  |
| Input Interface              | HDMI*4 (HDMI 1.4a)   |
| Video Format                 | I420, NV12, YV12, IYU2, YUY2, YUYV,<br>UYVY, AYUV, RGB565, RGB555,<br>RGB24, RGB32, ARGB32, XRGB,<br>V210,Y210, V410, Y410 |
| Color Depth                  | 8 bit/10bit  |
| Channel No.                  | 4 channels   |
| Max. Input Resolution        | 4096x2160 30fps  |
| Max. Recording<br>Resolution | 4096x2160 30fps (2ch)<br>1920x1080 60fps (4ch)   |

| Encoding Mode         | Software Encoding  |
|-----------------------|--|
| Multi-Card Support    | Yes  |
| Supported OS          | Windows 7, 8.1, 10 (32/64-Bit)<br>Linux Kernel 2.6.14 and above<br>(32/64-bit) |
| Form Factor           | PCIe Low Profile   |
| Dimension (L x W)     | 180 x 68.78 mm   |
| Power Consumption     | 15W<   |
| Operating Temperature | 0°C ~ 50°C   |
| Operating Humidity    | 5% - 80% Relative Humidity   |
| Safety Certification  | FCC / CE   |

All specifications are subject to change without prior notice.

## **Ordering Information**

- CL314H1: 1080p60 HDMI Quad-Channel Low Profile Video Accessories: Capture Card
- SDK kits:
  - SDK Pro
  - SDK Premium add-on kits

- - Low-profile bracket







# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660