



EMX-TGLC

11th Gen Intel® Core™ SoC i5/i3 BGA Processor Thin Mini ITX Motherboard

- > Onboard 11th Gen. Intel® Core™ SoC i5/i3 @ BGA Processor (Support Consumer CPU SKU)
- > 2 x 260-pin DDR4 3200 MHz SO-DIMM supports up to 64GB (non ECC only)
- > 2 x DP++, 1 x LVDS, 1 x eDP (Quadrupe independent displays)
- > 1 x Intel® I226LM 2.5 Gigabit Ethernet
- > 1 x Intel® I219LM Gigabit Ethernet PHY
- > Realtek ALC897 co-lay ALC888S (Default: Realtek ALC897)
- > TI TPA3113D2PWP Stereo Class-D 6W x 2 Audio Amplifier
- > 1 x M.2 Type B 3042/3052/2242/2260/2280 (with 1 x PCI-e x1 (default) or SATA, USB 3.0 with 1 x SIM card slot, support WWAN+GNSS or NVMe SSD
*SATA 2 share with M.2 key B SATA
- > 1 x M.2 Key E 2230 support WiFi module and CNVi (1 x PCI-e x1 & USB 2.0 Signal)
- > 1 x PCI-e x4 slot support PCI-2 x2(Gen3) device
- > GPIO 16bit
- > Onboard NuvoTon NPCT754AADYX support TPM 2.0
- > Support Line-out & Mic-in & Front audio pin-header
- > DC in +12V~24V

Spec

-System Information-	
Processor	Intel® Core™ i5-1135G7 (up to 4.2GHz, quad-core, 8M Cache, TDP: 15W) Intel® Core™ i3-1115G4 (up to 3.0GHz, dual-core, 6M Cache, TDP: 15W) Intel® Celeron® 6305E (up to 1.8GHz, dual-core, 4M Cache, TDP: 15W)
System Memory	2 x 260-pin DDR4 3200 MHz SO-DIMM supports up to 64GB (non ECC only)
I/O Chipset	EC ITE IT8528E
BIOS Information	AMI uEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
TPM	Onboard NuvoTon NPCT754AADYX support TPM 2.0
Expansion	
Expansion	1 x M.2 Type B 3042/3052/2242/2260/2280 (with 1 x PCI-e x1 (default) or SATA, USB 3.0 with 1 x SIM card slot, support WWAN+GNSS or NVMe SSD *SATA 2 share with M.2 key B SATA 1 x M.2 Key E 2230 support WiFi module and CNVi (1 x PCI-e x1 & USB 2.0 Signal) 1 x PCI-e x4 slot support PCI-e x2(Gen3) device *Only support 25W Slot, +V12A total current is 8.7A.
I/O	
USB Port	3 x USB 3.1 Gen2, 1 x USB 3.1 Gen1 at I/O 4 x USB2.0 by pin header
COM Port	4 x RS232 2 x RS232/422/485
SATA	1 x SATA Power 2 x SATA III
DIO	1 x 16-bit GPIO
Display	
Graphic Chipset	Intel® 12th Generation CPU integrated
Spec. & Resolution	DP1+DP2 (DP1.4): Max: 7680 x 4329@60 Hz Single DP port (2021/2 Lab test): 5120 x 2160 @60 Hz, DVT check Max: 7680 x 4329@60 Hz Note: This resolution is actual test result. Intel resolution as below: 2 x DP++ : 1920 x 1080@60 Hz LVDS: 1920 x 1080 Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS) eDP 4096 x 2304@60 Hz *2 x DP++, LVDS, eDP (Quadrupe independent displays)
Multiple Display	2 x DP++/1 x LVDS/1 x eDP (Quadrupe independent displays)
LVDS	2CH 18/24bits LVDS 1920 x 1080 Chrontel. CH7511B eDP to LVDS Converter
Audio	
Audio Codec	Realtek ALC897 co-lay ALC888S
Audio Interface	Support Line-out & Mic-in & Front audio pin-header
Audio Amplifier	2 x Stereo Class-D 6W Audio Amplifier
Ethernet	
LAN Chipset	1 x Intel® I226LM 2.5 Gigabit Ethernet 1 x Intel® I219LM Gigabit Ethernet PHY
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ45
Mechanical & Environmental	
Operating Temperature	Intel@ standard CPU SKU support: 0~60C
Storage Temperature	-40 ~ 75°C (-40 ~ 167°F)



Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.88lbs (0.4Kgs)
Power Requirement	+12V~24V
Power Mode	AT/ATX
Dimension (L x W)	6.69" x 6.69" (170mm x 170mm)
Software Support	
OS Information	Win10 64bit Linux
Ordering Information	
Ordering Information	EMX-TGLC-15-A1R (Core i3, Thin, 2DP/2LAN, Standard Temp.) EMX-TGLC-35-A1R (Core i5, Thin, 2DP/2LAN, Standard Temp.) Intel® 11th Gen. Core™ SoC i5/i3 @BGA Processor Mini ITX Motherboard

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660