



ECM-EHL

Intel® Elkhart Lake 3.5" Micro Module

- > Bottom Layer Soldered Processor
- > Single DRAM Socket, Max, Up to 32GB DDR4 3200MTs (non-ECC Supported)
- > Triple Display, DP 1.4a , HDMI 2.0b, eDP 1.3
- > Dual Expansion Slot, M.2 Key-B, M.2 Key-E
- > Dual Intel® Gigabit Ethernet, 2.5GbE
- > With extend temperature, -40°C ~ 85°C
- > Wide DC-Input, +9~36Vdc

Spec

-System Information-	
Processor	Onboard Intel® Pentium®/Celeron®/Atom™ SoC BGA Processor (Elkhart Lake Platform 4.5~12W)- (with CPU Bottom Mounted) Intel® Celeron® J6412 Processor (1.5M Cache, up to 2.60 GHz) Intel® Celeron® J6413 Processor (1.5M Cache, up to 3.00 GHz) Intel Atom® x6413E Processor (1.5M Cache, up to 3.00 GHz) Intel Atom® x6425RE Processor (1.5M Cache)
Platform Controller Hub	Elkhart lake SoC integrated
System Memory	Single 260-pin DDR4 SODIMM Socket, Supports Up to 32GB DDR4 3200MTs SDRAM (non ECC Supported)
I/O Chipset	EC ITE IT5571
BIOS Information	AMI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
H/W Status Monitor	CPU & system temperature monitoring Voltages monitoring
TPM	TPM 2.0 NuvoTon_NPCT750AADYX (for standard temp) & NPCT754AADYX (for extend temp), co-lay Infineon_SLB9670VQ2.0 Default is NuvoTon
Expansion	
Expansion	1 x M.2 (Key-B, 2242/3042, PCIe x2, or (PCIe x1+USB3.1 GEN 1), or (SATA III + USB 3.1 GEN1), USB2.0, SIM Slot for SSD/LTE/IO Cards) *Default is PCIe x1/SATA III+USB3.1 GEN1 1 x M.2 (Key-E, 2230, PCIe x1, USB2.0)
Storage	
Storage	1 x M.2 (Key-B, 2242) 1 x SATA III
I/O	
USB Port	2 x USB 3.1 (Gen2 10Gbps) 4 x USB 2.0
COM Port	1 x RS-232/422/485 3 x RS232
SATA	1 x SATA III
DIO	1 x 2x6-Pin Header (2.0mm) for 8-bit GPIO, SMBUS, +5V, GND
MIO	1 x eSPI
Other	2 x LAN
Display	
Graphic Chipset	Intel® UHD Graphics
Spec. & Resolution	HDMI 2.0b Max resolution 4096x2160@60Hz DP 1.4a Max resolution 4096x2160@60Hz eDP 1.3 Max resolution 4096x2160@60Hz
Multiple Display	Triple Display
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	Mic-In, Line-In, Line-Out in pin header
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	Intel® I226LM/I226IT
Ethernet Interface	2 x 10/100/1000/2.5G Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Operating Temperature	Operating Standard Temp: 0°C ~ 60°C with 0.5m/s air flow Extend Temp: -40°C ~ 85°C with 0.5m/s air flow.
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)

www.avalue.com.tw



Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.44lbs (0.2kg)
Power Requirement	DC in +9V ~ +36V
ACPI	Single power ATX Support S0,S3, S4, S5

	ACPI 5.0 Compliant
Power Mode	AT/ATX (Default Setting: AT)
Dimension (L x W)	5.7" x 4" (146mm x 101mm)
Software Support	
OS Information	Win 10 Linux
Ordering Information	
Ordering Information	ECM-EHL-J6412-B1R ECM-EHL/J6412/1SATA/4COM/6USB/2LAN/B1 ECM-EHL-J6413-B1R ECM-EHL/J6413/1SATA/4COM/6USB/2LAN/B1 ECM-EHL-X13E-B1R ECM-EHL/x6413E/1SATA/4COM/6USB/2LAN/B1 ECM-EHL-X25RE-B1R ECM-EHL/x6425RE/1SATA/4COM/6USB/2LAN/B1



www.avalue.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660