


NUC 1200 Motherboard Series

NUC Motherboard



KEY FEATURES

- Intel® 12th Gen (Alder Lake-P) Core™ Processors
- 2 x 260-pin SO-DIMM DDR4 3200 MHz, up to 64GB
- 6 x USB 3.2 Gen2, 2 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E, 1 x COM, 1 x SATA3
- 2 x Intel 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0b, 3 x DP 1.4a (2 from Type-C)
- TPM 2.0 onboard IC
- Supports Intel® vPro, AMT (NUC-1265UE/NUC-1245UE)
- 12V~19V DC-In

SPECIFICATIONS

Form Factor

Dimensions	NUC (4.09-in x 4.02-in x 1.5-in, 10.4 cm x 10.2 cm x 3.8 cm)
------------	--

Processor System

CPU	Intel® 12th Gen (Alder Lake-P) Core™ Processors NUC-1260P(i7-1260P, 4P+8E) NUC-1240P(i5-1240P, 4P+8E) NUC-1220P(i3-1220P, 2P+8E) NUC-1265UE(i7-1265UE, 2P+8E) NUC-1245UE(i5-1245UE, 2P+8E) NUC-1215UE(i3-1215UE, 2P+4E) NUC-7305 (Celeron-7305, 1P+4E)
Chipset	MCP
BIOS	AMI SPI 256 Mbit

Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	Intel® Iris® Xe Graphics for i7/i5 CPU Intel® UHD Graphics for i3/Celeron CPU
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 4 display (Included 2 outputs from Type-C)

Expansion Slot

M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless
-----	---

Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

Ethernet

Controller/ Speed	NUC-1265UE/ NUC-1245UE: Intel® I225LM with 10/100/1000/2500 Mbps, supports AMT/vPro NUC-1260P/ NUC-1240P/ NUC-1220P/NUC-1215UE/NUC-7305 : Intel® I225LM with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

Front I/O

USB	2 x USB 3.2 Gen2 (Type-A) 2 x USB 3.2 Gen2 (Type-C, Supports DP1.4a display output) * USB4™ Compliance Test is pending for certification
Audio	1 (headphone & microphone jack)

Rear I/O

HDMI	1 x HDMI 2.0b
DisplayPort	1 x DP1.4a
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type A)
DC Jack	1

Internal Connector

USB	2 x USB 2.0 (1 x 2.00 pitch header)
COM	1 x COM(RS-232/RS-422/RS-485)
TPM	TPM 2.0 onboard IC

Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe Gen4 x4 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	12V~19V DC-In Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C ~ 60°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660