



LEP-401M-KIT

Industrial IP30 Ethernet Extender, 800 meters, 10/100Mbps Ethernet PoE Extender (1 Pair: LEP-401M-L and LEP-401M-R)




INTRODUCTION

Antaira Technologies' LEP-401M-KIT contains both LEP-401M-L and LEP-401M-R. The former is a long reach transceiver with one Ethernet port and one PoE Long Reach injector port, and the latter is a long reach receiver with one PoE Long Reach Extender port and one PoE PSE Ethernet port.

LEP-401M-KIT is greatly beyond the 100 meters distance limitation of RJ45 cable. Up to 800 meters the data and power can be transmitted simultaneously over the UTP cable. This kit is fully compliant with IEEE 802.3, 802.3u, 802.3af/at standards. Operation status can be locally monitored through a set of diagnostic LEDs located in the front and rear panels.

DIMENSIONS



Front View Side View

Rear View Wall-Mount Kit View

LEP-401M-R

www.antaira.com

Toll-Free:1 (844) 268-2472 | T: 1 (714) 671-9000 | F: 1 (714) 671-9944



Ontaira[®]

SPECIFICATIONS

TECHNOLOGY		MECHAN
Standards	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3af/at Power over Ethernet	Housing Dimensio
SWITCH PROPERTIES		
Switch Architecture	Store-and-Forward	Weight Mounting
DIP Switch	LEP-401M-L 1: Power over line- ON: Disable; OFF: Enable	POWER F
	2: LFPT- ON: Enable; OFF: Disable 3: Line Speed- ON: 10M; OFF: Auto	Input Vol
	LEP-401M-R	Power Co
	1: PoE for PD- ON: Disable; OFF: Enable 2: LFPT- ON: Enable; OFF: Disable 3: PoE PD mode- ON: Passive PoE; OFF:	PoE Pow
	Standard PoE	System F Consump
PORT INTERFACE		oonsum
Network Connector	LEP-401M-L 2 pin Terminal Block for power input	ENVIRON
	connector 1 RJ45 for LAN 10/100Base-TX Ethernet port	Operating Tempera
	1 RJ-45 for extension distance and delivery power	Storage Tempera
	and communication data to remote unit LEP-401M-R 1 RJ45 for LAN 10/100Base-TX PoE/PSE	Ambient Humidity
	Ethernet	REGULAT
	1 RJ-45 for long distance receiving power and communication data from local unit	Free Fall Shock
LED Indicators	LEP-401M-L Power (Green); Delivery Power Range <15W (Amber), >15W (Green); LFPT (Amber)	Vibration EMC
	LAN Link active (Green), Line Speed/Link active 10M(Amber), 100M(Green)	EMI
	LEP-401M-R	EMS
	Power (Green); PoE Power Range for PD <15W (Amber), >15W (Green); LFPT (Amber); LAN Link active (Green) Line Speed/Link active 10M (Amber), 100M (Green)	Warranty

NICAL CHARACTERISTICS Metal, IP30 protection on 52 x 25 x 102.5 mm (W x H x D) Unit: 0.38 lb. Shipping: 0.75 lb. Wall mounting g REQUIREMENT 55~57VDC oltage connection 2-contact removable terminal block ver Output 30W LEP-401M-L: < 3W (without PoE); 34.5W (with PoE @ 30W) Power LEP-401M-R: < 1.5W (without PoE); 32.5W ption (with PoE @ 30W) NMENTAL LIMITS ıg -40°C to 75°C ature -40°C ~ 85°C ature Relative 10 to 95%, (non-condensing) v TORY APPROVALS IEC60068-2-31 IEC60068-2-27 IEC60068-2-6 n CE (EN55032, EN55035) FCC Part 15 Subpart B Class A, CE EN61000-4-2,3,4,5,6,8 5 Years V

ORDERING INFORMATION

LEP-401M-KIT	Industrial IP30 Ethernet Extender, 800 meters, 10/100Mbps Ethernet PoE Extender (1 Pair: LEP-401M-L and LEP-401M-R)
LEP-401M-L	Industrial IP30 Ethernet Extender, 800 meters, 10/100Mbps Ethernet PoE Extender (Local End); EOT: -40°C to 75°C
LEP-401M-R	Industrial IP30 Ethernet Extender, 800 meters, 10/100Mbps Ethernet PoE Extender (Remote End); EOT: EOT: -40°C to 75°C

www.antaira.com

Toll-Free:1 (844) 268-2472

| T: 1 (714) 671-9000 | F: 1 (714) 671-9944



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660