



iTC-1121R

Fanless Industrial Panel PC w/ Intel® Elkhart Lake Processor



Features

- Intel® Celeron® Processor J6413 (1.5M Cache, up to 3.00 GHz)
- 12.1" 1024 x 768 XGA LCD display
- Fanless design w/ Aluminum Front bezel
- Flush front panel w/ IP65 waterproof compliant
- Support 2.5GbE LAN and USB 3.2 Gen1 (5Gbps)
- Rich I/O: 4 x COM/ 2 x LAN/ 4 x USB3.2(5Gbps)/ 8-bit DI/O & dual video output: DisplayPort and DVI-D
- Easy-accessible expansion for storage and wireless module.
- 9~36V wide-range DC input with reverse protection

Industrial Automation System

System

CPU	Intel® Celeron® J6413 Quad-Core™ Processor 1.80GHz
Memory	1 x 260 pin DDR4 SO-DIMM socket, supporting 3200MHz SDRAM up to 32GB (4GB DDR4 SO-DIMM pre-installed)
LAN	1 x Intel® 225LM controller 1 x Intel® i211AT controller
Watchdog Timer	1~255 levels reset

Storage

1st Device	1 x M.2 M-key 2242/ 2280 (SATAIII only)
2nd Device	1 x 2.5" SSD/ HDD tray

Audio

Type	1 x Mic-in / 1 x Line out
Speaker	2 x 1.5W speakers (optional)

LCD Display

Size/Type	12.1" TFT LCD Panel
Max. Resolution	1024 x 768, XGA
Max. Colors	16.2M
Luminance	500 cd/m ²
Touch Screen	Flat 5-wire Analog Resistive
View Angle (U/D/R/L)	89°/89°/89°/89°

Button & Indicator

Buttons	Power on & Reset
LED Indicator	Power-on status/ HDD status/ RTC battery status

Power System

Power Input	DC 9~36V
Power Consumption	Typical 25W (w/o I/O cards)
Remote Control	1x3-pin terminal block for remote control and PWR LED output

Qualification

Certification	CE, FCC Class A
---------------	-----------------

Expansion

Expansion Bus	1 x Mini PCIe slot (PCIe x1+ USB2.0, Full size) (for Wireless connection) w/ 1 x SIM card slot
---------------	--

External I/O

Serial Ports	2 x DB-9 connectors for RS232/422/485 2 x DB-9 connectors for RS232
USB Ports	4 x Type-A USB 3.2 Gen 1 (5Gbps)
LAN	1 x RJ-45 ports for GbE LAN 1 x RJ-45 ports for 2.5 GbE LAN
Video Ports	1 x DVI-D connector, supporting Full HD resolution 1 x DisplayPort 1.4 connector, supporting 4K2K resolution
Digital I/O	8 bit Digital I/O

Mechanical

Mounting Type	Panel mount (clamps are provided) VESA-75/100 mount (optional)
Chassis	Aluminum front bezel and steel-metal chassis
Dimension (W x H x D)	315 x 260 x 68.8 mm
Weight (Net)	3.6 kg


Environmental

Operating Temp.	-10 ~ 55°C
Storage Temp.	-20 ~ 70°C
Operating Humidity	10 ~ 95% RH @ 55°C (non-condensing)
Vibration	5 ~ 500Hz, 1Grms X,Y,Z axis (with SSD)
Shock	Operating 10G, 11ms X,Y,Z axis (with SSD)


OS Support

Windows®10 (64bit)

All specifications are subject to change without notice.



Dimensions



Optional Accessories

PAC-60W6A-FSP-ES 12V/5A 60W AC/DC power adapter kit



VMB-1150 iTC-1150R VESA-mount bracket kit, w/ 75 x 75 mm & 100 x 100 mm VESA supports



64/128/256GB SSD 2.5" SSD MLC 64/128/256GB



64GB M.2 SSD M.2 M-key 2242/ 2280, 64GB, SATA3.0



WiFi-AT4550 Atheros, QCNFA324 Wi-Fi module w/ 2*30cm internal wiring



ANT-D11 1 x Wi-Fi Dual-band 2.4G/5G antenna



ADK-11X iTC-11xx series audio kit



SCK-722C Assembly kit for SiP-41B/42B
(Note: SCK-722C can only be installed with VMB-1121 Mounting Bracket)



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660