



ASRock
— Industrial —

STX-1500

Mini-STX Motherboard



KEY FEATURES

- Intel® Tiger Lake-UP3 MCP Processor
- 2 x 260-pin SO-DIMM, Support Dual Channel up to 64GB DDR4 3200 MHz
- 3 x USB 3.2 Gen2, 5 x USB 2.0, 1 x M.2 Key E, 1 x M.2 Key M, 1 x M.2 Key B, 2 x COM, 2 x SATA3
- 1 x Intel 2.5 Gigabit LAN, 1 x Intel 1 Gigabit LAN
- Support Quadruple display, 1 x LVDS, 1 x eDP1.4, 4 x HDMI 2.0a
- TPM Header (STX-1500E/STX-1500V)
TPM 2.0 IC onboard, supports Intel® vPro, AMT (STX-1500M/STX-1500P)
- Supports RAID 0/1
- 12~28V DC-In

SPECIFICATIONS

Form Factor

Dimensions	Mini-STX (5.5-in x 5.8-in)
------------	----------------------------

Processor System

CPU	Intel® 11th Gen (Tiger Lake-UP3) Core™ Processors - STX-1500P (i7-1185G7E, QC, Max Speed up to 4.4GHz, up to 28W) - STX-1500M (i5-1145G7E, QC, Max Speed up to 4.1GHz, up to 28W) - STX-1500V (i3-1115G4E, DC, Max Speed up to 3.9GHz, up to 28W) - STX-1500E (Celeron 6305E, DC, 1.8GHz, 15W)
Chipset	MCP
BIOS	AMI SPI 256 Mbit

Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	Intel® Iris® X ^e Graphics for i7/i5 CPU Intel® UHD Graphics for i3/Celeron Processor
HDMI	HDMI 2.0a Max resolution up to 4096x2160@60Hz
DisplayPort	N/A
VGA	N/A
LVDS	Dual channel 24 bit up to 1920 x 1200@60Hz
eDP	eDP 1.4 Max resolution up to 4096x2304@60Hz
DVI	N/A
MultiDisplay	Quadruple display

Expansion Slot

PCIe	N/A
PCI	N/A
mini-PCIe	N/A
M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless 1 x M.2 (Key B, 3042/3052/2280) with PCIe x1 / USB 3.2 / USB2.0 and SIM for 4G/5G
SIM Socket	1x SIM socket connected to M.2 key B

Audio

Interface	Realtek ALC897 HD , High Definition Audio. Mic-In / Line-Out
-----------	--

Ethernet

Controller/ Speed	STX-1500E/STX-1500V: LAN1: Intel® I225LM with 10/100/1000/2500 Mbps LAN2: Intel® I219V with 10/100/1000 Mbps STX-1500M/STX-1500P: LAN1: Intel® I225LM with 10/100/1000/2500 Mbps LAN2: Intel® I219LM with 10/100/1000 Mbps
Connector	2 x RJ-45

Front I/O

USB	1 x USB 3.2 Gen2, 1 x USB2.0
HDMI	1 x HDMI 2.0a
Audio	2 (Mic-In, Line-Out)

Rear I/O

HDMI	3 x HDMI 2.0a
DisplayPort	N/A
VGA	N/A
DVI	N/A
Ethernet	1 x 2.5 Gigabit LAN 1 x 1 Gigabit LAN
USB	2 x USB 3.2 (Gen2), 2 x USB2.0
DC Jack	1

Internal Connector

USB	1 x USB 2.0 (1x2.54 pitch header)
COM	1 x COM (RS232/422/485) 1 x COM (RS232)
Parallel	N/A
GPIO	4 x GPI, 4 x GPO
TPM	STX-1500M/STX-1500P: TPM 2.0 IC onboard STX-1500E/STX-1500V: TPM Header
LVDS	1
eDP	1
VGA	N/A
SATA PWR Output	1
Speaker Header	1

Storage

M.2	1 x M.2 (Key M, 2242/2260/2280) with SATA3 and PCIe Gen4x4 for SSD * Shared with SATA3_0
mSATA	N/A
SATA	2 x SATA3 (6Gb/s)
RAID	Intel® SATA RAID 0/1
eMMC	N/A

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	12~28V DC-In with 4-pin wafer PWR cable or DC Jack
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C - 60°C
Storage Temp	-40° C - 85° C
Operating Humidity	5% - 90%
Storage Humidity	5% - 90%

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660