

IN-VEHICLE Computing

# **VBOX-3611-4L-D5G**

Taiwan Patent No. M447854, M448011

Intel Gen 6 Core i7-6600U CPU with 4 x GbE LAN On-Board Computer with Dual 5G Modem Capability

#### **Features**

- Intel Core i7-6600U
- Wireless support Dual 5G w/ Dual SIM Cards, WLAN, GPS Dead Reckoning, WiFi, BT (Optional)
- 9V 48V DC Power Input
- · Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0, 1, 5
- 1 x CAN Bus 2.0B (Optional)
- E13 and EN50155 certified





Operating System Win 10 64bit, Ubuntu 18.04









Dela

Introduction

VBOX-3611-4L-D5G, as an In-Vehicle Computer, is powered by Intel Gen 6 Core i7-6600U CPU and features wide range 9~48V DC power inputs, smart vehicle power ignition, and adjustable power management. Dedicated power system design for a variety of vehicles is E13 and EN50155 certified, and can be adapted to unstable vehicle power source with ease. Optional CAN Bus and GPS Dead Reckoning provide interfaces for real time vehicle status monitoring and accurate location tracking. With addition of unique and first in the industry design of Dual 5G Networks capability, VBOX-3611-4L-D5G fulfills applications needs of blazing fast mobile internet connection through aggregating networks and secondary 5G connection for redundancy in modern transportation, smart production, logistics, manufacturing, and automated guided vehicles (AGVs) sectors.

Software

**Environmental** 

### **Specifications**

System		
СРИ	Intel Gen 6 (Skylake-U) Core i7-6600U CPU	
	Intel Gen 6 (Skylake-U) Core i5-6300U CPU	
	Intel Gen 6 (Skylake-U) Core i3-6100U CPU	
	Intel Gen 6 (Skylake-U) Celeron 3955U CPU	
	CPU Socket type: FCBGA1356	
Memory	Supports up to 2 x SO-DIMM DDR4 2133MHz up to 32GB	
Chipset	Intel 6th Generation Core SoC Processor	
LAN Chipset	3 x Intel i210-AT GbE Controllers	
	1 x i219LM (support iAMT and PXE support) GbE Controller	
Audio	Realtek HD Codec Onboard	
Watchdog	Watchdog Timer Support, Offer 1 – 255 Step	
TPM	2.0	
1/0		
Serial Port	2 x RS 232/422/485 (with RS-422/485 Auto Direction Control)	
USB Port	4 x USB 3.2 Gen1 Type A	
	4 x RJ-45 for GbE (LAN 1 with iAMT and PXE support)	
LAN	Optional 4 x M12 X-code for GbE (LAN 1 with iAMT and PXE support)	
Video Port	1 x DVI-I Single link*, 1 x DP 1.2, 1 x VGA *Use only with Single link DVI cables.	
DIO Port	4 x DI (5~48VDC) and 4 x DO (12VDC, 100mA)	
Audio	1 x Line out , 1 x Line-in	
SIM Card Socket	2 x SIM Card Sockets (Onboard with Pin eject)	
Expansion Bus	$1\times M.2$ 2230 A-E Key, $2\times M.2$ 3042/52 B Key (USB 3.0 only), $2\times Full$ Mini-PCle (full function)	
Graphics		
Graphics	Intel UHD Graphics 520 (for i7, i5, and i3)	
	Intel UHD Graphics 510 (for Celeron)	

Operating Temp.	-40°C ~ 70°C, ambient w/ 0.6m/s airflow  Patent No. : M448011 - Thermal Cooling	
Storage Temp.	-40°C ~ 85°C	
Relative Humidity	10% RH – 90% RH (non-condensing)	
Vibration	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis	
(with SSD)	MIL-STD-810G, Method 514.6, Procedure I, Cat.4, Operating	
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD	
Certifications	CE, FCC Class A, E13, EN50155, EN45545-2 (R25) (The input Negative connects with chassis Ground)	
Storage		
Tune	2 x 2.5" Drive Bay for SATA Type HDD/SSD RAID 0, 1, 5	
Туре	1 x M.2 M key 2280 slot supports M.2 SATA SSD	
Power Requirement		
Power Input	9V - 48V DC Power Input	
Power Protection	Automatics Recovery Short Circuit Protection	
Power Mgmt.	Vehicle Power Ignition for Variety Vehicle	
Power Off Control	Power off Delay Time Setting by Software and BIOS	
Battery (UPS)	Internal Battery Kit for 10 Mins Operating (Optional)  *UPS backup time varies depending on actual overall system power consumption.  Patent No.: M447854 - Build-in Battery	
Mechanical		
Construction	Aluminum Alloy	
Mounting	Supports Both of Wall-mount/VESA-mount	
Weight	2160 g (Barebone)	
	250 x 150 x 55 mm	


All specifications are subject to change without notice.




VBOX-3611-4L-D5G

### **Dimensions**

Unit: mm







Please Scan The QR Code For More Information

## **Ordering Information**

Part Number	VBOX-3611-4L-D5G, option for i5/i3/C1	
Description	Intel Gen 6 Core i7-6600U CPU with 4 x GbE LAN On-Board Computer with Dual 5G Modem Capability	
State of Origin	Made in Taiwan	

### **Optional Accessories**

•	
DRAM	SO-DIMM max.DDR4-2133,4GB~32GB,0~70°C/-40~85°C
SATA SSD	2.5inch MLC/TLC 64GB~1TB 0~70°C/-40~85°C
SATA DOM	MLC 8GB~128GB, 0~70°C/-40~85°C
Wifi	M.2 A-E key 2230, 802.3a/b/g/n/ac
Modem	Dual 5G Sub 6 modem
GPS	GPS miniPCle card
CANBUS	CANBUS miniPCle card
Battery backup kit	BAT-3610 kit, 1150mAH 3S1P Battery kit (-30~60°C)
Power adapter	Power Adapter 12V/5A 60W Jack

All specifications are subject to change without notice.



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

#### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

#### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660