

# LMP-1204G-SFP-bt-T-BOS

12-Port Industrial Gigabit IEEE 802.3bt PoE++ Light Layer 3 Managed Ethernet Switch, with 4\*10/100/1000Tx (90W/Port), 4\*10/100/1000Tx (30W/Port), and 4\*100/1000 SFP Slots; EOT: -40°C to 75°C



## Features


- ▶ Supports 4\*10/100/1000Tx IEEE 802.3bt Compliant with 90W/Port, 4\*10/100/1000Tx IEEE 802.3af/at Compliant with 30W/Port, and 4\*100/1000 SFP Slots
- ▶ Network Redundancy Support: RSTP/MSTP, and G.8032 ERPS v1/v2 (Recovery Time <50ms)
- ▶ Configuration: Web Console, Telnet, CLI Command
- ▶ Supports IGMP v1/v2/v3, up to 1024 Groups
- ▶ Supports QoS (IEEE 802.1p) and CoS/ToS
- ▶ Supports IEEE 802.1Q VLAN, SNMP v1/v2c
- ▶ Power Input: 48~55VDC in 6-Pin Terminal Block
- ▶ Reverse Polarity Protection
- ▶ IP30 Protection
- ▶ DIN-Rail or Wall Mountable
- ▶ Operating Temperature Range – EOT: -40°C to 75°C
- ▶ 5-Year Warranty

## INTRODUCTION

Antaira Technologies' LMP-1204G-SFP-bt-T-BOS is a 12-port industrial Gigabit PoE++ managed Ethernet switch embedded with 4\*10/100/1000Tx Ethernet ports that support IEEE 802.3bt for a maximum of 90W/port, 4\*10/100/1000Tx Ethernet ports with IEEE 802.3af/at support for a maximum of 30W/Port, and 4\*100/1000 dual rate SFP slots for fiber connection. The LMP-1204G-SFP-bt-T-BOS is a fully-manageable Light Layer 3 Ethernet switch that is pre-loaded with a user-friendly web management console design. It supports the ring network redundancy function using the market's open standard ITU-T G.8032 Ethernet Ring Protection Switch (ERPS) protocol that has a <50ms network recovery time. The advanced network filtering and security functions, such as IGMP, VLAN, QoS, SNMP, RMON, Modbus TCP, and 802.1X/HTTPS/SSH/SSL increase determinism and improve network management for remote SCADA systems or control networks.

The LMP-1204G-SFP-bt-T-BOS is IP30 rated, DIN-rail mountable, and supports an extended temperature range (EOT: -40°C to 75°C). It also provides high industrial networking applications, such as power/utility, water wastewater, oil/gas/mining, factory automation, security surveillance, ITS and any other outdoor or harsh environment.

## DIMENSIONS



## SPECIFICATIONS

<b>Technology</b>		<b>Protection</b>	
<b>L2 Switching</b>	Port/MAC/Protocol/IP Subnet-based VLAN, GARP/GVRP, Loop Guard, Link Aggregation static/LACP, BPDU guard, Error disable recovery, IGMP snooping v1/v2/v3, MLD snooping v1/v2, IGMP filtering, IPMC throttling / filtering leave proxy, DHCP snooping, G.8032 v1/v2	<b>Network Cable</b>	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m) 1000Base-TX: 4-pair UTP/STP Cat.5/5E cable; EIA/TIA-568 100-ohm (100m)
<b>L3 Switching</b>	DHCP option82, static routes	<b>Mechanical Characteristics</b>	
<b>QoS</b>	802.1p Queueing, Input priority mapping, Storm control for Unicast/Multicast/Broadcast, Port/Queue/ACL policer, Port egress shaper, Queue egress shaper, DiffServ (DSCP), Tag remarking, Scheduler mode	<b>Housing</b>	Metal, IP30 protection
<b>Power Saving</b>	ActiPHY, PerfectReach, IEEE 802.3az EEE power management	<b>Dimensions</b>	54 x 142 x 99mm (W x H x D)
<b>Network Redundancy</b>	STP/RSTP/MSTP, port trunk with LACP, ERPS v1/v2 (<50ms)	<b>Weight</b>	Unit: 2.38 lbs Shipping: 3.07 lbs
<b>Configuration</b>	Http, Https, Telnet, SSH, CLI, TFTP, SNMP v3	<b>Mounting</b>	DIN-Rail Mounting, Wall Mounting
<b>System / Diagnostics</b>	Dual Image Protection, PING, PING6	<b>Power Requirement</b>	
<b>Switch Properties</b>		<b>Input Voltage</b>	48-55VDC Redundant Power Inputs (53~55VDC power input for bt PoE PSE) (DC to AC power supply sold separately)
<b>Switch Architecture</b>	Back-Plane (Switching Fabric): 24Gbps IPv4/IPv6, SNMP v1/v2c/v3, LLDP, LLDP-MED, HTTP, HTTPS, SSHv2 telnet, DHCP client, DHCPv6 client, DHCP server, Port Mirror, DNS client/proxy, IP based Access Filter, ICMPv6, syslog, Time Zone /Daylight Saving, NTP client, RMON, sFlow, Loop detection, Console Port, USB configuration backup/restore, Power lost warning, relay trigger	<b>Power Connection</b>	Removable 6-Contact Terminal Block
<b>Protocols</b>		<b>Relay Contact</b>	24VDC, 1A resistive
<b>Priority Queues</b>	8	<b>PoE Pin Assignment</b>	V-, V-, V+, V+ for pin 1, 2, 3, 6; V+, V+, V-, V- for pin 4, 5, 7, 8 *Support Modes: Mode A, Mode B, 4-Pair Mode
<b>Processing Type</b>	Store and Forward	<b>Overload Current Protection</b>	Present
<b>Flow Control</b>	IEEE 802.3x for full duplex mode, back pressure for half duplex mode	<b>Reverse Polarity Protection</b>	Present
<b>Transfer Rate</b>	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port	<b>System Power Consumption</b>	12.5W
<b>Packet Buffer</b>	4Mbits	<b>PoE Power Budget</b>	240W @48-55VDC
<b>Jumbo Frame</b>	9.6Kbytes	<b>Environmental Limits</b>	
<b>MAC Table Size</b>	8K	<b>Operating Temperature</b>	-40°C to 75°C
<b>VLAN Group</b>	4095	<b>Storage Temperature</b>	-40°C to 85°C
<b>IGMP Group</b>	1024	<b>Ambient Relative Humidity</b>	5% to 95%, (non-condensing)
<b>Port Interface</b>		<b>Regulatory Approvals</b>	
<b>Ethernet Port</b>	8*10/100/1000Base-TX (90W/Port for Port 1~4, 30W/Port for Port 5~8), auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	<b>EMI</b>	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
<b>SFP Port</b>	4*100/1000 SFP Slots	<b>EMS</b>	CE EN55035/EN61000-6-2 Class A: IEC61000-4-2,3,4,5,6,8
<b>RS232 Serial Console</b>	1*RS232 in RJ45	<b>Free Fall Shock</b>	IEC60068-2-32
<b>LED Indicators</b>	System: Power 1, Power 2, Master (M), Ring (R), Status, PoE Load (P/L) Ethernet ports: Speed/Link/Active PoE: On-connected to PD devices SFP: Link/Active	<b>Vibration</b>	IEC60068-2-6
		<b>Green</b>	RoHS Compliant
		<b>Certifications</b>	FCC, CE
		<b>Warranty</b>	5 Years

## ORDERING INFO

<b>LMP-1204G-SFP-bt-T-BOS</b>	12-Port Industrial Gigabit IEEE 802.3bt PoE++ Light Layer 3 Managed Ethernet Switch, with 4*10/100/1000Tx (90W/Port), 4*10/100/1000Tx (30W/Port), and 4*100/1000 SFP Slots; EOT: -40°C to 75°C
-------------------------------	--

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660