



UTS-404AK 4-Port RS-232 to USB Adapter with Screw Lock



Features

- Provides 4 RS-232 Serial Ports over USB Port
- Provides 4 DSUB-9 Connectors
- USB Screw Lock Mechanism Enhances the Reliability
- Rigid Metal Case for Critical Applications
- Baud Rate up to 921.6Kbps
- Supports 7,8 Data Bits
- Odd, Even, Mark, Space, or None parity mode
- Supports 1, or 2 Stop Bits
- Supports USB Bus Power
- DC Jack for Optional DC 5V Power Input
- Supports Windows 98, Me, XP, 2000, 2003, 7, 8, 8.1, 10, CE, Linux

Description

The UTS-404AK is a 4-port RS-232 to USB serial adapter that is designed for PC, thin client, or server to provide instant COM port expansion via the Universal Serial Bus (USB).

It supports screw lock features for the upstream (USB type B) connector with the screw lock USB cables. It prevents from disconnecting the USB cables accidentally.

The UTS-404AK provides the scalability to quickly adapt to new USB technologies. Multiple modules can be added to a single USB interface allowing you to add RS-232 connectivity as needed. Complete product line of many choices help you to expand and make your network grow with your requirements.

With the USB Plug-and-Play feature, simply plug in, follow the instructions of Install Wizard, and then you are done. You don't have to deal with Card Slots, I/O address, IRQ jumpers, DMA and others when you are connecting the devices. The System will recognize the device and install the drivers automatically. The UTS-404AK is an ideal solution for your expanding applications.



UTS-404AK 4-Port RS-232 to USB Adapter with Screw Lock

Specifications

USB Port

Fully compatible with USB1.0 and USB1.1; Forward compatible with USB2.0, the USB connector equips the Screw Lock Mechanism

Serial Port

Supports 4 DB9-Male UART Serial ports, the key benefits are:

- Data Rate up to 921.6Kbps
- Supports 7,8 Data Bits
- Odd, Even, Mark, Space, or None parity mode
- Supports 1 or 2 Stop Bits
- Rigid Metal Case for Critical Applications

OS Support

Windows 98, Me, XP, 2000, 2003, 7, 8, 8.1, 10, CE, Linux

Power Requirements

- Normally Power solely from USB Bus, no external power supply needed.
- +5V DC Jack Input for supports Power over DB9-Male applications.

Environment

Operating Temp.: 0° to 55° C (32° to 131° F)

Storage Temp: -20° to 85° C (-4° to 185° F)

Operating Humidity: 5 to 95% RH

Form Factor

5.90"(L)x2.61"(W)x1.02"(H) (15.00 x 6.65 x 2.60 cm)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660