



## OFF-15W38

15.6" Full-HD PCAP Multi-Touch Fanless Open Frame Panel PC with Intel® Core™ SoC i7/i5/i3 & Celeron® BGA Processor

- > 15.6" Full-HD Open frame panel PC with PCAP TouchOnboard Intel® Core Soc i7/i5/i3 & Celeron® BGA Processor
- > 2 x 260-pin DDR4 3200 MHz SO-DIMM
- > supports up to 64GB 1 x M.2 Type B 3042/3052/2242/2260/2280 (with 1 x PCIe x1 (default) or SATA, USB 3.0 with 1 x SIM card slot, support WWAN+GNSS or NVMe SSD
- > 2x GbE LAN, 4 x USB 3.0, Line-out, Mic-in, 1 x COM, DP++, HDMI/DP
- > Option for 4 x COM, 3 x USB 2.0
- > 16bit GPIO
- > TPM 2.0
- > Slim & Strength Design
- > Fanless Operation from 0° ~ 45°C
- > Wide Voltage Input +12 ~ 24V DC
- > Option for Wi-Fi & BT function

### Spec

-System Information-	
Processor	Onboard Tiger Lake U 11th Intel® Core™ SoC i7/i5/i3 & Celeron® BGA Processor
System Memory	Default with 4GB DDR4 Memory Option supports up to 64GB DDR4 3200MHz SO-DIMM
I/O Chipset	EC ITE IT8528
BIOS Information	AMI uEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
CPU Cooler (Type)	Fanless Heatsink
Board	EMX-TGLP
Expansion	
Expansion	1 x M.2 (2230) E-Key support WiFi module
Storage	
Storage	Default with 128GB M.2 SATA Reserve space for 1 x 2.5" SSD (by option)
Other Storage Device	Reserve space for 1 x 2.5" SSD (by option)
Panel	
LCD Size	15.6", 16:9
Display Type	Full HD
B/L Inverter/Converter	LCD built in
Resolution	1920 x 1080
Pixel pitch	179.25um(H) x 179.25um(V)
Luminance	220 cd/m²
Contrast ratio	800
Viewing angle	85 (U), 85 (D), 85 (L), 85 (R)
Response time	30 ms
Backlight	LED
Touch Type	Projective Capacitive Multi-Touch supports up to 10 points
Touch Light Transmission	89 %
Touch Controller	EETI
I/O	
USB Port	4 x USB 3.0 2 x USB 2.0 (option)
COM Port	1 x RS232(default)/RS422/485, 4 x RS232(option, pin9 without power)
GPIO	16bit GPIO
Expansion	1 x M.2 (2230) E-Key support WiFi module
Other	6 x Antenna Mounting with Dust Cover (Reserve)
DC In/Out Characteristics	
Power Type	AT/ATX
Display	
Graphic Chipset	Intel® HD Graphics 500
Spec. & Resolution	2 x DP++: 1920 x 1080@60 Hz
Audio	
Audio Codec	Realtek ALC897
Audio Interface	Mic-in, Line-out
Audio Amplifier	2 x Stereo Class-D 3W Audio Amplifier
Certifications	
Certification Information	CE / FCC Class A
Ethernet	
LAN Chipset	1 x Intel® I219LM Gigabit Ethernet PHY (LAN1) 1 x Intel® I225LM 2.5 Gigabit Ethernet (LAN2)



<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ45
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	0°C ~ 45°C
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	387 x 235 x 48 mm
<b>Weight</b>	4.9 Kgs
<b>Vibration Test</b>	With M.2 SATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 0.5hr/axis
<b>Shock Test</b>	Operating with M.2 SATA : IEC 60068-2-27 testing procedures, 10G for operation mode
<b>Mounting Kit</b>	Panel / Wall Mount with mounting kits, VESA 100mm x 100mm
<b>Power Requirement</b>	+12V~24V DC in 3 pins Phoenix connector and Power Din DC Jack Extend Power Connector for Reset
<b>Power Mode</b>	AT/ATX
<b>System Fan</b>	Fanless
<b>Relative Humidity</b>	0~90% Relative Humidity, Non-condensing
<b>Fanless</b>	Yes
<b>Drop</b>	ISTA 2A, IEC-60068-2-32 Test:Ed
<b>Software Support</b>	
<b>OS Information</b>	Windows 10 IoT, Linux
<b>Ordering Information</b>	
<b>Ordering Information</b>	<p>OFP-15W38-630-A1R 15.6" Full-HD Multi Touch Open Frame Panel PC / Intel Celeron 6305E, 4GR,128GB M.2 SATA,4xUSB3,COM,2xLAN,2xDP++ without adapter</p> <p>OFP-15W38-111-A1R 15.6" Full-HD Multi Touch Open Frame Panel PC / Intel Core i3, 4GR, 128GB mSATA,4xUSB3,COM,2xLAN,2xDP++ without adapter</p> <p>OFP-15W38-114-A1R 15.6" Full-HD Multi Touch Open Frame Panel PC / Intel Core i5, 4GR, 128GB mSATA,4xUSB3,COM,2xLAN,2xDP++ without adapter</p> <p>OFP-15W38-118-A1R 15.6" Full-HD Multi Touch Open Frame Panel PC / Intel Core i7, 4GR, 128GB mSATA,4xUSB3,COM,2xLAN,2xDP++ without adapter</p> <p>ACC-ADP-090N-06R AC/DC adapter 24V/3.75A PWR DIN Plug</p> <p>E1702031835R USA Power Cord</p> <p>E170203183DR EU Power Cord</p> <p>E170203183BR Japan Power Cord</p> <p>E170203183ER UK Power Cord</p> <p>E1702031800R Australia Power Cord</p>

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660