IEOUSYS

TECHNOLOGY

Rugged Embedded

(€ F©

Introduction

Industrial-grade x86-based IIoT Gateway with Dual Gigabit Ethernet LAN, 4 COM, 4 USB and Pre-installed Debian

IGT-124 is an x86-based industrial-grade IoT gateway that accepts wide DC voltage input range from 8 to 35VDC and supports wide operating
temperature from -25°C to 70°C. As a member of Neousys IGT series, IGT-124 is shipped as a complete system with pre-installed Intel® Atom™ Bay
Trail, DDR3L RAM, data storage capacity and Ubuntu operating system.

🖊 Key Features

· Two Gigabit Ethernet LAN ports

Contact Neousys

· Intel[®] Atom[™] E3826 1.46GHz dual-core processor

Up to two RS-232/422/485 ports and two RS-232 ports
Compact design with 150 mm x 100 mm foot-print

Rugged, wide temperature range from -25°C to 70°C fanless operation

Get Quote

To acquire data, IGT-124 features 4 COM, 4 USB and 2 Gigabit Ethernet ports to connect to a variety of industrial devices. It also has a DVI-I connector for video output, allowing it to display dashboard statistics or aid in maintenance, if necessary. For ease of deployment, IGT-124 can choose between two mounting options, wall or DIN-rail mounting. Of the two, the DIN -rail kit provides a rugged clamping force to resist vibration and shock during operation. Communication wise, IGT-124 provides a PCIe mini socket for WiFi or LTE modules. Neousys offers an LTE connectivity solution that is precertified to operate on AT&T and Verizon networks.

Besides the standard hardware design, Neousys also provides a highly customizable service with IGT-124. Customizations such as CIS branding, color bands on the chassis, preloaded IIoT software or customize a tailor-made OS image. This service not only offers greater capability and compatibility for deployment but also a more personalized solution matching your company's image and specific needs.

As with the nature of industrial IoT applications, the gateway will be expected to and is more than capable of operating 24/7 in extreme or harsh environments for fragmented applications. The reliable hardware design and open-source software development environment make IGT-124 an effective and quick time-to-market solution that requires minimum human intervention for a variety of industrial IoT applications.

Specifications

System Co	ore	Power Supply	
Processor	Intel [®] Atom™ E3826 1.46 GHz dual-core processor	DC Input	1x 2-pin pluggable terminal block for built-in 8~35 VDC DC input
Graphics	Integrated Intel [®] HD Graphics	Mechanical	·
Memory	Single-slot pre-installed 2GB SODIMM DDR3L-1333	Dimension (W	149 mm (W) x 105 mm (D) x 58 mm (H)
Storage	1x 32GB 2.5" SSD	x D x H)	149 mm (W) x 105 mm (D) x 38 mm (H)
Panel I/O	Interface	Weight	1.0 kg
Ethernet	2x Gigabit Ethernet ports by Intel [®] I210 GbE controller	Mounting	Optional wall and DIN-rail mounting
	VGA and DVI dual display outputs via DVI-I connector,	Environmental	
Video Port	supporting up to 2560 x 1600 resolution	Operating	-25°C ~ 70°C with SSD , 100% CPU loading
Serial Port	2x software-programmable RS-232/422/485 (COM1 & COM3),	Temp. Storage Temp.	-40°C ~85°C
Schurrore	2x RS-232 (COM2 & COM4)		
USB 3.1	1x USB 3.0 ports		
USB 2.0	3x USB 2.0 ports	Humidity	10%~90% , non-condensing
Expansion	Bus	Vibration	Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64)
Mini-PCle	1x mini PCI Express slot with USIM socket	Shock	Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
		EMC	CE/FCC Class A, according to EN 55024 & EN 55032









NEOUSYS IGT-124 TECHNOLOGY Appearance LED Indicators (Power, HDD, WDT, IGN) USB 3.1 x 2 USB 3.1 x 1 COM1 ~ COM4 DVI-I 8-35V DC IN GbE F USB 2.0 x 1 t x 2 9 **Dimensions** Unit : mm 149 105

Ordering Information

Model No.	Product Description
IGT-124	Industrial grade x86-based IIoT Gateway with 2 Gigabit Ethernet LAN ports, 4 COM ports, 4 USB ports

58

Optional Accessories

PA-60W-OW 60W AC/DC power adapter with 12V, 5A DC output, cord end terminals for terminal block. operating temperature: -30 to 60 °C.

Optional Cellular Module

NSIO-LTE-7455 Cat. 6 LTE embedded socket modem

```
www.neousys-tech.com
```



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660