



Data Sheet RSM-Ex 01

Remote Speaker

Microphone for Zone 1/21



Ⓜ II 2G Ex ib IIC T4 Gb
Ⓜ II 2D Ex ib IIIC T135°C Db IP64
Ⓜ I M2 Ex ib I Mb



Ex ib IIC T4 Gb
Ex ib IIIC T135°C Db IP64
Ex ib I Mb



CI, II, III, Division 1, Groups A-G, T4, T135°C
CI I Zn 1, AEx ib IIC T4 Gb
CI II Zn 21, AEx ib IIIC T135°C Db
CI I, Zn 1, Ex ib IIC T4 Gb
CI II, Zn 21, Ex ib IIIC T135°C Db

Technical Data

Loudspeaker performance	Up to 103 dB			
Power supply	Li-Ion 2200 mAh			
Charging	- Charging cable and docking station with magnetic charging plug: similar concept to Smart-Ex® 01 or Ident-Ex® 01. A docking station without any electronics and a mounting option for the charging plug. - Optical charging level indication (multiple LEDs)			
Connector	- Plug, 3.5 mm, 4-pin, straight, with lock (Smart-Ex® 01 / Ex-Handy 09) or - Plug, 3.5 mm, 4-pin, right-angled or - Plug, 3.5 mm, 4-pin, straight or - Plug, 3.5 mm, 4-pin, straight, Next Generation (Smart-Ex® 02 / Ex-Handy 10) or - Plug, 3.5 mm, 4-pin, right-angled, Next Generation (Ex-Handy 10)			
Connection	Socket, 3.5 mm, for headset			
Buttons	- PTT button operable with thick gloves - Front-facing multi-function button - Volume up / down - Red Button			
Features	- Lone worker ready (Red Button) - IOT ready (4 standard Google intents usable and/or optional 4 additional Android Intents) - Build in NFC Technologie			
Run times**	Use time in % with typical user profiles speak/hear/standby	Noisy areas with sound level above 100 dB	Noisy areas with sound level between 84 and 100 dB	Noisy areas with sound level up to 84 dB
	5 / 5 / 90	-> 55 h	-> 72 h	-> 72 h
	25 / 25 / 50	-> 28 h	-> 70 h	-> 71 h
	50 / 50 / 0	-> 17 h	-> 67 h	-> 69 h
		Highest noise level (8/8)*	Very high noise level (4/8)*	High noise level (2/8)*
*There are 8 different volume levels possible. **determined runtimes on the Smart-Ex® 01 based on RSM-Ex 01 software version V 16				
Standby time	Approx. 75 hours after commissioning via the 3.5 mm jack of an Android or Windows device			
Temperature range	Ta = -20...+55°C			
IP rating	IP 64 according to EN/IEC 60079-0 (ATEX/ IECEx) IP 65 / 67 according to EN/IEC 60529 (industrial standard)			
Accessories	- Removable belt clip - Charging cable - Docking station (optional) - Connection of additional headsets (optional)			

Your automation, our passion.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660