



EMS-EHL

Intel® Celeron®/Atom™ SoC Processor J6413/x6425E Fanless Rugged Embedded System

- > On board Intel® Celeron®/Atom™ J6413/x6425E SoC BGA Processor
- > 1 x 260-pin SODIMM socket Max. up to 32GB DDR4 3200MT/s
- > Rich I/O, 4-USB3.2, 1-DP, 1-HDMI, 2-COM, 2-LAN, 1-8bit GPIO.
- > Support 5G (Sub-6G) module, HDMI 2.0b (4K @ 60Hz), LAN 2.5G Base-Tx GbE
- > Fanless operation temperature from -40°C ~ 70°C (WT) / 0°C ~ 65°C (ST)
- > CE, FCC Class B, LVD 62368-1, IP50
- > Wide range DC power input from +9~36V
- > Support HW TPM 2.0
- > Support IET modules

Spec

System Information	
Processor	Intel® Celeron® Processor J6413 (1.5M Cache, up to 3.00Ghz), ST, Tj=105°C Intel® Atom® Processor x6425E(1.5M Cache, up to 3.00Ghz), WT, Tj=-40°C ~105°C
System Memory	1 x 260-pin SODIMM socket Max. Up to 32GB DDR4 3200 MT/s
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	CPU & system temperature monitoring and Voltages monitoring
TPM	TPM 2.0
SBC	EBM-EHLS
-Expansion-	
M.2	1 x M.2 Key-B 2242/3042/3052 support SATA3/ PCIe III/ USB3.2 Gen.1 and SIM slot1 (internal), default support 3.3V, jumper setting to adjust 3.3V/3.8V 1 x M.2 Key-E 2230 for Wi-Fi & BT Module (USB2.0/ PCIe III)
IET	1 x IET interface (1 x DDI, 4x PCIeIII x1, 3 x USB2.0, 1 x Line-Out(R/L), 1 x SMBus, LPC)
-Storage-	
M.2	1 x M.2 Key-B 2242/2280, support SATA 1 x M.2 Key-B 2242, support SATA (share with expansion slot)
-Front I/O-	
COM Port	2 x COM RS232/422/485 (select via BIOS, auto flow control via HW)
Power Button	1 x Push Button for Power on/off
Reset Button	1 x Push Button for Reset
Wire-Control Power On/Off	1 x 2-Pin Terminal Block for wire-control power on/off
LED Indicator	1 x Power LED (Blue) 1 x Storage LED (Yellow)- M.2 B-key SATA 1 x LTE LED (Green)- M.2 B-key PCIe 1 x Wifi LED (Green)- M.2 E key
Digital I/O	1 x 8-bit GPIO (DB9)
Antenna	2 x Antenna with dust cover
-Rear I/O-	
USB Port	2 x USB 3.1 Gen.2 (10Gbp/s) 2 x USB 3.1 Gen.1 (5Gbp/s), via USB Hub
HDMI	1 x HDMI 2.0b
DP	1 x DP 1.4
Audio	1 x Mic-In, 1 x Line-Out
RJ-45	2 x RJ45
Antenna	2 x Antenna with dust cover
-Right I/O-	
Antenna	2 x Antenna with dust cover
-Left I/O-	
Antenna	2 x Antenna with dust cover
-Display-	
Graphic Chipset	Intel® UHD Graphics for 10th Gen Intel® Processors
Resolution	DP++ 1.4: 4096x2304 @ 60Hz HDMI 2.0b : Max. resolution 4096x2304 @ 60Hz
-Audio-	
Audio Codec	Realtek ALC888S (co-lay with ALC897) HD codec
-Ethernet-	
LAN Chipset	2 x Intel I226-IT
Specification	2x 10/100/1000/2.5G Base-Tx GbE compatible
-Power Requirement-	
DC Input Voltage	DC in typical 12/24V (+9V ~ +36V), wide voltage single power input TVS component for surge protection Reverse current/voltage protection (Max. Currency: 13A)



DC Input Connector	3-Pin Terminal Block (V+, V-, GND)
ACPI	Single power ATX Support S0,S3, S4, S5 ACPI 5.0 Compliant
Power Mode	AT/ATX (ATX is default setting)
-Software Support-	
OS Information	Win 10 64bit / Win 11 64 bit/ Linux
-Certification-	
Certification Information	CE, FCC Class B, LVD 62368-1
Mechanical & Environmental	
Operating Temperature	-40°C ~ 70°C (w/SSD) ambient w/ 0.5 air flow, WT sku, x6425E -40°C ~ 60°C (w/SSD) ambient w/ 0.2 air flow, WT sku, x6425E 0°C ~ 65°C (w/SSD) ambient w/ 0.5 air flow, ST sku, J6413 0°C ~ 55°C (w/SSD) ambient w/ 0.2 air flow, ST sku, J6413
Storage Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	240mm x 150mm x 43 mm (Standard) 240mm x 150mm x 64 mm (w/ IET module)
Weight	1.9 kg (System) 2.7 kg (w/ Package)
Vibration Test	With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
Shock Test	With SSD : 55Grms, IEC 60068-2-27, Half Sine, 11ms
IP Rating	IP 50
Mounting Kit	Wall mount kit (standard) DIN RAIL (optional)
Ordering Information	
Ordering Information	EMS-EHL-J64-A1-1R Intel® Celeron® SoC Processor J6413 Fanless Rugged Embedded System EMS-EHL-X64-A1-1R Intel® Atom™ SoC Processor x6425E Fanless Rugged Embedded System

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660