


ICO120-E3350 NEW

DIN-Rail Fanless Embedded System with Intel® Celeron® Processor N3350, COM/CAN/DIO, 2 LAN, 2 USB, HDMI, WT



▲ Front view



▲ Rear view



2 x USB




HDMI

COM/CAN/DIO port

Features

- Extreme cost-effective with fanless and cableless design
- Intel® Celeron® processor N3350, reliable F1 stepping version CPU
- COM/CAN/DIO, 2 USB, and 2 GbE LAN
- Wide operating temperature range from -40°C to +70°C
- 9 to 36 VDC wide range power input (typical: 12-24 VDC)
- OVP, UVP, OCP, RPP power protection design
- eAPI for intelligent remote monitoring software integration



Specifications

Standard Color	Sliver	
Construction	Extruded aluminum and heavy-duty steel, IP30	
CPU	Intel® Celeron® N3350 2C @1.1 GHz, TDP: 6W	
Chipset	SoC integrated	
System Memory	1 x DDR3L-1600 SO-DIMM, up to 8GB	
BIOS	AMI	
System I/O Outlet	DB9 Port	Selection for 2 of DB9: COM (RS-232/422/485) DIO (8-bit Programmable DIO) CAN (CAN 2.0 A/B, 1 Mbps bitrate with SocketCAN & J1939 supported)
	Display	1 x HDMI
	USB	2 x USB 2.0
	Ethernet	2 x RJ-45 isolated GbE Ethernet (Intel® I210-IT) Isolation voltage: 1.5 kV
	Others	2 x Antenna opening
Extension Interface	1 x Full-size Rev. 1.2 PCI Express Mini Card slot: USB/PCIe with SIM socket	
	1 x Half-size Rev. 1.2 PCI Express Mini Card slot: mSATA/USB/PCIe	
Storage	SATA Drive	1 x mSATA (occupied 1 x PCI Express Mini Card slot)
	eMMC	Optional
Watchdog Timer	255 levels, 1 to 255 sec.	
Power Supply	1 x Terminal block, 9 to 36 VDC (typical: 12-24 VDC)	
System Indicator	1 x LED indicator for SATA drive activity	
	1 x LED indicator for power	
TPM	TPM 2.0	
Operating Temperature	-40°C to +70°C (-40°F to +158°F) with W.T. peripheral*	
Humidity	0% to 95%	

Specifications

Vibration Endurance	2 Gms with storage (5 to 500Hz, X/Y/Z direction; random, operating)	
Weight (net/gross)	0.3 kg (0.67 lb)/0.45 kg (0.99 lb)	
Certifications	CE (Class A), FCC (Class A), UL EN 55032 (Class A), EN 55035 FCC part 15 B (Class A)	
EMC	CE/FCC	EN 55035 (Class A), FCC part 15 B (Class A)
Dimensions	31 mm (1.22") (W) x 100 mm (3.93") (D) x 125 mm (4.92") (H)	
EOS Support	Windows® 10 IoT, Linux	
Software Support	eAPI	

* Wide Temperature. All W.T. supported products have to be sorted by Axiomtek.


Ordering Information

ICO120-E3350-A (P/N: E22C120114)	DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 2 COM, 2 GbE LAN, and 2 USB
ICO120-E3350-B (P/N: E22C120115)	DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 1 COM, DIO, 2 GbE LAN, and 2 USB
ICO120-E3350-C (P/N: E22C120116)	DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 1 COM, 1 CAN, 2 GbE LAN, and 2 USB
ICO120-E3350-E (P/N: E22C120117)	DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 1 CAN, 1 DIO, 2 GbE LAN, and 2 USB

Packing List

- 1 x DRAM Thermal Pad
- 1 x 3-pin Terminal Block Connector for Power DC-in
- 1 x DIN-Rail Kit

Dimensions



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660