

iEPF-9032S-EW4
Expandable Edge AIoT Platform

Preliminary



KEY FEATURES

- Intel® 14th Gen Core™ Processors with H610 Chipset
- 2 x 262-pin DDR5 SO-DIMM up to 96GB (48GB per DIMM)
- 1 x PCIe x16 (Up to PCIe Gen5)
- 1 x M.2 Key M, 2 x M.2 Key B, 1 x M.2 Key E
- 4 x USB 3.2 Gen2x1, 2 x USB 2.0, 6 x COM, 4 x SATA3, 8 x DI, 8 x DO
- 4 x Intel 2.5G LAN (2 support PoE)
- 1 x Displayport, 1 x HDMI 2.0b, 1 x VGA
- Powerful Edge AI acceleration enabled by the most flexible mechanical, thermal, and power design, with support for 275mm x 138 mm x 60 mm (L x H x D) max. and up to 600W graphic card

SPECIFICATIONS

Processor System

| | |
|---------|----------------------------------|
| CPU | Intel® 14th Gen Core™ Processors |
| Chipset | Intel® H610 |
| Socket | LGA 1700 |

Memory

| | |
|------------|---------------------------|
| Technology | Dual Channel DDR5 5600MHz |
| Capacity | 96 GB (48GB per DIMM) |
| Socket | 2 x 262-pin SO-DIMM |

Graphics

| | |
|-------------|---|
| Controller | Intel® UHD Graphics |
| DisplayPort | DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz |
| HDMI | HDMI 2.0b Max resolution up to 4096x2160@60Hz |
| VGA | Max resolution up to 1920x1200@60Hz |

Audio

| | |
|-----------|--|
| Interface | Realtek ALC897, High Definition Audio. |
|-----------|--|

Expansion Slot

| | |
|-------------|--|
| PCIe | 1 x PCIe Gen5 x16 (single x16), PCIe x16 slot with default power cable can support up to 180W graphic card (275mm x 113mm x 60mm (L x H x D), if remove the card holder, it can be limited on 275mm x 138mm x 60mm) Graphic card can be up to 600W with optional VGA module |
| RF& Antenna | 8 x SMA connector hole reserved |
| M.2 | 1 x M.2 (Key E, 2230) with CNVI/PCIe Gen3 x1 and USB2.0 for Wi-Fi/BT module 1 x M.2 (Key B1, 2280/3042/3052) with PCIe Gen3 x1 / USB3.2 Gen1x1 and USB2.0 for 4G / 5G 1 x M.2 (Key B2, 3042/3052) with PCIe Gen3 x1 / USB3.2 Gen1x1 and USB2.0 for 4G / 5G |
| SIM Socket | 2 x Nano SIM Card slot (2 connected to M.2 Key B) |

Ethernet

| | |
|-------------------|--|
| Controller/ Speed | 2 x Intel® i226IT 2 x Intel® i226IT (PoE Support, each port supports IEEE 802.3AT PoE, PoE output max. 30W/single port or 30W/two ports shared) |
| Connector | 4 x RJ45 |

Storage

| | |
|----------------|--|
| M.2 | 1 x M.2 (Key M, 2242/2280/22110/25110) with Gen3 x1 for NVMe SSD |
| SATA | 4 x SATA3 (6Gb/s) 4 x 2.5" HDD/SSD Tray (Default 1 piece) |
| CFast (Option) | 1 x Type II socket (Shared with SATA3) |

Front I/O

| | |
|-------------|---|
| DisplayPort | 1 |
| HDMI | 1 |
| VGA | 1 |
| Ethernet | 4 x Intel 2.5G LAN |
| USB | 4 x USB 3.2 Gen2x1, 2 x USB 2.0, 1 x USB2.0 internal connector w/ lock function |
| Audio | 1 x Mic-in, 1 x Line-out |
| COM | 4 x RS232/422/485 (COM1, COM2- optional Card w/ Isolation Protection, COM5- Isolation Protection, COM6) |
| DIO | 2 x RS232 (COM3, COM4) 8DI/8DOs |

Watchdog Timer

| | |
|----------|----------------------------------|
| Output | From Super I/O to drag RESETCON# |
| Interval | 256 Segments, 0, 1, 2, ...255sec |

Power Requirements

| | |
|-----------|---|
| Input PWR | 9V~36V VDC with Ignition control and remote power on/off switch. 80V Surge Protection, OVP, UVP, OCP and reverse protection Ignition Power Input w/ 13-mode condition |
|-----------|---|

Environment

| | |
|-----------------------|--|
| Operating Temperature | 35W CPU: -40°C~75°C (-40°F~167°F) 46W~65W CPU: -40°C~55°C (-40°F~131°F) (with FAN inside, without Add-on Card) (w/ air flow 0.5~0.8 m/s) |
| Storage Temperature | -40°C~85°C (-40°F~185°F) |
| Humidity | ~95% @ 40°C (non-condensing) |
| Shock | Operating: 50 G, half sine 11ms duration with SSD |
| Vibration | Operating: 5 Grms, 5~500 Hz, 3 axes with SSD |
| ESD | Contact +/-4kV, Air +/-8kV |
| EMC | EN61000-6-4/-2, CE & FCC Class A |
| Safety | LVD |

Mechanical

| | |
|--------------|--|
| Construction | Aluminum heatsink + Metal chassis |
| Mounting | Desk Mount |
| Dimensions | 201.7mm (W) x 290.8mm (D) x 209.8mm (H) (7.94" x 11.45" x 8.26") |
| Net Weight | 10kg |

Others

| | |
|----------------------|------------------------------|
| OS Support | Windows 10 & Linux |
| TPM | TPM 2.0 |
| Real-Time Enablement | TSN, TCC support under YOCTO |

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660