

ADAM-4510/S ADAM-4520 ADAM-4521

RS-422/485 Repeater

Isolated RS-232 to RS-422/485 Converter

Addressable RS-422/485 to RS-232 Converter



Specifications

General

- 2 x plug-in terminal blocks Connectors (#14~22 AWG)
- (RS-422/485)
- Isolation Voltage 3,000 Vpc (ADAM-4510S) Power Consumption 1.4 W @ 24 V_{DC}
- **Serial Communications**
- Input
- Output
- Speed Modes (bps)
 - 1.200. 2.400. 4.800. 9.600. 19.2 k, 38.4 k, 57.6 k, 115.2 k, RTS control and RS-422 (switchable)

RS-485 (2-wire) or

RS-422 (4-wire) RS-485 (2-wire) or

RS-422 (4-wire)



Specifications

General Connectors

- Isolation Voltage
- Power Consumption 1.2 W @ 24 V_{DC}

Serial Communications

- Input
- Output
- Speed Modes (bps)
 - 1.200. 2.400. 4.800. 9.600. 19.2 k, 38.4 k, 57.6 k, 115.2 k, RTS control and RS-422 (switchable)

1 x plug-in terminal block

(#14 ~ 22 AWG)

1 x DB9-F (RS-232)

(RS-422/485)

RS-232 (DB9)

RS-485 (2-wire) or

RS-422 (4-wire)

3,000 VDC



Specifications

General Connectors

Input

Output

- 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-422/485) 1 x DB9-F (RS-232)
- Isolation Voltage 1,000 VDC
- Power Consumption 1.0 W @ 24 V_{DC}
- · Built-in microprocessor and watchdog timer

Serial Communications

- RS-485 (2-wire) or RS-422 (4-wire) RS-232 (DB9) Speed Modes (bps) 300, 600, 1,200, 2,400,
 - 4.800, 9.600, 19.2 k. 38.4 k, 57.6 k, 115.2 k (software configurable)
- RS-232 and 485 can be set to different baudrates
- RS-485 surge protection and automatic **RS-485 data flow control**
- Software configurable to either addressable or non-addressable mode

Common Specifications

General

Power Input

Environment

- Operating Humidity
- Operating - 10 ~ 70°C (14 ~ 158°F)

5~95% RH

Unregulated $10 \sim 30 V_{DC}$ w/ power reversal protection

Temperature Storage Temperature - 25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- ADAM-4510 ADAM-4510S
- Isolated RS-422/485 Repeater
- Isolated RS-232 to RS-422/485 Converter Addressable

RS-422/485 Repeater

RS-422/485 to RS-232 Converter

Last updated: 7-Jul-2017

RS-485 I/O Modules: ADAM-4000 **AD\ANTECH** All product specifications are subject to change without notice

www.assured-systems.com | sales@assured-systems.com

ADAM-4520 ADAM-4521



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660