

LNX-1604G-SFP Series

16-Port Industrial Gigabit Unmanaged Ethernet Switch, 12*10/100/1000Tx and 4*100/1000 SFP Slots



FEATURES


- ▶ Support 12*10/100/1000Tx and 4*100/1000 SFP Slot
- ▶ Built-in Relay for Power Redundancy Failure Warning
- ▶ RJ45 Port Support Auto MDI / MDI-X Function
- ▶ Auto Negotiation Speed, Half / Full Duplex
- ▶ Store-and-Forward Switching Architecture
- ▶ Redundant Power Input 12~48VDC in 6-Pin Terminal Block
- ▶ Reverse Polarity Protection
- ▶ Overload Current Protection
- ▶ IP30 Protection
- ▶ DIN-Rail or Wall Mountable
- ▶ Operating Temperature - STD: -10°C to 65°C, EOT: -40°C to 75°C
- ▶ 5-Year Warranty



INTRODUCTION

Antaira Technologies' LNX-1604G-SFP Series is a 16-port industrial Gigabit unmanaged Ethernet switch embedded with 12*10/100/1000Tx Ethernet ports and 4*100/1000 SFP Slots. It is IP30 rated and designed with both DIN-Rail and wall mounting options. It is ideal for applications that require high density port connections with wide network bandwidth. The LNX-1604G-SFP series works well in industrial applications such as, security video surveillance, GigE machine vision, process control automation, and intelligent transportation. This product series provides high EFT and ESD protection with a redundant power input support of 12~48VDC. The unit also supports a standard operating temperature from -10°C to 65°C or -40°C to 75°C with the extended temperature version.

DIMENSIONS



SPECIFICATIONS

TECHNOLOGY		POWER REQUIREMENT	
Standards	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Fiber	Input Voltage	12~48VDC Redundant Input
SWITCH PROPERTIES		Power Connection	1 removable 6-contact terminal block
Switch Architecture	Switching Fabric (Back-Plane): 32Gbps	Relay Contact	24VDC, 1A resistive
Processing Type	Store and Forward	Overload Current Protection	Present (Slow-Blown Fuse)
Flow Control	IEEE 802.3x flow control, back pressure flow control	Reverse Polarity Protection	Present
Protocol	CSMA/CD	System Power Consumption	Max 15 Watts full loading
Transfer Rate	14,880pps for Ethernet 148,800pps for Fast Ethernet 1,488,000pps for Gigabit Ethernet	ENVIRONMENTAL LIMITS	
MAC Table Size	8K	Operating Temperature	STD: -10°C to 65°C EOT: -40°C to 75°C
Jumbo Frame	9.6Kbytes	Storage Temperature	-40°C ~ 85°C
Memory Buffer	4Mbits	Ambient Relative Humidity	5 to 95%, (non-condensing)
PORT INTERFACE		REGULATORY APPROVALS	
Ethernet Port	12*10/100/1000Base-TX Auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	EMI	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
SFP Port	4*100/1000 SFP Slots	EMS	CE EN55035/EN61000-6-2, IEC61000-4-2,3,4,5,6,8
LED Indicators	System: Power 1, Power 2, Fault Ethernet ports: On-Link/Flash-data transmitting SFP: Speed/Link/Active	Free Fall	IEC60068-2-32
Network Cable	10BaseT: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100BaseTX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m) 1000BaseTX: UTP/STP Cat. 5/5E cable; EIA/TIA-568 100-ohm (100m)	Shock	IEC60068-2-27
MECHANICAL CHARACTERISTICS		Vibration	IEC60068-2-6
Housing	Metal, IP30 protection	Green	RoHS Compliant
Dimension	67 x 142 x 99 mm (W x H x D)	Certifications	FCC, CE, UL61010-1, UL61010-2-201
Weight	Unit: 2.57 lbs. Shipping: 3.22 lbs.	Warranty	5 Years
Mounting	DIN-Rail mounting, Wall mounting		

ORDERING INFORMATION

LNX-1604G-SFP	16-Port Industrial Gigabit Unmanaged Ethernet Switch, 12*10/100/1000Tx and 4*100/1000 SFP Slots
LNX-1604G-SFP-T	16-Port Industrial Gigabit Unmanaged Ethernet Switch, 12*10/100/1000Tx and 4*100/1000 SFP Slots; EOT: -40°C to 75°C

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660