

AIR6NO-C-MB NX SDVoE-C

YUAN

Al Edge for 10G Copper

Features

- · Powered by NVIDIA® Jetson Orin™ NX Super up to 157 / 117 TOPS
- · Business Card Size
- · Support SDVoE
- · 1×USB3.2 Gen2
- · 1×Mini DisplayPort



Specifications

	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano		
SOM	16GB Super	8GB Super	8GB Super	4GB Super		
СРИ	8-Core Arm® Cortex®-A78AE v8.2 6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3 64-Bit CPU 1.5MB L2 + 4MB L3 66-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3					
GPU	1024-Core NVIDIA Ampere Architecture GPU with 32 Tensor Cores		1024-core NVIDIA Ampere Architecture GPU with 32 Tensor Cores	512-core NVIDIA Ampere Architecture GPU with 16 Tensor Cores		
Al Performance	157 TOPS	117 TOPS	67 TOPS	34 TOPS		
System Memory	16GB 128-bit LPDDR5 102.4GB/s	8GB 128-bit LPDDR5 102.4GB/s	8GB 128-bit LPDDR5 102 GB/s	4GB 64-bit LPDDR5 51 GB/s		
Interface						
Storage	Supports External NVMe					
Display Interface	1×Mini DP1.4					
Ethernet	1×RJ45 for 10/100/1000Mbps Ethernet (DHCP Client)					
Expansion Slot	1×M.2 2230 M Key PCle Gen4×2 Slot (Nano: Gen3×2) 1×M.2 2230 E Key PCle Gen4×1 Slot (Nano: Gen3×1)					
USB	1×USB3.2 Gen2 (Type-C)					
MIPI	8 MIPI CSI-2 Lanes (D-PHY 2.1, Support MIPI Camera, Capture Card)					
Peripheral Communication	10 Pin Header 1×USB2.0 4×GPIO 1×I2C 6 Pin Wafer 1×UART 4 Pin Header 5V / 3A					
Misc. Features	Firmware Upgradable					
Development Environment						
JetPack	6.2 or Higher	6.2 or Higher				
Environment						
Power Supply	DC input : 12~36V					
Power Consumption	TBA					
Operating Temperature	0~60 C with Airflow					
Storage Temperature	-20~80 °C					
Certification	CE, FCC					

Key Points

Video Feature			
Video Input	1×RJ45 for 10Gbps Ethernet (Support SDVoE and DHCP Client)		



SDK / Software

Video Feature								
SOM	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano				
30101	16GB Super	8GB Super	8GB Super	4GB Super				
Video Encode	AV1 (UHP)							
	1×4K60 3×4K30 6×1080p60 12×1080p30		1080p30 supported by 1-2 CPU cores					
	H.265 (UHP)							
	1×4K60 3×4K30 6×1080p60 12×1080p30							
	H.264 (UHP)							
	1×4K60 2×4K30 5×1080p60	11×1080p30						
	AV1 (Main Profile)		AV1 (Main Profile)					
	1×8K30 2×4K60 4×4K30 10×1080p60 20×1080p30		1×4K60 2×4K30 5×1080p60	10×1080p30				
	H.265 (Main, Main10)		H.265 (Main, Main10)					
Video Decode	1×8K30 2×4K60 4×4K30 9×1080p60 18×1080p30		1×4K60 2×4K30 5×1080p60 11×1080p30					
	H.264 (Baseline, Main, High)		H.264 (Baseline, Main, High)					
	1×4K60 2×4K30 5×1080p60 11×1080p30		1×4K30 3×1080p60 7×1080p30					
	VP9 (Profile 0, Profile 2)		VP9 (Profile 0, Profile 2)					
	1×4K60 3×4K30 7×1080p60 15×1080p30			10×1080p30				
SDK								
	Capture							
	High Performance Renderer							
	Image Snapshot							
	De-interlace, Alpha Blending Engine							
	Auto Signal Detection 2D/2D Video Audio and VANC Streams Capture							
	2D/3D Video, Audio and VANC Streams Capture Record							
	Encrypt / Sync / Clone / Recording							
	Time-Shifting / Rewind / Pre-Event / Recording							
QCAP	Multi-Streams (3D) Recording							
200	Animation Transition Effect							
	Video Cropping, Scaling and Alpha Blending Engine							
	Stream							
	2D/3D Universal Stream Client							
	2D/3D Multi-Streams Stream Server							
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)							
	Animation Transition Effect							
	Video Cropping, Scaling and Alpha Blending Engine							
	*Separate License Required							
	AI SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications							
	Face Recognition							
00550	Objects Detection							
QDEEP	Objects Segment Optical Character Recognition							
	License Plate Recognition							
	Customizable Video Al Functions Upon Request							
Software (Optional)	Custoffizubie Video Al i difetions	орон нечисэт						
Software (Optional)	W.I. B III I f							
	Web Based User Interface		Schaller .	And				
Xtreamer	Encode / Decode							
	AV1, H.26X							
	Color Format Adjust 444 / 422 / 420 10Rit / SRit Select							
	444 / 422 / 420, 10Bit / 8Bit Select							
	Record MP4, TS		Transition of the second of th	Since				
	Stream / Network							
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*) *Separate License Required							
	separate actions negulined							

Mechanical

· Dimension: $90\text{mm} \times 55\text{mm}$

 \cdot Weight: 226g (With SOM and Fan)

Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.

^{*} All registered trademarks are the property of their owners. The photo is for reference only.

^{*} Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660