

## Digital Signage Displays

# PDX75UF86/4





## **Key Features**




#### **Operation Time Support**

Professional Panels used with this series are quality confirmed to operate 24 hours a day without any issues. Upon this, the series come with 2500 Nits brightness levels suitable for indoor and semi-outdoor environments.



#### **Optional OPS Support**

All our products in this series have an optional OPS (Open Pluggable Standard) slot. OPS will empower your screens with enhanced processing power and ability to choose Windows or Android as your operating system to fit your specific application.



#### **Daisy Chain**

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



#### **External Device Connections**

You may want to connect your teleconference system, screen sharing system, set-top box or external PCs via HDMI port. For this purposes, our monitors help you to maximize user experience with HDMI CEC (Consumer Electronics Control) and HDMI Hotplug capabilities.



### **Open Platform Support**

Our SoC supports API (Application Programming Interface) for solution providers/integrators to develop and integrate any HTML5-based to be installed and used on our displays.



#### Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



#### Panel

Screen Size	75"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	1000 cd/m <sup>2</sup>
Native Resolution	3840 x 2160 (16:9) - UHD	Contrast Ratio (typical)	1200:1
Dynamic Contrast Ratio	100000:1	Panel Life Time ( Min. )	50000 Hrs
Response Time (typical)	8 ms	Active Area (H x V)	1650 x 928 mm
Pixel Pitch (H x V)	0.429 x 0.429 mm	PPI (pixel per inch)	59
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07 B (10-bit)
Screen Treatment	2H	Haze Level	3%
Refresh Rate	60 Hz	Front Type	Ultra Narrow Bezel
Orientation	Horizontal / Vertical	Operation Hours	24/7
Area of Usage	Indoor		

## Built-in System

Mainboard Model 17MB135VS

## Monitor Connectivity

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	4xHDMI2.0, 1xDP1.2a, 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0, DP1.2a
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

### Mechanical

Product Dimensions (WxDxH)	1684 x 100 x 967 mm	Package Dimensions (WxDxH)	1948 x 210 x 1170 mm
Product Weight	37	Package Weight	52
Vesa Mounting	600 x 400 mm - M6	Bezel Width	B:21   T:16   L/R:16 mm

### **Environmental Conditions**

Operating Temperature	0-40°C	Operating Humidity	10-90%
Operating remperature	U-4U C	Operating numbers	10-90/0

#### Power

Power Supply 110 VAC - 240 VAC - 50/60 Hz

## Power Consumption

Typical 240 W	Deep Standby	≤0.5 W
---------------	--------------	--------

#### Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, remote control via LAN, Real Time Clock	Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance, IR Overlay Touch	Speaker	2x12W



Accessory

Standard

QSG, IB, Power Cord, Remote

Control Unit, RC Battery, Mounting Kit, Extension Brackets, IR Extender

Cable

Certification

Safety YES EMC YES

CE YES



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660