


Digital Signage Displays  
PF55D-2H

**VESTEL**



**Key Features**



**Daisy Chain**

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



**Usb Security**

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.




**Usb Auto-Play**

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



**Subtle Design**

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



**SoC Content Management**

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



**Signal Failover**

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.

### Panel

Screen Size	55"	Panel Technology	IPS
Backlight Type	Slim DLED	Brightness (typical)	500 cd/m <sup>2</sup>
Native Resolution	3840 x 2160 (16:9) - UHD	Contrast Ratio (typical)	1200:1 (typ.)
Dynamic Contrast Ratio	50000:1	Panel Life Time ( Min. )	50000 Hrs
Response Time (typical)	8 ms	Active Area (H x V)	1209.6 (H) x 680.4 (V) mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07G (8bits + FRC)
Color Gamut	72% NTSC	Haze Level	1%
Refresh Rate	60 Hz	Orientation	Landscape
Operation Hours	16/7	Area of Usage	Indoor

### Built-in System

Mainboard Model	17MB400VS	Operating System	Android 9
Memory	2 GB DDR4	Storage	16 GB eMMC
Additional Storage	Micro SD (up to 1TB)	CPU	Quad-Core ARM Cortex-A55
GPU	ARM Mali-G31 MP2	Wired	10/100/1000 Mbps Ethernet, IEEE 802.1X Authentication
WiFi	WiFi 5 (802.11 a/b/g/n/ac), IEEE 802.1X Authentication	Bluetooth	BT 5.1
HTML5 Browser	Vewd	Wireless Display	Miracast

### Monitor Connectivity

Video Input	2xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB	Video Output	1xHDMI2.0
Audio Input	Headphone, Optic SPDIF	External Control	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12)
External Sensor	RJ12		

### Mechanical

Product Dimensions (WxDxH)	1236 x 63 x 709 mm	Package Dimensions (WxDxH)	1369 x 165 x 874 mm
Product Weight	18.5 kg	Package Weight	24.1 kg
Vesa Mounting	400 (W) x 400 (H) mm M6	Bezel Width	B: 11 mm, T/L/R: 9 mm

### Environmental Conditions

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

### Power

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

### Power Consumption

Typical	138 W	Maximum	180 W
Deep Standby	≤0.5 W		

## Features

<p><b>Main Features</b></p>	<p>HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, Crestron Connected, SNMP</p>	<p><b>Mechanical Features</b></p>	<p>Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover</p>
<p><b>Speaker</b></p>	<p>2x10 W</p>		

## Accessory

<p><b>Standard</b></p>	<p>QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable</p>		
------------------------	--	--	--

## Certification

<p><b>Safety</b></p>	<p>Yes</p>	<p><b>EMC</b></p>	<p>Yes</p>
<p><b>CE</b></p>	<p>Yes</p>		

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660