


## Digital Signage Displays PR43B-4F

**VESTEL**



### Key Features



#### Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



#### Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.




#### Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



#### Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



#### SoC Content Management

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



#### Signal Failover

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.

## Panel

|                          |                         |                         |                                                    |
|--------------------------|-------------------------|-------------------------|----------------------------------------------------|
| Screen Size              | 43"                     | Backlight Type          | Slim DLED                                          |
| Brightness (typical)     | 700 cd/m <sup>2</sup>   | Native Resolution       | 3840 x 2160 (16:9) - UHD                           |
| Contrast Ratio (typical) | 1200:1 (typ.)           | Dynamic Contrast Ratio  | 70000:1                                            |
| Panel Life Time ( Min. ) | 50000 Hrs               | Response Time (typical) | 8 ms                                               |
| Active Area (H x V)      | 941.184(H) x 529.416(V) | Viewing Angle           | 178° Vert., 178° Hor.<br>(89U/89D/89L/89R) @ CR>10 |
| Color Value              | 1.07 G (8 bit + FRC)    | Screen Treatment        | 3H                                                 |
| Haze Level               | 1%                      | Refresh Rate            | 60 Hz                                              |
| Orientation              | Landscape / Portrait    | Operation Hours         | 24 / 7                                             |
| Area of Usage            | Indoor                  |                         |                                                    |

## Built-in System

|                 |           |
|-----------------|-----------|
| Mainboard Model | 17MB135VS |
|-----------------|-----------|

## Monitor Connectivity

|                  |                                               |                 |                        |
|------------------|-----------------------------------------------|-----------------|------------------------|
| RGB Input        | VGA(DE-15F)                                   | RGB Output      | N/A                    |
| Video Input      | 4xHDMI2.0, DP1.2a, 2xUSB2.0, USB2.0(Internal) | Video Output    | HDMI2.0, DP1.2a        |
| Audio Input      | Line In L/R                                   | Audio Output    | Headphone, Optic SPDIF |
| External Control | RS232(DE-9F), Ethernet(RJ45), Service(RJ12)   | External Sensor | RJ12                   |

## Mechanical

|                            |                                                                       |                            |                     |
|----------------------------|-----------------------------------------------------------------------|----------------------------|---------------------|
| Product Dimensions (WxDxH) | *963 x 83 x 555 mm with OPS/SDM<br>963 x 63 x 555 mm without OPS/SDM* | Package Dimensions (WxDxH) | 1050 x 178 x 718 mm |
| Product Weight             | 10.4kg                                                                | Package Weight             | 13.5kg              |
| Vesa Mounting              | 200 mm(W) x 200 mm(H) M6                                              | Bezel Width                | 6/6/6/9 mm          |

## Environmental Conditions

|                       |        |                    |        |
|-----------------------|--------|--------------------|--------|
| Operating Temperature | 0-40°C | Operating Humidity | 10-90% |
|-----------------------|--------|--------------------|--------|

## Power

|              |                              |
|--------------|------------------------------|
| Power Supply | 110 VAC - 240 VAC - 50/60 Hz |
|--------------|------------------------------|

## Power Consumption

|              |        |         |       |
|--------------|--------|---------|-------|
| Typical      | 127 W  | Maximum | 160 W |
| Deep Standby | ≤0.5 W |         |       |

## Features

|                   |                                                                                                                                                                                                                                                                     |                     |                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------|
| Main Features     | Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock | Mechanical Features | Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal Usb Cover, 30-degrees Tilting Installation |
| Optional Features | SDM or OPS compatibility, Embedded IR, IR extender option                                                                                                                                                                                                           | Speaker             | 2x8 W                                                                                                                 |



Accessory

|          |                                                                                       |  |  |
|----------|---------------------------------------------------------------------------------------|--|--|
| Standard | QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable |  |  |
|----------|---------------------------------------------------------------------------------------|--|--|

Certification

|        |     |     |     |
|--------|-----|-----|-----|
| Safety | Yes | EMC | Yes |
| CE     | Yes |     |     |

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660