

Railway Computer

COMPACT-RSL Rail Series

Embedded Railway Computer with Intel® Atom™ E39xx processor (formerly Apollo Lake-I)



IPC/COMPACT81

This fan less RPC COMPACT81 generation is based on the Intel® Atom™ E3900 (formerly Apollo Lake-I) processor technology and offers a wide range of interface options. The robust and uncompromising industrial design allows the implementation in the most demanding rail applications and guarantees long term availability.

- 24/7 continuous operation
- M12 connector
- EN50155 Class S2 power supply
- Extended temp. Range
- Railway approved (EN50155 & EN45545)



Product Highlights

- Maintenance free/Long term availability
- Goldcap instead of battery backup
- No moving parts
- Scalable CPU core
- Hardware watchdog
- Temperature supervision
- Intelligent power management system
- ESD- protection on all interfaces
- Motion Sensor
- Dead Reckoning
- Shock and vibration resistant

Product Features

- Intel® Atom™ E3900 Series
- up to 2.0GHz, up to 4 Cores
- RAM soldered on board up to 8GB
- Socket for CFast
- Graphic resolution up to WUXGA
- Ethernet, USB, CAN
- M12 connectors
- Stainless steel housing
- Protection class IP40
- EN50155 certified (OT4)

Markets / Applications

- Railway (rolling stock)
- Automotive
- Traffic control
- Transportation and vehicle construction
- Automated Guided Vehicle (AGV)

	Order Code	IPC/RSL81120-R245E ¹	IPC/RSL81120-R301E ¹	MySyslogic ¹
Processor / Performance				
Intel® Atom™ x5-E3930 1.80GHz (Burst) 1.3GHz Clock - Dual Core		optional	optional	
Intel® Atom™ x7-E3950 2.00GHz (Burst) 1.6GHz Clock - Quad Core		•	•	
Memory				
L2 cache		2MB	2MB	2MB
DDR3 RAM		8GB	8GB	8GB
4GB or 2GB DDR3 RAM ¹		optional	optional	optional
Features				
Real time clock PC compatible		•	•	•
Hardware Watchdog & Temperature supervisor		•	•	•
Intelligent power management (Ignition controller)		•	•	•
Goldcap backup		•	•	•
TPM2.0 (SLB9665)		•	optional	optional
Communication Interfaces				
DisplayPort 1.2 up to 4096x2160 @60Hz		•	•	•
CFast socket with retention frame ²		1	1	1
USB version 3.0 (Type A)		1	1	1
USB version 2.0 (Type A)		1	1	1
Ethernet 10/100/1000 (I210-IT) (M12 female X-coded)			2	up to 2
Ethernet 10/100 (I210-IT) (M12 female d-coded)		2		
RS232 ESD protected (DSUB9)			2	up to 6
RS422/485 ESD protected (DSUB9)				up to 2
CAN (PEAK, SJA1000 compatible) ESD protected, isolated (DSUB9)		2		up to 6
Mini PCIe socket ²		1	1	up to 4
I2C bus ²		•	•	•
Buzzer		•	•	•
Wireless Functions				
Cellular 4G Module (GSM/UMTS/LTE) u-blox MPC1-L210-03S-00 Module (TOBY-L210) - M2M only!		2x SMA		
Dual SIM Support		•		
Positioning Wireless Module (GPS, Galileo, Glonass, Beidou) u-blox NEO-M8U Module		1x SMA		
Acceleration / Motion Sensor STMicroelectronics ISM330DLC		•		
Technical Data				
Dimensions w262 x h52 x d138 mm (housing)		•	•	•
Net weight in gram		1750	1850	1750
Input voltage (isolated and reverse polarity protected) (M12 4P male A-coded)		16.8 ... 45VDC	optional	optional
Wide input voltage (isolated and reverse polarity protected) (M12 4P male A-coded)		optional	16.8 ... 137.5VDC	16.8 ... 137.5VDC
Interruption of voltage supply time: EN50155 (>10ms)		Class S2	Class S2	Class S2
UPS: Interruption of voltage supply time up to 30s ³				optional
Power consumption typ. in Watt @ 24V without Add-Ins, idle		~ 10	~ 12	~ 10
Environmental Conditions				
Operating temperature (up to 85°C for 10 min. according to EN 50155 Class OT4) ³		-40°C ... +70°C	-40°C ... +70°C	-40°C ... +70°C
Storage temperature -40 ... +85°C		•	•	•
Protection standard: IP40		•	•	•
Conformal coating ⁴		•	•	•
Shock: EN60068-2-27 / EN61373		•	•	•
Vibration: EN60068-2-64 / EN61373		•	•	•
EMI-Conformity EN50121-3-2 / EN301489-1		•	•	•
Safety according to EN62368-1		•	•	•
Fire protection HL3: DIN EN45545-2		•	•	•
Radio and Telecommunication: Designed to meet RED		•	•	•
MTBF ~ 455 000h @ 25°C according to Telcordia SR-332, Environment GB, excluding battery		•	•	•
Enhancement cards				
Wireless Module (LTE / GPS / WiFi / BT) ¹			optional	optional
Digital and Analog I/O ¹			optional	optional

¹ Please contact factory for minimum order quantities
² Internal connector

³ Depending on installation situation and interface connection. Please see user documentation.
⁴ on all possible components (excl. Connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2020 Syslogic Datentechnik AG
 All rights reserved

Syslogic Datentechnik AG
 Täferstrasse 28
 CH-5405 Baden Dättwil

Version 0.8 | May 2020

For further information and support:
info@syslogic.com
support@syslogic.com
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)
 +49 7741 967 14 20 Germany and Austria



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660