

Hisense

HIK Series



HIK SERIES

P1.875 INDOOR LED DISPLAY

HIK series LED solutions deliver unrivalled versatility due to the variety of cabinet configurations available. Integrators specifying the HIK range have access to the broadest range of pixel pitch and aspect ratios options. Perfect for any internal space, these innovative Hisense LED modules include cable-less internal construction and full frontal access for ease of maintenance.



Highlights



High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



Brightness nits

With an average 500 nits and 1,000 nits maximum brightness, the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Low brightness & High gray level

LED display could reveal more details, including layers and colors, than traditional displays do.



160° High viewing angle

The extra wide 160° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



High color calibration

LED display correction technology could uniformly lighten several hundred thousand LED lights, presenting a uniform display effect with the same brightness and color scale.



AOB Admixture on board

AOB Transparent glass on surface enhances the mixed light property with scratch resistance, water-proof & easy to clean.













Specification subject to change | January 2022

www.hisense-b2b.com



Hisense


HIK Series

Specifications

HIK Series	
Pixel Pitch	P1.875
LED Type	SMD1515 3in1
Thickness	53.7mm
Module Size (W H/mm)	240 x 270
Cabinet Dimension (W H/mm)	480 x 540 / 480 x 270 / 240 x 540
Cabinet Resolution	256 x 288
Cabinet Weight (kg/panel)	≤7kg (480 x 540) / ≤4kg (480 x 270) / ≤4kg (240 x 540)
Brightness (Nits)	500 (0-1000 Adjustable)
Contrast Ratio	7000:1
Maintanance	Front Access
IP Rating	IP50
Max Power Consumption (W/sqm)	≤650
Avg Power Consumption (W/sqm)	≤150
Viewing Angle	160°
Refresh Rate (Hz)	3840
Operating Enviroment	-10° to 40° / 10 to 90% Relative Humidity (non condensing)

Display Dimensions

Life Span



100,000 Hours



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660