

17" Medical Panel PC Series

| 17" Medical Panel PC | WMP-175 | WMP-172D | WMP-172S |
|-----------------------------|---|--|--|
| Thermal | Fanless | Fanless | Fanless |
| CPU | Intel Atom D525 1.80G | Intel Core 2 Duo U7500 1.06G | Intel Core 2 Duo U7500 1.06G |
| Chipset | SB: ICH8M | NB: GME965 SB: ICH8M | NB: GME965 SB: ICH8M |
| Memory | DDR3 1066, Max. 4GB | DDR2 800, Max. 4GB | DDR2 800, Max. 4GB |
| Touch-screen | 17" / 5wire resistive | 17" / 5wire resistive | 17" / 5wire resistive |
| External I / O | <ul style="list-style-type: none"> • USB 2.0 x 3 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 1 • DB-15 VGA output x 1 • 3.5mm Audio jack x 2 (Line-out, and Mic-in) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 3 (RS422/485 x 1, RS232 x 2) • Giga LAN x 2 • DB-15 VGA output x 1 • DVI x 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 2 • DB-15 VGA output x 1 • DVI x 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 |
| Storage HDD | 2.5"SATA HDD drive bay x1 ,Max.500G | 2.5"SATA HDD drive bay x1,Max.500G | 2.5"SATA HDD drive bay x1,Max.500G |
| Expansion | Optional PCI or PCI- E slot x 1 Mini-PCIe x1 | <ul style="list-style-type: none"> • PCI x 1 • Mini-PCI x1 • Mini-PCIe x1 | <ul style="list-style-type: none"> • Mini-PCI x1 |
| Regulations | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 |
| Size | 420 (W) x 360 (H) x 83 (D) mm | 420 (W) x 360 (H) x 83 (D) mm | 420 (W) x 360 (H) x 83 (D) mm |
| Weight | 6.5KG (w/o power adapter) | 6.5KG (w/o power adapter) | 6.5KG (w/o power adapter) |
| Ordering information | 1. WMP-175/Atom D525 1.8G/1G RAM/160G HDD/R-touch/PCI 2. WMP-175/Atom D525 1.8G/1G RAM/160G HDD/IR-touch/PCI-Ex4 | WMP-172D/Intel Core 2 Duo/1G RAM/160G HDD/R-touch | WMP-172S/Intel Core 2 Duo/1G RAM/160G HDD/R-touch |
| Other | 1. I/O cover as option | 1. I/O cover as default | 1. I/O cover as option |
| | 2. Optional PCI or PCIe expansion slot for WMP-175 | 2. Support bootable Compact Flash Slot for CF Type I/II storages x 1(Optiona CF card) | |
| | | 3. Support WebCam for option | |

17" Medical Panel PC Series

| 17" Medical Panel PC | WMP-171D | WMP-171S |
|-----------------------------|--|--|
| Thermal | Low noise smart Fan | Low noise smart Fan |
| CPU | Intel Core 2 Duo T7500 2.20G Celeron M550 2.0G | Intel Core 2 Duo T7500 2.20G Celeron M550 2.0G |
| Chipset | NB: GME965 SB: ICH8M | NB: GME965 SB: ICH8M |
| Memory | DDR2 800, Max. 4GB | DDR2 800, Max. 4GB |
| Touch-screen | 17" / 5wire resistive | 17" / 5wire resistive |
| External I / O | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 3 (RS422/485 x 1, RS232 x 2) • Giga LAN x 2 • DB-15 VGA output x 1 • DVI x 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 2 • DB-15 VGA output x 1 • DVI x 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 |
| Storage HDD | 2.5"SATA HDD drive bay x1, Max.500G | 2.5"SATA HDD drive bay x1, Max.500G |
| Expansion | <ul style="list-style-type: none"> • PCI x 1 • Mini-PCI x1 • Mini-PCIe x1 | <ul style="list-style-type: none"> • Mini-PCI x1 |
| Regulations | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 |
| Size | 420 (W) x 360 (H) x 83 (D) mm | 420 (W) x 360 (H) x 83 (D) mm |
| Weight | 6.5KG (w/o power adapter) | 6.5KG (w/o power adapter) |
| Ordering information | WMP-171D/Intel Core 2 Duo/1G RAM/160G HDD/R-touch | WMP-171S/Intel Core 2 Duo/1G RAM/160G HDD/R-touch |
| Other | <ol style="list-style-type: none"> 1. I/O cover as default 2. Support bootable Compact Flash Slot for CF Type I/II storages x 1 (Optional CF card) 3. Support WebCam for option | 1. I/O cover as option |

19" Medical Panel PC Series

| 19" Medical Panel PC | WMP-195 | WMP-191 | WMP-192 |
|-----------------------------|---|---|---|
| Thermal | Fanless | Low noise smart Fan | Fanless |
| CPU | Intel Atom D525 1.80G | Intel Core 2 Duo T7500 2.20G Celeron M550 2.0G | Intel Core 2 Duo U7500 1.06G |
| Chipset | SB: ICH8M | NB: GME965 SB: ICH8M | NB: GME965 SB: ICH8M |
| Memory | DDR3 1066, Max. 4GB | DDR2 800, Max. 4GB | DDR2 800, Max. 4GB |
| Touch-screen | 19" / 5wire resistive/ Full Falt | 19" / 5wire resistive/ Full Falt | 19" / 5wire resistive/ Full Falt |
| External I / O | <ul style="list-style-type: none"> • USB 2.0 x 3 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 1 • DB-15 VGA output x 1 • 3.5mm Audio jack x 2 (Line-out, and Mic-in) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 3 (RS422/485 x 1, RS232 x 2) • Giga LAN x 2 • DB-15 VGA output x 1 • DVIx 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 3 (RS422/485 x 1, RS232 x 2) • Giga LAN x 2 • DB-15 VGA output x 1 • DVIx 1 • 3.5mm Audio jack x 3 (Line-out, Line-in and Mic-in) • PS/2 x 2 (Keyboard, mouse) • DC-In x 1 • Reset button x 1 |
| Storage HDD | 2.5"SATA HDD drive bay x1 .Max.500G | 2.5"SATA HDD drive bay x1.Max.500G | 2.5"SATA HDD drive bay x1.Max.500G |
| Expansion | Optional PCI or PCI- E slot x 1 Mini-PCIe x1 | <ul style="list-style-type: none"> • PCI x 1 • Mini-PCI x1 • Mini-PCIe x1 | <ul style="list-style-type: none"> • PCI x 1 • Mini-PCI x1 • Mini-PCIe x1 |
| Regulations | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 |
| Size | 440.5 (W) x 369.8 (H) x 83 (D) mm | 440.5 (W) x 369.8 (H) x 83 (D) mm | 440.5 (W) x 369.8 (H) x 83 (D) mm |
| Weight | 7.5KG (w/o power adapter) | 7.5KG (w/o power adapter) | 7.5KG (w/o power adapter) |
| Ordering information | WMP-195, Atom D525 1.8G, DDR3 1G, SATA 160G, R-touch | 1. WMP-191, Intel Core 2 Duo 2.2 G, DDR2 1G, SATA 160G, PCI 2. WMP-191, Intel Celeron 550 2.0G, DDR2 1G, SATA 160G, PCI | WMP-192, Intel Core 2 Duo 1.06G, DDR2 1G, SATA 160G, PCI |
| Other | Optional PCI or PCIe expansion slot for WMP-195 | | |

21.5" Medical Panel PC Series

| 21.5" Medical Panel PC | WMP-227 | WMP-226 |
|-----------------------------|---|---|
| Thermal | Fanless | Low noise smart Fan |
| CPU | Intel Core i5-2467M Processor (3M Cache, 1.60 GHz) | Intel Core i5-2410M (3M Cache, 2.30 GHz) 35W |
| | | Intel Core i5-2510E (3M Cache, 2.50 GHz) 35W |
| | | Intel Core i3-2330E (3M Cache, 2.20 GHz) 35W |
| | | Intel Celeron B810 (2M Cache, 1.60 GHz) 35W |
| Chipset | HM65 | HM65 |
| Memory | DDR3 1066/1333, Max. 8GB | DDR3 1066/1333, Max. 8GB |
| Touch-screen | 21.5" / 5wire resistive / Full Flat | 21.5" / 5wire resistive / Full Flat |
| External I / O | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 2 • DVI-I output x 1 • 3.5mm Audio jack x 2 (Line-out, and Mic-in) • DC-In x 1 • Reset button x 1 | <ul style="list-style-type: none"> • USB 2.0 x 4 • COM x 2 (RS422/485 x 1, RS232 x 1) • Giga LAN x 2 • DVI-I output x 1 • 3.5mm Audio jack x 2 (Line-out, and Mic-in) • DC-In x 1 • Reset button x 1 |
| Storage HDD | 2.5"SATA HDD drive bay x2, Max.500G | 2.5"SATA HDD drive bay x2, Max.500G |
| Expansion | <ul style="list-style-type: none"> • Optional PCI or PCIe x 1 • Mini-PCIe x2 | <ul style="list-style-type: none"> • Optional PCI or PCIe x 1 • Mini-PCIe x2 |
| Regulations | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 | UL/cUL 60601-1 version 3, FCC/VCCI class B / EN 60601-1 / EN60601-1-2:2007 / ISO 14971 |
| Size | 540 (W) x 375(H) x 78 (D) mm | 540 (W) x 375(H) x 78 (D) mm |
| Weight | 7 KG (w/o power adapter) | 6.5KG (w/o power adapter) |
| Ordering information | WMP-227, Core i5-2467M/1.60GHz/DDR3 2G RAM/ SATA 160G HDD/ Full flat resistive touch/PCI-Ex16 | WMP-226, Core i5-2410M 2.30GHz/ DDR3 2G RAM/ SATA 160G HDD/ Full flat resistive touch/PCI-Ex16 |
| Other | | |
| | | |

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660