

Manufactured using a 0.16um process controller and high-quality industrial MLC NAND Flash memory, Transcend Industrial Temp SDHC10I cards provide high performance, low power consumption, excellent reliability, and wide operating temperature tolerance.

#### Hardware Features

- Compliant with RoHS 2.0 standards
- MLC NAND flash
- Compliant with SD specification 3.01
- Compliant with Speed Class 10
- Promised operational reliability in a wide temperature range (from -40°C to 85°C)

#### Firmware Features

- Mechanical Write Protection switch for data security
- Supports S.M.A.R.T. function to conduct health monitoring, analysis, and reporting for storage devices
- Built-in ECC (Error Correction Code) functionality
- · Wear-Leveling
- · Early Move

## **Ordering Information**

| 8GB  | TS8GSDHC10I  |
|------|--------------|
| 16GB | TS16GSDHC10I |
| 32GB | TS32GSDHC10I |

<sup>\*</sup>Scope Pro is only available when used with the RDF5 card reader.






www.transcend-info.com

# **Specifications**

| Appearance               | Dimensions               | 24 mm x 32 mm x 2.1 mm (0.94" x 1.26" x 0.08")   |
|--------------------------|--------------------------|--|
|                          | Form Factor              | SD flash card  |
| Storage                  | Flash Type               | MLC NAND flash   |
|                          | Capacity                 | 8 GB / 16 GB / 32 GB   |
| Operating<br>Environment | Operating Voltage        | 2.7V ~ 3.6V  |
|                          | Drop Test                | 1.5m free fall   |
|                          | Operating Temperature    | Wide Temp.<br>-40°C (-40°F) ~ 85°C (185°F)   |
|                          | Storage Temperature      | -40°C (-40°F) ~ 85°C (185°F)   |
|                          | Humidity                 | 0% ~ 95%   |
|                          | Shock                    | Acceleration: 490 m/s² (standard holding time: 11 ms, semi-sine wave, velocity change: 3.44 m/s) |
|                          | Vibration (Operating)    | 20 G (peak-to-peak), 20 Hz ~ 2,000 Hz (frequency)  |
| Power                    | Power Consumption (Max.) | 0.72 watt(s)   |
| Performance              | Read Speed (Max.)        | up to 24 MB/s  |
|                          | Write Speed (Max.)       | up to 16 MB/s  |
|                          | Terabytes Written (TBW)  | up to 60 TBW   |
| Warranty                 | Certificate              | CE / FCC / UKCA  |
|                          | Warranty                 | Three-year Limited Warranty  |

#### **Mechanical Dimensions**



Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment. Due to the complexity and variety of industrial applications, Transcend cannot guarantee 100% compatibility with all platforms and under all scenarios. For special applications and environments, it is strongly suggested that you contact Transcend beforehand for clarification.



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

# US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660