

Digital Signage Displays PN55B-4H





Key Features



Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



SoC Content Management

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



Signal Failover

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.



Panel

Screen Size	55"	Backlight Type	Slim DLED		
Brightness (typical)	500 cd/m ²	Native Resolution	3840 x 2160 (16:9) - UHD		
Contrast Ratio (typical)	1200:1(typ.)	Dynamic Contrast Ratio	50000:1		
Panel Life Time (Min.)	50000 Hrs	Response Time (typical)	8ms		
Active Area (H x V)	1209.6 × 680.4	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10		
Color Value	1.07 G (8 bit + FRC)	Screen Treatment	ЗН		
Haze Level	1%	Refresh Rate	60Hz		
Orientation	Landscape / Portrait	Operation Hours	24 / 7		
Area of Usage	Indoor				
Built-in System					
Mainboard Model	17MB135VS				
Monitor Connectivity					
RGB Input	VGA(DE-15F)	RGB Output	N/A		
Video Input	4xHDMI2.0, 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0		
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF		
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12		
Mechanical					
Product Dimensions (WxDxH)	"1236 x 83 x 709 mm with OPS/SDM 1236 x 63 x 709 mm without OPS/SDM"	Package Dimensions (WxDxH)	1369 x 165 x 874		
Product Weight	17 kg	Package Weight	22 kg		
Vesa Mounting	400 mm(W) x 400 mm(H) M6	Bezel Width	9/9/9/11 mm		
Environmental Conditions					
Operating Temperature	0-40°C	Operating Humidity	10-90%		
Power					
Power Supply	110 VAC - 240 VAC - 50/60 Hz				
Power Consumption					
Typical	138 W	Maximum	180 W		
Deep Standby	≤0.5 W				
Features					
Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff,	Mechanical Features	Joystick, Rocker Switch, Detachable Power Cable, Dettachable Logo, Internal Usb Cover, 30-degrees		

2x10 W

Compatibility

Optional Features

Videowall support, Remote control via LAN, Real Time Clock SDM or OPS compatibility,

Embedded IR, IR extender option

Speaker



Accessory

Standard	QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable
Certification	

Safety	Yes	EMC	Yes
CE	Yes		



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660