

Digital Signage Displays





Key Features



Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



SoC Content Management

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



Signal Failover

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.



Panel

Screen Size	50"	Panel Technology	VA
Backlight Type	Slim DLED	Brightness (typical)	500 cd/m ²
Native Resolution	3840 x 2160 (16:9) - UHD	Contrast Ratio (typical)	5000:1 (typ.)
Dynamic Contrast Ratio	50000:1	Panel Life Time (Min.)	50000 Hrs
Response Time (typical)	9.5 ms	Active Area (H x V)	1095.8 (H) x 616.4 (V) mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07B
Color Gamut	72% NTSC	Haze Level	3%
Refresh Rate	60 Hz	Orientation	Landscape
Operation Hours	16/7	Area of Usage	Indoor
Built-in System			
Mainboard Model	17MB400VS	Operating System	Android 9
Memory	2 GB DDR4	Storage	16 GB eMMC
Additional Storage	Micro SD (up to 1TB)	CPU	Quad-Core ARM Cortex-A55
GPU	ARM Mali-G31 MP2	Wired	10/100/1000 Mbps Ethernet, IEEE 802.1X Authentication
WiFi	WiFi 5 (802.11 a/b/g/n/ac), IEEE 802.1X Authentication	Bluetooth	BT 5.1
HTML5 Browser	Vewd	Wireless Display	Miracast
Monitor Connectivity Video Input	2xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB	Video Output	1xHDMI2.0
Audio Output	Headphone, Optic SPDIF	External Control	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12)
External Sensor	RJ12		
External Sensor Mechanical	RJ12		
	RJ12 1121 x 63 x 646 mm	Package Dimensions (WxDxH)	1215 x 165 x 775 mm
Mechanical		Package Dimensions (WxDxH) Package Weight	
Mechanical Product Dimensions (WxDxH)	1121 x 63 x 646 mm		1215 x 165 x 775 mm
Mechanical Product Dimensions (WxDxH) Product Weight	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6	Package Weight	1215 x 165 x 775 mm 16.8 kg
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6	Package Weight	1215 x 165 x 775 mm 16.8 kg
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6	Package Weight Bezel Width	1215 x 165 x 775 mm 16.8 kg B: 13 mm, T/L/R: 9 mm
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition Operating Temperature	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6	Package Weight Bezel Width	1215 x 165 x 775 mm 16.8 kg B: 13 mm, T/L/R: 9 mm
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition Operating Temperature Power	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6 S 0-40°C	Package Weight Bezel Width	1215 x 165 x 775 mm 16.8 kg B: 13 mm, T/L/R: 9 mm
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition Operating Temperature Power Power Power Supply	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6 S 0-40°C	Package Weight Bezel Width	1215 x 165 x 775 mm 16.8 kg B: 13 mm, T/L/R: 9 mm
Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption	1121 x 63 x 646 mm 12.8 kg 200 (W) x 200 (H) mm M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Package Weight Bezel Width Operating Humidity	1215 x 165 x 775 mm 16.8 kg B: 13 mm, T/L/R: 9 mm 10-90%



Features

Main Features	HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI- CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, Crestron Connected, SNMP	Mechanical Features	Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover
Speaker	2x10 W		
Accessory Standard	QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable		
Certification			
Safety	Yes	EMC	Yes
CE	Yes		



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660