

Digital Signage Displays XD86D-4H





Key Features



Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



Signal Failover

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.




Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



Pixel Shifting

The Pixel Shifting feature can be activated in order to reduce the potential risk of image sticking when static content is displayed over long periods of time. The feature periodically shifts the image on the display, without causing any interference of the visual experience.



Panel

Screen Size	86"	Panel Technology	IPS
Backlight Type	DLED	Brightness (typical)	400 cd/m ²
Native Resolution	3840 x 2160 (16:9) - UHD	Contrast Ratio (typical)	1200:1 (typ.)
Dynamic Contrast Ratio	40000:1	Panel Life Time (Min.)	30000 Hrs
Response Time (typical)	8 ms	Active Area (H x V)	1895 (H) x 1066 (V) mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07G (8bits + FRC)
Color Gamut	72% NTSC	Haze Level	25%
Refresh Rate	60 Hz	Orientation	Landscape
Operation Hours	16/7	Area of Usage	Indoor
Built-in System			
Mainboard Model	17MB400VS	Operating System	Android 9
Memory	2 GB DDR4	Storage	16 GB eMMC
Additional Storage	Micro SD (up to 1TB)	CPU	Quad-Core ARM Cortex-A55
GPU	ARM Mali-G31 MP2	Wired	10/100/1000 Mbps Ethernet, IEEE 802.1X Authentication
WiFi	WiFi 5 (802.11 a/b/g/n/ac), IEEE 802.1X Authentication	Bluetooth	BT 5.1
HTML5 Browser	Vewd	Wireless Display	Miracast
Monitor Connectivity Video Input	4xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB	Video Output	1xHDMI2.0
	2.0, 1xUSB-A 2.0 (Internal), 1x Micro	Video Output External Control	1xHDMI2.0 RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12)
Video Input	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB		RS232 (3.5mm jack green), Gigabit
Video Input Audio Output	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF		RS232 (3.5mm jack green), Gigabit
Video Input Audio Output External Sensor	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF		RS232 (3.5mm jack green), Gigabit
Video Input Audio Output External Sensor Mechanical	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF RJ12	External Control	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12)
Video Input Audio Output External Sensor Mechanical Product Dimensions (WxDxH)	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF RJ12 1962 x 79 x 1133 mm	External Control Package Dimensions (WxDxH)	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12) 2163 x 380 x 1490 mm
Video Input Audio Output External Sensor Mechanical Product Dimensions (WxDxH) Product Weight	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF RJ12 1962 x 79 x 1133 mm 62 kg 800 (W) x 600 (H) mm M8	External Control Package Dimensions (WxDxH) Package Weight	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12) 2163 x 380 x 1490 mm 83 kg
Video Input Audio Output External Sensor Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF RJ12 1962 x 79 x 1133 mm 62 kg 800 (W) x 600 (H) mm M8	External Control Package Dimensions (WxDxH) Package Weight	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12) 2163 x 380 x 1490 mm 83 kg
Video Input Audio Output External Sensor Mechanical Product Dimensions (WxDxH) Product Weight Vesa Mounting Environmental Condition	2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB Headphone, Optic SPDIF RJ12 1962 x 79 x 1133 mm 62 kg 800 (W) x 600 (H) mm M8	External Control Package Dimensions (WxDxH) Package Weight Bezel Width	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12) 2163 x 380 x 1490 mm 83 kg B/T/L/R: 25 mm

Power Consumption

Typical	TBD	Maximum	400 W
Deep Standby	≤0.5 W		



Features

Speaker 2x12 W Accessory QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable Certification Safety Yes EMC Yes	Main Features	HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI- CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, Crestron Connected, SNMP	Mechanical Features	Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover
Standard QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable Certification Safety Yes EMC Yes	Speaker	2x12 W		
Safety Yes EMC Yes		unit, RC battery, Mounting kit, IR		
	Certification			
	Safety	Yes	EMC	Yes
CE Yes	CE	Yes		



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660