



EPC-WHL-Din Rail

8th Gen Intel® Whiskey Lake Fanless Tiny System

- > 8th Gen Intel® Whiskey Lake-U 4 Core Ultra Low 15W Processor
- > Intel® UHD Graphics 620/610
- > Dual Gigabit Ethernet, HD Audio
- > Dual Channel Max up to 64GB DDR4 2400Mhz
- > Dual Expansion, M.2 Key-B/E
- > Dual HDMI w/CEC Controller (Factory Option)
- > TPM 2.0, RAID 0/1
- > Din Rail Type

Spec

| -System Information- | |
|----------------------------------|--|
| Processor | Intel® Core™ i7-8665UE Processor (8M Cache, up to 4.40 GHz) Intel® Core™ i5-8365UE Processor (6M Cache, up to 4.10 GHz) Intel® Core™ i3-8145UE Processor (4M Cache, up to 3.9GHz) Intel® Celeron® Processor 4305UE (2M Cache, 2.00 GHz) |
| System Memory | 2x 260-Pin SO-DIMM Socket, Max. Up to 64GB DDR4 2400MHz |
| BIOS Information | AMI uEFI BIOS, 128Mbit SPI Flash ROM |
| Watchdog Timer | H/W Reset, 1sec. ~ 65535sec. |
| H/W Status Monitor | Monitoring System Temperature and Voltage with Auto Throttling Control |
| TPM | TPM 2.0 |
| SBC | ECM-WHL |
| Expansion | |
| Expansion | 1 x M.2 (Key-B, 2242/3042, PCIe, SATA, USB 3.0, USB 2.0, SIM Slot) 1 x M.2 (Key-E, 2230, PCIe, USB2.0, CNVi) |
| Storage | |
| Storage | 1 x 2.5" Drive Bay (7mm) 1 x M.2 (2242) Key-B Support RAID 0/1 |
| I/O | |
| USB Port | 4 x USB 3.1 |
| Antenna | 2 x Antenna Mounting with Dust Protection Cover |
| System Control | |
| LED Indicator | 1 x Power on/off LED on front side 1 x Storage Access LED on front side |
| Display | |
| Graphic Chipset | Intel® UHD Graphics 620 (i7-8665UE, i5-8365UE, i3-8145UE) Intel® UHD Graphics 610 (4305UE) |
| Spec. & Resolution | 2 x HDMI 1.4: Max. Resolution 4096x2160@24Hz |
| Multiple Display | Dual Display |
| Audio | |
| Audio Codec | Realtek ALC888S |
| Audio Interface | 1 x Mic-in, 1 x Line-out |
| Certifications | |
| Certification Information | CE, FCC Class B, UKCA |
| Ethernet | |
| LAN Chipset | 1 x Intel® I210AT 1 x Intel® I219LM |
| Ethernet Interface | 10/100/1000 Base-Tx Gigabit Ethernet Compatible |
| LAN Port | 2 x RJ-45 |
| Power Requirement | |
| DC Input | Typical +12V |
| DC Input Connector | Lockable DC Jack |
| ACPI | Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant |
| Power Mode | AT/ATX (ATX is default setting) |
| Adapter | Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 12V/10A AC-DC 120W Adapter |
| Mechanical & Environmental | |



| | |
|------------------------------|--|
| Operating Temperature | With extended temperature peripherals: -10°C ~ 50°C (14°F ~ 122°F) with 0.5m/s air flow With extended temperature peripherals: -10°C ~ 40°C (14°F ~ 104°F) with 0.2m/s air flow With 2.5" hard drive: 0°C ~ 40°C (32°F ~ 113°F) with 0.5m/s air flow |
| Storage Temperature | -30~70C° (-22°F ~ 158°F) |
| Operating Humidity | 40°C @ 95% Relative Humidity, Non-condensing |
| Dimension (W x L x H) | 177mm x 123mm x 55mm (7" x 4.8" x 2.2") |
| Weight | 2.65lbs(1.2KG) |
| Vibration Test | With SSD: 5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis |
| Shock Test | With SSD: 50G, IEC 60068-2-27, Half Sine, 11ms, Z Axis |
| Mounting Kit | Din-Rail (Default) |
| Drop | ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces |
| Construction | Aluminum + Metal |
| Software Support | |
| OS Information | Win 10, Linux |
| Ordering Information | |
| Ordering Information | EPC-WHL-86-C2-2R 8th Gen Intel®Core™ Processor Core™ i7-8665UE Fanless Din Rail System EPC-WHL-83-C2-2R 8th Gen Intel®Core™ Processor Core™ i5-8365UE Fanless Din Rail System EPC-WHL-81-C2-2R 8th Gen Intel®Core™ Processor Core™ i3-8145UE Fanless Din Rail System EPC-WHL-43-C2-2R 8th Gen Intel®Celeron 4305UE Fanless Din Rail System E1702031831R Australia Power Cord E1702031833R USA Power Cord E1702031834R Japan Power Cord E170P060380R UK Power Cord E1702031000R EU Power Cord |

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660