



Rugged Computer RML A4NX

Computer Vision Edge Unit with NVIDIA Jetson Orin NX (16GB)

Rugged Series



Product Highlights

- 24/7 continuous operation
- IP67 protection, extended temperature range
- Power ignition controller
- High shock and vibration resistance
- Power Over Ethernet (PoE+)



© 2024 Syslogic AG

Rugged Computer RML A4NX

 Order Code [RPC/RMLA4NX16-A202S-02^{1,6}](#) [RPC/RMLA4NX16-B202S-02^{1,6}](#)

Processor module / Performance

NVIDIA Jetson Orin NX I (16GB RAM) 1024-core NVIDIA Ampere GPU with 32 Tensor Cores 8-core NVIDIA Arm® Cortex A78AE 64-bit CPU	✓	✓
NVIDIA Jetson Orin NX I (8GB RAM) 1024-core NVIDIA Ampere GPU with 32 Tensor Cores 6-core NVIDIA Arm® Cortex A78AE 64-bit CPU	on request ¹	on request ¹
AI Performance	100 TOPs	100 TOPs

Memory / Storage

128-Bit LPDDR5 (102,4 GB/s) RAM soldered on board	16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) ⁶ , an SSD is <u>required</u> , no internal eMMC storage available	240GB	240GB
microSD Card socket ²	1	1

Features

Inertial measurement unit (IMU) STMicro ISM330DHCXTR	✓	✓
Real time clock (RTC), with battery backup Renata CR2477 (950 mAh)	✓	✓

Communication Interfaces

DisplayPort 1.4a @ 8K30 <small>behind the service cover (rear)</small>	1	1
Internal USB version 2.0 <small>behind the service cover (rear), for device flashing and SSH access only</small> (micro USB Type AB)	1	1
USB version 2.0 <small>behind the service cover (rear)</small> (Type A)	2	2
USB version 3.1 (5 Gbit/s) with dustcap (Type A)	1	1
Ethernet 10/100/1000 BASE-T (1x native, 1x 1210-IT) (M12 female, x-coded)	2	2
Power over Ethernet - IEEE802.3at 10/100/1000Mbit (M12 female x-coded)	4	4
PSE - Power sourcing equipment, producing 48VDC out		
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (M12 female, a-coded)	1	1
CAN 2.0B only (active/passive), CAN FD supported, isolated (M12 female, a-coded)	1	1
Digital I/O's, current sinking, isolated ^{12/24VDC} (M12 male, a-coded)	4in / 2out ⁵	4in / 2out ⁵
Serial RS232 (M12 male, a-coded)	1	1
Mini PCIe socket ² , PCIe bandwidth shared with PoE ports	1	1
USB version 2.0 ¹ (M12 female, a-coded)	on request	on request

Wireless Connectivity

Cellular 4G Module (LTE/UMTS/GSM) with GNSS Sierra Wireless EM7590 (Dual nano SIM support)	none	3 x SMA
Wireless LAN (Wi-Fi 6/6E) 802.11ax/ac/a/b/g/n dual-band 2x2 MIMO & Bluetooth 5.2 Intel AX210	none	2 x RP-SMA
Cellular 5G module (4G/3G fallback) with GNSS	on request	on request
High precision multiband GNSS module with optional heading support ¹ u-blox ZED-F9P/F9R	on request	on request

Technical Data

Dimensions excl. mounting holes [mm]	w250 x h100 x d170	w250 x h100 x d170
Net weight [gram]	~3600	~3650
Non-isolated input voltage with ignition controller and RP protection (M12 male, a-coded)	9 ... 45VDC	9 ... 45VDC
Typical power consumption under load with few peripherals attached (25W Mode) ³	35W	35W

Software / OS

NVIDIA JetPack SDK - Jetson Linux (Ubuntu based)	✓	✓
--	---	---

Environmental Conditions

Operating temperature ³ , *Cold startup max. -25°C	-40°C* ... +70°C	-40°C* ... +70°C
Storage temperature	-40°C ... +85°C	-40°C ... +85°C
Ingress protection standard according to EN60529	IP67	IP67
Conformal coating ⁴	on request	on request
Shock according to ISO 15003 (designed to meet)	50g peak acc. (11ms)	50g peak acc. (11ms)
Vibration according to ISO 15003 (designed to meet)	2g (10 - 350Hz)	2g (10 - 350Hz)
EMC-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	n/a	RED
estimated MTBF @ 25°C ambient <small>according to Telcordia SR-332, Environment GB, excluding battery and SSD</small>	~tbd	~tbd

¹ Please contact factory for minimum order quantities

² Internal connector

³ Depends on installation situation interface connection and device load. Please see user documentation. Cold startup maximal -25°C

⁴ On all possible components (excl. Xavier NX module, connectors and wireless devices)

⁵ The six total digital I/Os are each configurable as either output or input via software.

⁶ The product must be ordered with an SSD, use the following order codes: [RPC/RMLA4NX16-x202S-02](#)(240GB), [-05](#)(480GB), [-10](#)(960GB), [-20](#)(1920GB)



Product specifications subject to change without notice. All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660