

/ R/G(H) 15" ⊮	P66 / IP69K	Stainless Steel Dis	splay	li	ndustrial Panel PC		Industrial play Monitor
Feat	tures /			Dimensions / 💭			
	15" New Generation Stainless Steel Display						
		el Design and Grade 304 S	tainlass Staal Englasura				
	de 316 for Opt		Stamless Steel Enclosure				
 IP66. 	/IP69K Rated	vith M12 (W.F.) Connectors	5				
Supp	port Resistive T	ouch, Projected Capacitive	Touch, and Glass				
 Touc 	ch on/off Button	on the Side Edge for Hygie	enic Cleaning)	
		Versatile Mounting: Yoke M	Nounting /		·		
Space	ce-saving VES	A 75 x 75 mm Mounting			399 305.11		<u>75 – 75 – 75 – 75 – 75 – 75 – 75 – 75 –</u>
					r		• •
							80039.00
		0					\setminus
Spe	cificatio	ons / 🔎				Action -	
				s 45		22 20	
- IO Port		1 x M12 12-pin for VGA with v	vaterproof cover and chain	•			• •
- HDMI		1 x W.F. HDMI with waterproo					
USB		1 x M12 USB 2.0 with waterpr	roof cover and chain				· 600
Speake	er	1 x 2W IP65 speaker (option)			Į	────) L®ta i (•	
OSD C		OSD on the rear side			<u> </u>		* *
Membra Power (ane		ith waterproof cover and chain				UNIT: mm
1.0101	Connoctor						Tolerance
Display		Standard	High Brightness Optional				
Display Max P	/ Type lesolution	15" TFT-LCD 1024 x 768	15" TFT-LCD 1024 x 768				
Max. Co		16.2M / 262K	16.7M				
	ance (cd/m ²)	300	1000				
View Ar	•	176(H) /176(V)	160(H) /150(V)				
Contras		2000:1	800:1	Environmental			
Backlig	ht Lifetime	70,000 hrs	50,000 hrs	Operating Temper		on)	
Touch	Screen			Storage Temperate Humidity	ure -30~70°C 10 to 95% @ 40°C, non-	condensing	
		Resistive Touch (for R model)		Certificate	CE/FCC Class A	contentaing	
Туре		Projected Capacitive Touch (for Glass (for G model)	or P model)				
Interfac	ce	USB		Ordering Informa	ation		
Light Tr		Resistive Touch : 80% Projected Capacitive : 90%		ViTAM-115P 15 pro	" XGA IP66/IP69K stainless steel disp ojected capacitive touch, 9~36V DC po	lay, VGA/HDMI input, OSD on the rear side, ower input with Adapter	
Power				VITAM-115R	" XGA IP66/IP69K stainless steel disp	lay, VGA/HDMI input, OSD on the rear side,	
Power		DC 9~36V		51	wire resistive touch window, 9~36V DC	power input with Adapter	
Power (Power Consumption VITAM-115R: Max 9W VITAM-115PH: Max 17W				" XGA IP66/IP69K stainless steel disp otection glass, 9~36V DC power input	lay, VGA/HDMI input, OSD on the rear side, with Adapter	
Mechan	Mechanical Construction 304 Stainless steel chassis(default), 316 Stainless steel chassis(optional)			ViTAM-115PH 15	5" XGA IP66/IP69K stainless steel disp ojected capacitive touch, 9~36V DC or	lay, VGA/HDMI input, OSD on the rear side, ower input with Adapter, 1,000 nits LCD	
Constru							
Mountin	ng	VESA Mount 75 x 75, Yoke m	ount (option)	VITAM-115RH 15	" XGA IP66/IP69K stainless steel disp wire resistive touch window, 9~36V DC	lay, VGA/HDMI input, OSD on the rear side, C power input with Adapter, 1,000 nits LCD	
IP Ratir	ng	Total IP66/IP69K				lay, VGA/HDMI input, OSD on the rear side,	
Dimens		399 x 324 x 53 mm					

Industrial Panel PC

Industrial Panel PC



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660