

## Aplex Technology PhanTAM-121 Get Quote

<b>nTAM-121AP(H)</b> 21.5" IP66 /	P69K True Flat and Slim Design Stainless Ste	el Display Industrial Panel PC HMI Controller Industrial Box PC Display Monitor
Footuroo		Dimensiona
Features		Dimensions / P
21.5" Fanless	Stainless Steel Display	
	Sealed with Anti-Corrosion Enclosure	
<ul> <li>Ultra Slim Fro</li> </ul>	nt Frame Design	
	nic Bolts on Rear Case	
M12 Connecto	ors with Waterproof Cover	
DC 24V Powe	-	
• 50 240 1 000	input	
		539.4 61.9
Specifica	ntions / 🔎	
IO Port		
VGA	1 x M12 12-pin for VGA with waterproof cover	
HDMI	1 x W.F. Micro-HDMI with waterproof cap	
USB	1 x M12 8-pin for USB Touch with waterproof cover	
OSD Control Membrane	OSD on the rear side	
Power Connector	1 x M12 3-pin for DC power with waterproof cover	
Display	Standard         High Brightness Optional           21.5" TFT-LCD         21.5" TFT-LCD	
Display Type Max. Resolution	1920 x 1080 1920 x 1080	UNIT: mm Tolerance:±0.5
Max. Color	16.7M 16.7M	
Luminance (cd/m <sup>2</sup>		
View Angle	178(H) /178(V) 178(H) /178(V)	
Contrast	1000:1 3000:1	
Backlight Lifetime	50,000 hrs 30,000 hrs	
Touch Screen		
Туре	Projected Capacitive Touch	
Interface	USB	
Light Transmissio	n(%) 90%	
Power		
Power Input	DC 24V	
Power Consumpti	on PhanTAM-121AP: 14.7W (MAX)	
Mechanical		
	304 Stainless steel chassis (default), 316 Stainless steel chassis	
Construction	(optional)	
Mounting	VESA Mount 100 x 100, Swing ARM (optional)	
IP Rating	Total IP66/IP69K	
Dimensions Net Weight	540.4 x 332.4 x 61.5 mm 7.6 kg	
	1.0 Kg	Ordering Information
Environmental		PhanTAM.121AP 21.5" FHD IP66/IP69K stainless steel display, VGA/HDMI input, OSD on the rear
	ature 0~50°C (WT1: -20~60°C for optional)	PhanTAM-121AP 21.5 PhD Poolie'ows statilities steed display, v GVMDM in iput, USD on the tear side, projected capacitive touch, 9~36V DC power input with Adapter
Storage Temperat Humidity	ure -30~70°C 10 to 90% @ 40°C, non- condensing	21.5" FHD IP66/IP69K stainless steel display, VGA/HDMI input, OSD on the rear
Certificate	CE/FCC Class A	PhanTAM-121APH side, projected capacitive touch, 9~36V DC power input with Adapter, 1,000 nits LCD
Germidate		
		V
		Industrial Display
All exercifications and photos	are subject to change without notice.	All specifications and photos are subject to change without notice.



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660