

LMX-0800G Series

8-Port Industrial Managed Ethernet Switch, with 8*10/100/1000Tx Ports; 12~48VDC Power Input



Features


- ▶ Supports 8*10/100/1000Tx RJ45 Ports
- ▶ Network Redundancy: STP/RSTP/MSTP, and G.8032 ERPS (Recovery Time <50ms)
- ▶ Supports IPv4/IPv6, and DHCP Option 66/67/82
- ▶ Supports Modbus/TCP Protocol for Device Management and Monitoring
- ▶ Configuration: Web Console, Telnet, CLI Command
- ▶ IGMP v1/v2 for Multicast Traffic Filtering
- ▶ System Warning Setting for Automatic Warning through E-mail
- ▶ QoS (IEEE802.1p/1Q), CoS/ToS to Increase Determinism
- ▶ IEEE802.1Q VLAN for Easy Network Planning
- ▶ Enhanced Network Security with IEEE802.1X, SNMP v1/v2c/v3, HTTPS, and SSH/SSL
- ▶ Auto Warning by Exception through E-mail, Relay Output
- ▶ Operating Temperature Range: STD: -10° to 70°C, EOT: -40° to 75°C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' LMX-0800G series is an 8-port industrial Gigabit managed Ethernet switch that is embedded with 8*10/100/1000Tx Ethernet ports. The LMX-0800G series is a fully manageable Layer 2 Ethernet switch that is pre-loaded with a user-friendly web management console design. It supports the ring network redundancy function using the market's open standard ITU-T G.8032 ERPS (Ethernet Ring Protection Switch) protocol that has a <50ms network recovery time. The advanced network filtering and security functions, such as, IGMP, VLAN, QoS, SNMP, port lock, RMON, Modbus TCP, and 802.1X/HTTPS/SSH/SSL increase determinism and improve network management for remote SCADA systems or control networks.

The LMX-0800G series is IP30 rated and DIN-rail mountable. There are also two wide operating temperature models for either a standard temperature range (STD: -10°C to 70°C) or an extended temperature range (EOT: -40°C to 75°C). It also provides high EFT and ESD protection for industrial networking applications, such as, power/utility, water wastewater, oil/gas/mining, factory automation, security surveillance within transportation, ITS and any other outdoor or harsh environment.

DIMENSIONS



SPECIFICATIONS

Technology		Protection	
	IEEE 802.3 10Tx Ethernet	Overload Current Protection	Present
	IEEE 802.3u 100Tx Fast Ethernet	Power Reverse Polarity	Present
	IEEE 802.3x Flow Control for Full Duplex	CPU Watchdog	Present
	IEEE 802.3ad for Port Trunk with LACP		10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable; 100Base-TX: 2-pair UTP/STP Cat. 5 cable. EIA/TIA-568 100-ohm (100m)
	IEEE 802.1d STP (Spanning Tree Protocol)	Network Cable	1000BaseTX: UTP/STP Cat.5/5E cable; EIA/TIA-568 100-ohm (100m)
	IEEE 802.1w RSTP (Rapid Spanning Tree Protocol)	Mechanical Characteristics	
Standards	IEEE 802.1s MSTP (Multiple Spanning Tree Protocol)	LED Indicators	Per Unit: Power 1 & 2 (Green), Fault (Green/Red)
	ITU-T G.8032/Y.1344 ERPS (Ethernet Ring Protection Switch) Protocol	Housing	Metal, IP30 rated
	IEEE 802.1Q for VLAN Tagging	Dimension	54 x 142 x 99 mm
	IEEE 802.1x for Network Authentication	Weight	Unit: 2.4 lbs Shipping: 2.9 lbs
	IEEE 802.1p QoS/CoS Protocol for Traffic Prioritization	Mounting	DIN-Rail; Wall-mount (optional)
Switch Properties		Power Requirement	
	IGMPv1/v2, SNMPv1/v2c/v3, TFTP, SNMP, SMTP, RMON, HTTP, HTTPS, Telnet, Syslog, DHCP Option 66/67/82, SSH/SSL, Modbus/TCP, LLDP, IPv4/IPv6, NAT, DHCP per port, SMTP, Quick ERPS, TLS	Input Voltage	12~48VDC Redundant Input
Protocol	Web Console, Telnet, CLI	Power Connection	1 removable 6-contact terminal block
Configuration	Store and Forward	Power Consumption	15 Watts
Processing Type	IEEE 802.3x for full duplex mode, back pressure for half duplex mode	Environmental Limits	
Flow Control	14,880pps for 10Base-T Ethernet	Operating Temperature	STD: -10° to 70°C EOT: -40° to 75°C
Transfer Rate	148,800pps for 100Base-T Fast Ethernet	Storage Temperature	-40°~85°C
	1,488,000pps for Gigabit Ethernet	Ambient Relative Humidity	5 to 95%, (non-condensing)
Packet Buffer	4 Mbits	Regulatory Approvals	
Jumbo Frame	9.6K	EMI	FCC Class A
MAC Table Size	8K	EMS	EN61000-4-2,3,4,5,6,8 EN61000-6-2,4
VLAN Group	0 ~ 4094	Free Fall	IEC60068-2-32
IGMP Group	Up to 256 Group	Shock	IEC60068-2-27
Port Interface		Vibration	IEC60068-2-6
Ethernet Port	8*10/100/1000BaseTx auto negotiation speed, Full/Half duplex mode, and auto MDI connection	Green	RoHS Compliant
RS232 Serial Console	1*RS232 in RJ45 connector with console cable, 115.2Kbps, 8,N,1	Certifications	FCC, CE, UL 61010-1, UL 61010-2-201
Configuration Backup	1*USB 2.0	Warranty	5 Years

ORDERING INFO

LMX-0800G	8-Port Industrial Managed Ethernet Switch, with 8*10/100/1000Tx Ports; 12~48VDC Power Input
LMX-0800G-T	8-Port Industrial Managed Ethernet Switch, with 8*10/100/1000Tx Ports; 12~48VDC Power Input; EOT: -40° to 75°C

Optional Accessories

MDR-60-24	60W Industrial Din Rail Power Supply, 24VDC
MDR-60-48	60W Industrial Din Rail Power Supply, 48VDC
DR-75-48	75W Industrial Din Rail Power Supply, 48VDC
DIN-RACK-2U	DIN-Rail to 19" Rack Mount Adapter for all DIN-Rail Mountable Products, 2U Height

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660