

EMS-EHL-USB

Intel® Elkhart Lake Atom®/Celeron®
Processor Fanless Rugged Embedded System,
w_ USB IET Module



Product Features

- Intel® Celeron®/Atom™ J6413/x6425E SoC BGA Processor
- Rich I/O, 8-USB3.2, 3-USB2.0, 1-DP, 1-HDMI, 2-COM, 2-LAN, 1-8bit GPIO
- Fanless operation temperature from -40°C ~ 70°C (WT) / 0°C ~ 65°C (ST)
- Wide range DC power input from +9~36V
- Support IET modules
- 1 x 260-pin SODIMM socket Max. up to 32GB DDR4 3200MT/s
- Support 5G (Sub-6G) module, HDMI 2.0b (4K @ 60Hz), LAN 2.5G Base-Tx GbE
- CE, FCC Class B, LVD 62368-1, IP50
- Support HW TPM 2.0

Specification

System Information

Processor	Intel® Celeron® Processor J6413 (1.5M Cache, up to 3.00Ghz), ST, Tj=105°C Intel® Atom® Processor x6425E(1.5M Cache, up to 3.00Ghz), WT, Tj=-40°C ~105°C
System Memory	1 x 260-pin SODIMM socket Max. Up to 32GB DDR4 3200 MT/s
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	CPU & system temperature monitoring and Voltages monitoring
TPM	TPM 2.0
SBC	EBM-EHLS

Expansion

M.2	1 x M.2 Key-B 2242/3042/3052 support SATA3/ PCIe III/ USB3.2 Gen.1 and SIM slot1 (internal), default support 3.3V, jumper setting to adjust 3.3V/ 3.8V 1 x M.2 Key-E 2230 for Wi-Fi & BT Module (USB2.0/ PCIe III)
------------	---

Storage

M.2	1 x M.2 Key-B 2242/2280, support SATA 1 x M.2 Key-B 2242, support SATA (share with expansion slot)
------------	---

Rear I/O

USB	3 x USB 2.0 6 x USB 3.1 Gen.1 (5Gbp/s), via USB Hub 2 x USB 3.1 Gen.2 (10Gbp/s)
------------	---

LAN Port	2 x RJ45
-----------------	----------

Audio	1 x Mic-In, 1 x Line-Out
--------------	--------------------------

DP	1 x DP 1.4
-----------	------------

HDMI	1 x HDMI 2.0b
-------------	---------------

Antenna	2 x Antenna with dust cover
----------------	-----------------------------

Right I/O

Antenna	2 x Antenna with dust cover
----------------	-----------------------------

Left I/O

Antenna	2 x Antenna with dust cover
----------------	-----------------------------

Display

Graphic Chipset	Intel® UHD Graphics for 10th Gen Intel® Processors
------------------------	--

Resolution	DP++ 1.4: 4096x2304 @ 60Hz HDMI 2.0b : Max. resolution 4096x2304 @ 60Hz
-------------------	--

Audio

Audio Codec	Realtek ALC888S (co-lay with ALC897) HD codec
--------------------	---

Ethernet

LAN Chipset	2 x Intel I226-IT
--------------------	-------------------

Specification	2 x 10/100/1000/2.5G Base-Tx GbE compatible
----------------------	---

Power Requirement

ACPI	Single power ATX Support S0,S3, S4, S5 ACPI 5.0 Compliant
-------------	--

Power Mode	AT/ATX (ATX is default setting)
-------------------	---------------------------------

Software Support

OS Win 10 64bit / Win 11 64 bit/ Linux

Certification

Certification Information CE, FCC Class B, LVD 62368-1

Mechanical & Environmental

Operating Temp. -40°C ~ 70°C (w/SSD) ambient w/ 0.5 air flow, WT sku, x6425E
 -40°C ~ 60°C (w/SSD) ambient w/ 0.2 air flow, WT sku, x6425E
 0°C ~ 65°C (w/SSD) ambient w/ 0.5 air flow, ST sku, J6413
 0°C ~ 55°C (w/SSD) ambient w/ 0.2 air flow, ST sku, J6413

Storage Temp. -30°C ~ 70°C (-22°F ~ 158°F)

Operating Humidity 40°C @ 95% Relative Humidity, Non-condensing

Dimension (W x L x H) 240mm x 150mm x 64 mm (w/ IET module)

Weight 1.9 kg (System)
 2.7 kg (w_Package)

Vibration Test With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis

Shock Test With SSD : 55Grms, IEC 60068-2-27, Half Sine, 11ms

IP Rating IP 50

Mounting Kit Wall mount kit (standard)
 DIN RAIL (optional)

Ordering Information

Ordering Information Intel® Elkhart Lake Atom®/Celeron® Processor Fanless Rugged Embedded System, w_USB IET Module

EMS-EHL-X64-A1-8R (x6425E)
 EMS-EHL-J64-A1-8R (J6413)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660