



## HPM-621DE

Intel® dual 2nd Gen. Xeon® Scalable Processors  
EATX Server Board With Intel® C621 Chipset,  
IPMI2.0

Processor supports up to 150W TDP

- > Dual Intel FCLGA3647 Sockets support 1st and 2nd Gen. Intel Xeon Scalable Processors (Max. TDP at 150W Each)
- > Intel C621 Chipset
- > 12 x DDR4 2933/ 2666/ 2400/ 2133 MHz RDIMM/ LRDIMM Up to 1.5TB
- > TPM 2.0 onboard
- > IPMI 2.0 with AST 2500 BMC controller onboard
- > 4 x Intel I210AT Giga-bit Ethernet
- > 10 x SATA III Support RAID 0,1,5,10
- > 2 x internal RS232 ports
- > 4 x USB 3.2 Gen1 ports at Edge I/O
- > 2 x internal USB 2.0 Ports
- > 2 x internal USB 3.2 Gen1 Ports
- > 1 x M.2 M-Key PCIe 3.0 x4 NVMe SSD, 2242/2260/2280 form factor
- > 12" x 13" (304.8mm x 330.2mm), PCB thickness is 2.0mm

**Spec**

System Information	
<b>Processor</b>	Dual Intel FCLGA3647 Sockets support 1st and 2nd Gen. Intel Xeon Scalable Processors (Max. TDP at 150W Each)
<b>Platform Controller Hub</b>	Intel C621 Chipset
<b>System Memory</b>	12 x DDR4 2933/ 2666/ 2400/ 2133 MHz RDIMM/ LRDIMM up to 1.5TB
<b>BIOS Information</b>	AMI UEFI BIOS
<b>Watchdog Timer</b>	System Reset Event. 0 ~ 6553 seconds
<b>H/W Status Monitor</b>	CPU temperature, Fan speed and voltage monitoring, Fan speed control, and Case Open detection
<b>TPM</b>	TPM 2.0 onboard
<b>iAMT</b>	IPMI 2.0 with AST 2500 BMC controller onboard
-Rear I/O-	
<b>USB Port</b>	4 x USB 3.2 Gen1 ports
<b>RJ-45</b>	4 x RJ45 (LAN1 share IPMI port)
-Display-	
<b>Graphic Chipset</b>	AST 2500 BMC controller
<b>Resolution</b>	1 x VGA port VGA: 1920 x 1200 @ 60Hz 32bpp
Expansion	
<b>Expansion</b>	4 x PCIe x16 slots, 2 x PCIe x8 slots, 1 x PCI 3.0 slot Slot 1, PCIe 3.0 x16 from CPU1 Slot 2, PCI 3.0 Slot 3, PCIe 3.0 x16 from CPU1 Slot 4, PCIe 3.0 x16 from CPU2 Slot 5, PCIe 3.0 x16 from CPU1 Slot 6, PCIe 3.0 x8 from CPU1 Slot 7, PCIe 3.0 x8 from CPU1 (Slot 7 is the slot closest to CPU)
Storage	
<b>M.2</b>	1 x M.2 M-Key PCIe 3.0 x4 NVMe SSD, 2242/2260/2280 form factor
I/O	
<b>USB Port</b>	2 x internal USB 2.0 ports 2 x internal USB 3.2 Gen1 ports
<b>SATA</b>	10 x SATA III Support RAID 0,1,5,10
<b>Serial</b>	2 x internal RS232 ports
<b>VGA</b>	1 x internal VGA port
<b>CMOS Battery</b>	1 x Horizontal Socket Type CMOS Battery Holder with CR2450
<b>Other</b>	4 x OcuLink ports from CPU 2 for U.2 SSD
Ethernet	
<b>LAN Chipset</b>	4 x Intel I210AT Giga-bit Ethernet
<b>LAN Port</b>	4 x RJ45 (LAN1 Share IPMI Port)
Mechanical & Environmental	
<b>Operating Temperature</b>	0 ~ 60°C (32 ~ 140°F)
<b>Storage Temperature</b>	-40 °C ~ 85 °C
<b>Operating Humidity</b>	40°C @95% Relative Humidity, Non-condensing
<b>Weight</b>	1.8Kg
<b>Power Connector</b>	1 x Std. 24 Pin ATX connector 2 x 8 Pin SSI 12V connector
<b>Dimension (L x W)</b>	12" x 13" (304.8mm x 330.2mm), PCB thickness is 2.0mm
Software Support	
<b>OS Information</b>	Windows 10 IOT Enterprise Windows Server 2016 Windows Server 2019
Ordering Information	
<b>Ordering Information</b>	HPM-621DEA-A1R EATX 2xLGA3647 Intel 1st/2nd Gen. C621 w/12xDDR4/4xPCIex16/4x1GbE/6xUSB3.1/10xSATA3.0

[www.avalue.com.tw](http://www.avalue.com.tw)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660