

# AX69150/AX69158

1U 15" LCD Rackmount Monitor/Keyboard Drawer  
with Optional 8-port KVM



## Features

- Industrial level input device for space-critical environments
- 15" TFT LCD display supports XGA (1024 x 768) resolution
- Compact design, only 492 mm depth
- LED display for status indicating grade
- Integrated keyboard/touchpad
- OSD (On Screen Display) function for LCD display
- Built-in power supply
- Knob lock and slide rail lock
- Tempered glass to protect LCD panel

## Specifications

Housing	Meets EIA RS-310C standard 1U 19" (482.6 mm) rackmount, black color or RAL 7035	Integrated Mousepad	PS/2, high-quality touchpad with mouse buttons Interface: DB25 system port
Construction	SECC	MTBF	30,000hrs
LCD	15" TFT LCD panel display with built-in power saving and back light protection functions	Power Supply	90 ~ 264 V <sub>AC</sub> , 47 ~ 63 Hz AC PSU auto-switching
Display Size	15" (381 mm) diagonal	Power Consumption	26.25W
Pixel Pitch (H x V)	0.297 x 0.297 mm	Viewing Area (W x H)	11.98" x 8.99" (304.1 x 228.1 mm)
Maximum Resolution	XGA (1024 x 768)	Dimensions	440 mm (17.34") (W) x 44 mm (1.73") (H) x 492 mm (19.38") (D)
Contrast Ratio	500:1 (typical)	Weight (net weight)	24.2 lb (11 kg)
Brightness	250 nits	Operating Environment	Temperature: 0° to 45° C (32° F to 113° F) Humidity: 20 to 90% @ 40° C (104° F), non-condensing Altitude: 10,000-feet (3048-meters) Shock: 10 g, 11 ms duration, half sine/six axis Vibration: 10 to 58 Hz, ±0.075 mm; 58 to 500 Hz, 1 g
Response Time	Tr: 10 ms; Tf: 30ms	Non-Operating Environment	Temperature: -40° to 70° C (-13° F to 158° F) Humidity: 5 to 95% @ 40° C (104° F), non-condensing Altitude: 50,000-feet (15,240-meter) Shock: 15 g, 11 ms duration, half sine/six axis Vibration: 10 to 58 Hz, ±0.15 mm; 58 to 500 Hz, 2 g
Scanning Frequencies	Vsync: 58 ~ 75 Hz Hsync: 46.8 ~ 60.2 kHz		
Display Colors	16.77 million		
LCD panel protection	Anti-glare glass with hard coating to protect LCD panel (2 x 249 x 333 mm)		
Viewing Angle	Horizontal: 60/60 degrees from center Vertical: 45/55 degrees from center		
Signal Connector	15-pin mini D-sub		
Monitor Control Type	Digital microprocessor OSD control		
Screen Adjustment	Menu, auto adjustment, brightness, contrast, phase, H/V		
Controls	position pitch, zoom, color, language and OSD position		
Plug & Play	DDC1/2 B		
Keyboard	PS/2, 88-key plus numeric keypad		

## Ordering Information

Standard	
AX69150	1U 15" TFT monitor/keyboard drawer with notebook keyboard and touchpad
AX69158	1U 15" TFT monitor/keyboard drawer with 8-port KVM, notebook keyboard and touchpad
KVM Cable Option	
59069178000E	1-port KVM cable

## Packing List

1U monitor/keyboard drawer  
Two sets of L-brackets for rear mount (screws included)  
AC power cord  
Utility CD  
One set KVM cable only

Overview

Embedded Systems

Embedded Systems for Transportation

Embedded Field Controllers

Embedded MicroBoxes

Industrial Barebone Systems

Industrial Chassis

Industrial Workstations

Backplanes

Power Supplies

Peripherals & Accessories

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660