

LMX-2602G-SFP Series

26-Port Industrial Gigabit Managed Ethernet Switch, w/24*10/100/1000Tx RJ45 and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)



Features

- ▶ 24-port 10/100/1000Tx Ethernet
- ▶ 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)
- ▶ Configuration: http, https, CLI Command, Telnet, SNMP, SSH
- ▶ Network redundancy support: G.8032 ERPS v2/STP/RSTP/MSTP
- ▶ System Power Input: 90~264VAC
- ▶ Built-in Relay Output Warning for Power Failure
- ▶ IP40 Rugged Metal Case Design
- ▶ 19" Rack-Mounting Installation Design
- ▶ Operating Temperature Range - STD: -10°C to 65°C, EOT: -40°C to 75°C
- ▶ 5-Year Warranty


INTRODUCTION

Antaira Technologies' **LMX-2602G-SFP series** is a 26-port industrial gigabit managed Ethernet switch featuring 24*10/100/1000Tx Ethernet ports and also provides 2*gigabit combo ports with 2*10/100/1000Tx RJ45 and 2*100/1000Fx SFP slots for fiber or twisted pair connections. This product is ideal for applications that demand high density of port connectivity, wide bandwidth and long-distance communication.

The LMX-2602G-SFP series is a fully manageable Layer 2 Ethernet switch that is pre-loaded with a user-friendly web management console design. It supports the ring network redundancy function using the market's open standard ITU-T G.8032 ERPS (Ethernet Ring Protection Switch) protocol that has a <50ms network recovery time. The advanced network filtering and security functions, such as IGMP, VLAN, QoS, SNMP, port lock, RMON, Modbus TCP, and 802.1X/HTTPS/SSH/SSL increase determinism and improve network management for remote SCADA systems or control networks.

The LMX-2602G-SFP series is designed with IP40 rated 1U 19" rackmount. Supporting the two wide operating temperature models with the standard version in -10° to 65°C or extended version in -40° to 75°C also makes it the best solution for any harsh and extreme ambient weather environment applications, such as power/utility, transportation, water wastewater treatment plant, oil/gas, and security surveillance system industries.

DIMENSIONS



SPECIFICATIONS

Technology		IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Fiber IEEE 802.3x Flow Control IEEE 802.1d STP (Spanning Tree Protocol) IEEE 802.1w RSTP (Rapid Spanning Tree Protocol) IEEE 802.1s MSTP (Multiple Spanning Tree Protocol)
Standards		ITU-T G.8032 / Y.1344 ERPS v1/v2 (Ethernet Ring Protection Switch) IEEE 802.1Q Virtual Local Area Network (VLAN) IEEE 802.1p QoS/CoS Protocol for Traffic Prioritization IEEE 802.1X Network Authentication IEEE 802.1AB Link Layer Discovery Protocol (LLDP) IEEE 802.3ad Link Aggregation (LACP)
Switch Properties		
Switch Architecture	Back-Plane (Switching Fabric): 52.0Gbps CSMA/CD, IGMP v1/v2, SNMP v1/v2c/v3, TFTP, SNMP, RARP, RMON, Syslog, NAT, DHCP per port, SMTP, Quick ERPS, TLS	
Protocols	Store and Forward IEEE 802.3x flow control, back pressure flow control	
Processing Type	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port	
Flow Control	4Mbits	
Transfer Rate	9.6Kbytes	
Packet Buffer	8K	
Jumbo Frame		
MAC Table Size		
Port Interface		
Ethernet Port	24*10/100/1000BaseT(X) and 2*10/100/1000BaseT(X) with combo port Auto-Negotiation, Full/Half Duplex, Auto-MDI/MDI-X	
Gigabit Combo Port (Copper/SFP)	2*RJ45 Ports w/10/100/1000Tx Ethernet and 2*100/1000 SFP Slot	
Wavelength	Depends on SFP modules	
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m) 1000Base-TX: 4-pair UTP/STP Cat.5/5E cable; EIA/TIA-568 100-ohm (100m)	
Protection		
Overload Current Protection	Present (Slow-Blow Fuse)	
Reverse Polarity Protection	Present	
Mechanical Characteristics		
Housing	Metal, IP40 Protection	
Dimensions	440 x 200 x 44 mm	
Weight	Unit: 6.17lbs Shipping: 7.94lbs	
Mounting	DIN-Rail, Wall-mount (Optional)	
Power Requirement		
Input Voltage	90~264VAC Power Input	
Power Connection	AC Socket	
Power Consumption	Max 24W full loading	
Environmental Limits		
Operating Temperature	STD: -10°C to 65°C EOT: -40°C to 75°C	
Storage Temperature	-40°C to 85°C	
Ambient Relative Humidity	5% to 95%, (non-condensing)	
Regulatory Approvals		
EMI	FCC Part 15 Subpart B Class A, CE EN61000-6-4 Class A CE EN61000-6-2 Class A IEC61000-4-2 (ESD) IEC61000-4-3 (RS)	
EMS	IEC61000-4-4 (EFT) IEC61000-4-5 (Surge) IEC61000-4-6 (CS) IEC61000-4-8 (Magnetic Field)	
Free Fall	IEC60068-2-32	
Shock	IEC60068-2-27	
Vibration	IEC60068-2-6	
Green	RoHS Compliant	
Certifications	FCC, CE	
Warranty	5 Years	

ORDERING INFO

LMX-2602G-SFP	26-Port Industrial Gigabit Managed Ethernet Switch, w/24*10/100/1000Tx RJ45 and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)
LMX-2602G-SFP-T	26-Port Industrial Gigabit Managed Ethernet Switch, w/24*10/100/1000Tx RJ45 and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots); EOT: -40°C to 75°C

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660