

DFI-ACP

ORavision Control OLong Life Cycle



Intel® G41 ATX Board

PROCESSOR

- LGA 775 socket supports:

 Inte № Core № 2 Duo E8400/E7400/E6400/E4300

 Inte № Pentium® E6500/E5300/E2160

 Inte № Celeron® E3400/E1500/440

- Intel Enhanced Memory 64 Technology (EM64T)
- Enhanced Intel Speed Step Technology (EISI) 1333/1066/800MHz FSB

- Inte l® c hip se t
 - Inte l[®] G 41 Exp re ss c hip se t
 - Intel® ICH7 I/O Controller Hub

SYSTEM MEMORY

- Two 240-pin DDR3 DIMM sockets Supports DDR3 800/1066MHz DIMM
- Maximum memory bandwidth of 17GB/s in dual-channel mode when using DDR3 1066MHz
- Supports dual channel me mory interface Supports up to 4GB system me mory
- Supports unbuffered x8 and x16 DIMMs

EXPANSION SLOTS

- 5 PCI slots (PCI 2.3)
- 3 ISA slots

Note: 1 PCI and 1 ISA are shared slots.

ONBOARD GRAPHICS FEATURES

- Integrated Intel GMA X4500
- 3D, 2D and video capabilities, DX10 and OpenGL2.1
- Display ports: DVFI(ChrontelCH7307C) and VGA

ONBOARD AUDIO FEATURES

- Realtek AIC 262 2-channel High Definition Audio High performance DACs with 100dB SNR
- ADCs with 90dB SNR
- Two stere o DACs support 24-bit PCM format for stere o audio playback
- Three stereo ADCs support 20-bit PCM format for multiple input streaming S/PDIF audio interface

ONBOARD LAN FEATURES

- 2 Realtek RTI8111DLPC I Express Gigabit Ethemet controllers
- 10Mbps, 100Mbps and 1Gbps data transmission
- EEE 802.3u (10/100Mbps) and EEE 802.3ab (1Gbps) compliant

SERIAL ATA (SATA) INTERFACE

- 4 Senal ATA ports compliant with SATA 1.0a specific ation
 SATA speed up to 3Gb/s (SATA 2.0)

- Winbond W83627DHG-P: supports 8-bit Digital I/O and
- Finte k F81217U: supports COM1 to COM4
- Finte k F81217U: supports COM5 to COM8

- IIE II8888G: PC I to ISA slot bridge
- 3 ISA slots
- Does not support ISA Master devices and ISA DMA devices

REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 2 DB-9 se rial ports
- Supports $\hat{RS}232/422/485$
- Pins 1 and 9 of RS232 functions as RS232 signal or power (se le c ta b le via jumper)
- 1 DB-15 VGA port
- 1 DVII port (DVID signal only) 2 RJ45 IAN ports
- 4 USB 2.0/1.1 ports
- Mic-in, line-in and line out jacks

- 2 connectors for 4 external USB 2.0/1.1 ports
- 6 connectors for 6 external RS232 serial ports 1 8-bit Digital VO connector
- 1 front audio connector for line-out and mic-in jacks
- 1 CD-in connector

- 1 S/PDIF connector 4 Serial ATA connectors 1 40-pin IDE connector
- 1 25-pin parallel connector 1 24-pin ATX power connector
- 1 4-pin 12V power connector 1 chassis intrusion connector
- 1 front panel connector 3 fan connectors

- AMI BIOS
 8Mb it SPI BIOS

ENERGY EFFICIENT DESIGN

- ACPI v3.0b specific ation
- System Power Management
- Wake-On-Events include:
- Wa ke -O n-PS/2 KB/ Mo use Wa ke -O n-USB KB/ Mo use
- Wake-On-IAN

 Mic ro so ft[®]/ Inte I[®] APM 1.2 c o mp liant

 AC power failure recovery

DAMAGE FREE INTELLIGENCE

- Monitors CPU/System/NB temperature and overheat alarm Monitors CPU/DIMM/NB/5V/12V/1.1V/VBATvoltages and
- Monitors CPU/System/2nd fan speed and failure alam Read back capability that displays temperature, voltage
- and fan speed

 Watchdog timer function

TEMPERATURE

• 0°C to 60°C **HUMIDITY**

10% to 90%

- ATX form factor
 305mm (12") x 244mm (9.6")





DFI reserves the right to change the specifications at any time prior to the product's release.

Changes there after will be based on the product's revision. Please contact your sales representative for the exact revision offered in your area. All product names mentioned are trademarks of their respective companies.

© September 29, 2011 DFI Inc.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660