



## 4-CH Lighting Control Module

## **Features**

- 4-CH independent constant current LED drivers (up to 1 A)
- Supports strobe and trigger mode
- Intensity control by software
- Supports duration and delay time for LED output





#### **Specifications**

Channels	4-CH
Drive Methods	Current-controlled
Operating Mode	Strobe, Trigger
Output Current	Trigger mode 0.5A per CH Strobe mode 1A per CH
Output Voltage	24 VDC
Duration time	Trigger mode 10ms to 65s Strobe mode 10us to 10ms
Output current step size	50mA by software
I/O Connector	8 pin terminal connector (black)
Power Connector	6-pin ATX power connector
Power Requirements	Trigger mode 60W @12 VDC Strobe mode 120W @12 VDC
Dimensions	151 x 80 mm

#### **Ordering Information**

AX92353	4-CH lighting control module (this optional module cannot be
	operating independently, please apply with AX92352.)

#### **Packing List**

CN-terminal block 4 x 2, cable (communication with AX92352)



Updated Apr. 15, 2020.

\* All specifications and photos are subject to change without notice. 

www.axiomtek.com © 2020 Axiomtek Co., Ltd. All rights reserved.

112



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

#### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660