



VMS-CFS-SLIM

Intel® 8th/9th Coffee Lake Rugged Fanless Vehicle Telematics System

- > 第8/9代英特尔® 处理器 (6核/8核)
- > 英特尔® Q370芯片组
- > 英特尔®超高清图形 630/610
- > 最大内存可达 64GB DDR4 2666
- > mPCIe, M.2 Key-E, M.2 Key-B 扩展槽
- > -40C~70C 工作温度
- > 9~36Vdc 输入, 带车辆电源管理
- > 支持 RAID 0/1, TPM 2.0, iATM 12.0
- > CE, FCC, IP50, E Mark, ISO7637-2 认证

Spec

System Information	
Processor	Intel® Core™ i7-8700T Processor (12M Cache, up to 4.00 GHz) Intel® Core™ i5-8500T Processor (9M Cache, up to 3.50 GHz) Intel® Core™ i3-8100T Processor (6M Cache, 3.10 GHz) Intel® Pentium® Gold G5400T Processor (4M Cache, 3.10 GHz) Intel® Celeron® G4900T Processor (2M Cache, 2.90 GHz) Intel® Core™ i7-9700TE Processor (12M Cache, up to 3.80 GHz) Intel® Core™ i5-9500TE Processor (9M Cache, up to 3.60 GHz) Intel® Core™ i3-9100TE Processor (6M Cache, up to 3.20 GHz)
Platform Controller Hub	Intel® Q370 Express Chipset
System Memory	2 x 260-pin DDR4 SODIMM 2400/2666MHz up to 64 GB
Watchdog Timer	H/W Reset, 1sec. ~ 65535min.
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
TPM	TPM 2.0 (Firmware)
SBC	EBM-CFSV
-Expansion-	
M.2	1 x M.2 Key-E 2230 for Wi-Fi & BT Module 2 x M.2 Key-B 2242/3042/2280 w/ push-push SIM slot for SSD/ LTE/ I/O Modules 1 x CANBus (supports OBDII, SAE J1939/ J1708)
IET	1 x Avalue 80-Pin IET Interface
mPCIe	1 x Full Size Mini PCIe (w/ push-push SIM Slot)
-Storage-	
M.2	2 x M.2 Key-B SSD (SATA III, Max. up to 2280)
-Front I/O-	
USB Port	2 x USB 3.2 Gen.1
Audio	1 x Line-Out 1 x Mic-In
Power Button	1 x Push Button for Power on/off w/ LED
Reset Button	1 x Push Button for Reset in hiding
LED Indicator	3 x LEDs for Storage, WLAN/ HSDPA
Digital I/O	1 x 8-bit GPIO, supports 1.5KV Isolation
SIM Slot	3 x SIM Card Slot (External Accessible w/Dust Protection Cover)
-Rear I/O-	
USB Port	4 x USB 3.2 Gen.1
COM Port	2 x RS232/422/485, (Jumper + DIP switch), with +5V and +12V support on Pin-9 via Jumper + DIP switch, support auto-flow (COM1 onboard, COM2 via Cable)
HDMI	2 x HDMI
DP	1 x DP
Audio	1 x Line-Out 1 x Mic-In
RJ-45	2 x RJ-45
CAN Bus	1 x CANBus (supports OBDII, SAE J1939/ J1708), share with COM2
-GPS-	
Chipset	Onboard u-blox NEO-M8N module supports GPS/ Glonass/ QZSS/ Galileo/ Beidou
Sensitivity	Industry leading -167 dBm navigation sensitivity Product variants to meet performance and cost requirements Combines low power consumption and high sensitivity
-Display-	
Graphic Chipset	Intel® UHD Graphics 630 (i7-8700T, i5-8500T, i3-8100T) Intel® UHD Graphics 610 (Pentium G5400T, Celeron G4900T)
Resolution	DP: Max. resolution 4096x2160 @ 60Hz HDMI: Max. resolution 4096x2160 @ 30Hz
-Audio-	

www.avalue.com.tw

Audio Codec	Realtek ALC888S supports 2-CH
-Ethernet-	
LAN Chipset	1 x Intel® I211AT 1 x Intel® I219LM
Specification	10/100/1000 Base-Tx GbE compatible
-Power Requirement-	
DC Input Voltage	Typical 12/24Vdc (+9~ 36Vdc)
DC Input Connector	3-Pin Terminal Block
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI5.0 Compliant
Power Mode	Vehicle Power Mode (Default Setting) Industrial PC Power Mode supports AT/ATX
-Software Support-	
OS Information	Win10, Linux
-Certification-	
Certification Information	CE, FCC Class A, E13 Mark, ISO 7637-2, IP50
Mechanical & Environmental	
Operating Temperature	-40°C ~ 70°C (-40°F ~ 158°F) with 0.5m/s air flow, extended temperature peripherals
Storage Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	239.4mm x 210mm x 75 mm(w/o wall mount)
Weight	TBD
Vibration Test	Operating with SSD : MIL-STD-810G, Method 514.6, Category 4, common carrier US highway truck vibration exposure Non-Operating with SSD : MIL-STD-810G, Method 514.6, Category 24, minimum integrity test
Shock Test	Operating with SSD : MIL-STD-810H, Method 516.8, Procedure I, functional shock=20G Non-Operating with SSD: MIL-STD-810H, Method 516.8, Procedure V, crash hazard shock test=75G
Mounting Kit	Wall Mount kit (Standard)
Construction	Aluminum + Metal
Ordering Information	
Ordering Information	With Intel® Q370 Chipset VMS-CFS-87-B1-4R (i7-8700T) VMS-CFS-85-B1-4R (i5-8500T) VMS-CFS-81-B1-4R (i3-8100T) VMS-CFS-54-B1-4R (Pentium Gold G5400T) VMS-CFS-49-B1-4R (Celeron G4900T) VMS-CFS-97-A1-4R (i7-9700TE) VMS-CFS-95-A1-4R (i5-9500TE) VMS-CFS-91-A1-4R (i3-9100TE)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660