

Matrix-522

Linux-ready ARM9 Industrial Box Computer



Features

- ATMEL 400MHz ARM9 AT91SAM9G20 CPU
- Linux kernel 2.6.29 with file system
- 64MB SDRAM and 256MB NAND Flash
- 1 x microSD socket inside, up to 32GB capacity
- 2 x CAN bus ports support SocketCAN / CANOpen
- 2 x 10/100Mbps Ethernet ports
- 2 x RS-232 / 422 / 485 serial ports
- 2 x USB hosts, 21 x GPIOs
- Ultra-low power consumption, less than 3 Watts

H/W Specifications

CPU / Memory

- CPU: ATMEL 400MHz AT91SAM9G20 w/ MMU
- Memory: 64MB SDRAM, 256MB NAND Flash
- DataFlash@: 2MB, for system backup

Network Interface

- Type: 2 x 10/100BaseT, RJ45 connector
- Protection: 1.5KV magnetic isolation

TTY (Serial) Ports

- 2 x RS-232 / 422 / 485
- Connector: DB9 male connector

TTY (Serial) Port Parameters

- Baud Rate: Up to 921.6Kbps
- Parity: None, Even, Odd, Mark, Space
- Data Bits: 5, 6, 7, 8
- Stop Bits: 1, 1.5, 2
- Flow Control: RTS / CTS, XON / XOFF, None
- RS-485 Direction Control: Auto, by hardware

USB Ports

- Host Ports: 2
- Client Port: 1, reserved
- Speed: USB 2.0 compliant, supports low-speed (1.5Mbps) and full-speed (12Mbps) data rate

Digital I/Os (GPIO)

- No. of Pins: 21
- Signal Level: CMOS / TTL compatible
- Each pin can be programmed as input or output

CAN Bus Ports

- Type: 2 x CAN bus 2.0A/B compliant ports
- Speed: Up to 1Mbps
- Isolation: 2500Vrms
- Connector: DB9 male connector

General

- Watchdog Timer: Yes
- Real Time Clock: Yes
- Buzzer: Yes
- Power Input: 9~40VDC
- Power Consumption: 190mA@12VDC
- Dimensions (W x H x D): 160 x 104 x 32mm

S/W Specifications

General

- OS: Linux, kernel 2.6.29
- Boot Loader: U-Boot 1.1.2
- File Systems: UBI, JFFS2, ETX2 / ETX3, VFAT / FAT, NFS

Pre-installed Utilities

- bash, busybox, sysvinit, wget, ipkg, procps (for webmin), psmics, lighttpd, vsftpd, iptables, ppp, ssh, wireless_tools, util-linux-mount / umount, usbutils, Artila utility, and more

Daemons Started by Default

- ssh (secured shell) with sftp
- syslog / klogd (system and kernel log)
- telnet server (disable root permission in /etc/securetty)
- ftp server (vsftpd)
- web server (lighttpd)
- amgrd (Artila broadcast search daemon)

Package Management & System Administration

- Supports ipkg to manage the package installation, upgrade and removal
- Supports webmin (use 'ipkg install webmin' to install) for web-based system administration

Toolchain for Linux

- GCC: C / C++ PC cross compiler
- GLIBC: POSIX Library


USB Host Drivers

- Generic Flash drive
- RS-232 adapters (for Prolific PL-2303 compatibles)
- WiFi dongles (rt2500 / rtl8187 / rt73 / zd1211 chips)

Ordering Information

- **Matrix-522**
Linux-ready ARM9 Industrial CAN Bus Box Computer
- **CBL-F10M9-20 (91-0P9M9-001)**
Console Cable (10Pin Header to DB9 Male, 20cm)
- **DK-35A (36-DK35A-000)**
DIN RAIL Mounting Kit

Rear View



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660