



Embedded Communication & Computing

sales@artila.com http://www.artila.com

Matrix-514

Linux-ready ARM9 Embedded Computer

- 100% Linux 2.6.x compatible computing platform
- 64MB SDRAM and 16MB Flash
- Ultra-low power consumption, less than 3 Watts
- Four 10/100Mbps Ethernet ports
- Four 921.6Kbps RS-232/422/485 TTY ports
- Two USB 2.0 host ports for add-on functionality expansion
- One SD memory card slot inside for storage expansion
- ▼ Twenty-one TTL-level digital I/Os (GPIO)
- ☑ GNU C/C++ tool chain for Linux/Windows environment



Introduction

The Matrix-514 is a mini-mighty Linux-ready ARM9-based computing platform for embedded headless run-only application. It comes equipped with four Ethernet, four RS-232/422/485 TTY ports, two USB host ports, plus one internal SD memory card slot and twenty-one CMOS/TTL-level GPIOs in an incredible small package measuring only 160x104x32 mm.

■ 100% Linux Compatible , Hassle Free

The Matrix-514 is a true Linux computing platform and it supports versatile file systems. Users can operate the Matrix-514 the same way as they do on a normal Linux deskton.

Support Wire and Wireless Networking

The Matrix-514 comes with four standard 10/100Mbps Ethernet ports for wired networking. In addition, it is easy to add IEEE-802.11b/g WiFi support by simply plugging an USB WiFi dongle into the Matrix-514.

9-40VDC 2x USB Host

21x GPIO

Four 921.6Kbps TTY Ports

Also, the Matrix-514 provides four 921.6Kbps RS-232/422 /485 TTY ports. Port 2 features full RS-232 supporting for modem connection. Port 1, Port 3 and Port 4 support standard RS-232.

Twenty-one TTL-level GPIOs

The Matrix-514 comes with twenty-one CMOS/TTL-level digital I/Os. Each pin can be individually programmed as input or output.

Optional 2GB SD Card for Data Storage

Users can install one standard SD Flash memory card, up to 2GB now, into the Matrix-514 as an additional hard drive.

GNU Tool Chain for Application Development

Open-source GNU Tool Chain, including C/C++ cross-compiler and POSIX standard C/C++ library, is bundled with the Matrix-514 for free.







Embedded Communication & Computing

sales@artila.com http://www.artila.com

H/W Specifications

CPU/Memory

- CPU: ATMEL 180MHz AT91RM9200 (ARM9, w/MMU)
- Memory: 64MB SDRAM, 16MB Flash

Network Interface

- No. of ports: four
- Type: 10/100BaseT, RJ-45 connector
- Protection: 1.5KV magnetic isolation

TTY (Serial) Ports

- Four RS-232/422/485 ports, software select
- Port 2: supports full modem signals
- Connector: DB9 male connector

TTY (Serial) Port Parameters

- Baud Rate: up to 921.6 Kbps
- Parity: None, Even, Odd, Mark, Space
- Data Bits: 5,6,7,8
- > Stop Bit: 1, 1.5, 2 bits
- Flow Control: RTS/CTS, XON/XOFF, None

USB Host Ports

- No. of ports: two
- Speed: USB 2.0 compliant, supports low-speed (1.5Mbps) and full- speed (12Mbps) data rate

Digital I/Os (GPIO)

- No. of pins: twenty one pins
- ▶ Signal level: CMOS/TTL compatible
- Each pin can be programmed as input or output

Mass Storage

Done SD 1.0 compliant socket inside

General

- WatchDog Timer: yes, for kernel use
- Real Time Clock: yes
- Buzzer: yes
- Power input: 9~40VDC
- Power consumption: 300mA@12VDC
- Dimension: 160 x 104 x 32mm
- Operation Temperature: 0 to 70C (32 to 158F)
- Regulation: CE Class A, FCC Class A

S/W Specifications

Canara

- OS: Linux, kernel 2.6.x
- Boot Loader: U-Boot 1.1.2
- File Systems: JFFS2, ETX2/ETX3, VFAT/FAT, NFS

Protocol stacks

▶ IPv4, ICMP, ARP, DHCP, NTP, TCP, UDP, FTP, Telnet, HTTP, PPP, PPPoE, CHAP, PAP, SMTP, SNMP V1/V2, SSL, SSH 1.0/2.0

Utilities

- bash: shell command
- tinylogin: login and user manager utility
- telnet: Telnet client program
- busybox: Linux utility collection
- ftp: FTP client program

Daemon

- pppd: Dial In/out over serial port and PPPoE
- snmpd: SNMP agent program
- telnetd: Telnet server program
- inetd: TCP server program
- ttpd: FTP server program
- boa: Web server programsshd: secured shell server
- iptables: Firewall service manager
- armd: Artila manager daemon

Tool Chain for Linux

- GCC: C/C++ PC cross compiler for Linux, CygWin
- GLIBC: POSIX Library

Device Drivers

SD/MMC, UART, Real Time Clock, Buzzer, Digital I/O, Ethernet, Watchdog Timer

USB Host Drivers (could be customized)

- Flash disk
- WiFi (IEEE-802.11b/g)
- RS-232 adaptors

TTY Pin Assignment

PIN	RS-232	RS-422	RS-485
1	DSR *	_	_
2	RTS	Tx+	Data+
3	GND	GND	GND
4	Tx	Tx-	Data-
5	Rx	Rx+	_
6	DCD *	Rx-	_
7	CTS	_	_
8	DTR *	_	_



* Port 2 only

Ordering Information

Matrix-514

ARM9-based Linux Computer with 16MB on-board Flash

CB-RJ45F9-150 (91-R45F9-150)

Serial Cable (RJ45 to DB9 Female, 150cm)

図 CB-RJ2CON-100 (91-RJCON-100)

Console Cable (RJ45 to DB9 Female, 100cm)

M DK-35A (36-DK35A-000)

DIN RAIL Mounting Kit



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660