*3 year advanced exchange warranty

Model	9XL1230QL	8XL4230QL 8XL4230QL	8XL4830QL 8XL4830QL	8XL5230QL 8XL5230QL	6XB0L3050QL	49BDL3650QD/00	55BDL3650QD/00	65BDL3650QD/00	75BDL3650QD/00	86BDL3650QD/00
Diagonal Size	32"	43"	48"	55"	65"	49"	50"	65"	75"	86"
Backlight Type	Direct-Lit LED					Edge-Lit LED			Edge-Lit LED	Edge-Lit LED
Placement	Landscape 16/7, Portrait 12/7					Landscape 16/7, Portrait 12/7				
Resolution	1920 x 1080p					3840 x 2160p				
Panel Technology	IPS	MVA	MVA	IPS	VA	IPS	VA	VA	IPS	IPS
Contrast Ratio	1400:1	3000:1	4000:1	1200:1	4000:1	1200:1	4000:1	4000:1	1200:1	1200:1
Dynamic Contrast Ratio	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1
Response Time	8 ms	6.5 ms	8 ms	6.5 ms	8 ms	9 ms	8 ms	8 ms	8 ms	8 ms
Viewing Angles	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree
Display Colors	16.7 Million	16.7 Million	1.07 Billion	16.7 Million	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion
Brightness	350 cd/m2	350 cd/m2	350 cd/m2	350 cd/m2	350 cd/m2	350 cd/m2	350 cd/m2	350 cd/m2	400 cd/m2	400 cd/m2
Protective Glass										
Touch Technology										
Touch Points										
Power Consumption	52 W (EPA 7.0)	67 W (EPA 7.0)	115 W (EPA 7.0)	147 W (EPA 7.0)	176 W (max)	140 W	145 W	295 W (max)	360 W (max)	430 W (max)
Video Input	DVI-D HDMI, Component Composite, VGA (Analog D-Sub), USB				Display Port, DVI-D, VGA (Analog D-Sub), Component, Composite, USB, eDM	DVI-D, HDMI (v.1.4), VGA (Analogue D-Sub), USB		DVI-D, HDMI (v.4), VGA (Analogue D-Sub), USB, DisplayPort		
Video Output	N/A				Display Port, DVI-I, VGA (via DVI-D)	N/A				
Audio Input	Audio Left/Right (RCA), 3.5 mm jack					Audio Left/Right, 3.5 mm jack				
Audio Output	Audio Left/Right (RCA), 3.5 mm jack					Audio Left/Right (RCA)				
Internal Speaker	2 x 10 W RMS									
External Control	RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack				RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack	RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack				
Extra Connectors	USB	USB	USB	USB	USB	micro SD, USB				
Dimensions (W x H x D)	726.5 x 425.4 x 63.6 mm	968.2 x 558.4 x 59.9 mm	1068.8 x 625.4 x 59.9 mm	1238.6 x 711.1 x 59.9 mm	1458.7 x 834.7 x 89.6 mm	1099.2 x 619.9 x 62.4 mm	1239.2 x 711.6 x 62.7 mm	1458.7 x 834.7 x 89.6 mm	1679.6 x 955.4 x 73.8 mm	1927.9 x 1139.8 x 85.9 mm
Bezel Width	(T/L/R) 18.6 mm / (B) 17.2 mm	(T/L/R) 11.9 mm / (B) 14.9 mm	(T/L/R) 11.9 mm / (B) 14.7 mm	(T/L/R) 12.6 mm / (B) 14.5 mm	(T/L/R) 13.9 mm / (B) 14.9 mm	(T/L/R) 9.9 mm / (B) 14.4 mm	(T/L/R) 12.9 mm / (B) 14.7 mm	(T/L/R) 13.9 mm / (B) 14.9 mm	(T/L/R) 13.9 mm / (B) 14.9 mm	(T/L/R) 15.5 mm
Vesa Mount	100 x 100 mm, 200 x 200 mm, M4	200 x 200 mm, 400 x 400 mm, M6	200 x 200 mm, 400 x 400 mm, M6	400 x 200 mm, 400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, 200 x 200 mm, M6	400 x 400 mm, M6	600 x 600 mm, M8	600 x 400 mm, M8
Smart Insert Mount	N/A	N/A	N/A	N/A	100 x 100 mm, 100 x 200 mm	N/A	N/A	100 x 100 mm, 100 x 200 mm	100 x 200 mm, 100 x 200 mm	100 x 100 mm, 100 x 200 mm
Weight (in KG)	5.20 kg	8.70 kg	11.52 kg	16 kg	24.8 kg	11.4 kg	15.95 kg	24.8 kg	53.3 kg	63.78 kg

Model	55BDL3650QT/00	65BDL3650QT/00	75BDL3650QT/00	86BDL3650QT/00	49BDL3515P	43BDL3515P	49BDL3515P	55BDL3515P	55BDL3515P
Diagonal Size	55"	65"	75"	86"	49"	43"	49"	55"	55"
Backlight Type	Edge-Lit LED		Direct-Lit LED	Direct-Lit LED	E-LED				
Placement	Landscape 16/7, Portrait 12/7				Landscape & Portrait 24/7				
Resolution	3840 x 2160p				1920 x 1080p				
Panel Technology	IPS				IPS 10 bit	IPS 10 bit	IPS 10 bit	IPS 10 bit	IPS 10 bit
Contrast Ratio	1200:1	1200:1	1300:1	1300:1	1300:1	1300:1	1300:1	1300:1	1300:1
Dynamic Contrast Ratio	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1
Response Time	8 ms		8 ms	8 ms	8 ms	8 ms	8 ms	8 ms	8 ms
Viewing Angles	178 / 178 degree				178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree
Display Colors	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion
Brightness	350 cd/m2	350 cd/m2	400 cd/m2	400 cd/m2	500 cd/m2	700 cd/m2	500 cd/m2	700 cd/m2	500 cd/m2
Protective Glass									
Touch Technology									
Touch Points									
Power Consumption	176 W (max)		360 W (max)	430 W (max)	71.08 (EPA 7.0)	63.32 W (EPA 7.0)	82.08 W (EPA 7.0)	99.83 W (EPA 7.0)	90.93 W (EPA 7.0)
Video Input	DVI-D, HDMI (v.4), VGA (Analogue D-Sub), USB, DisplayPort				DisplayPort, DVI-I, VGA (via DVI)				
Video Output	DisplayPort, DVI-I, VGA (via DVI)				DisplayPort		DisplayPort, DVI-I, VGA (via DVI)		
Audio Input	3.5 mm jack, Audio Left/Right (RCA)				3.5 mm jack		Audio Left/Right (3.5 mm jack)		
Audio Output	Audio Left/Right (3.5 mm jack), External speaker connector				Audio Left/Right (3.5 mm jack)				
Internal Speaker	2 x 10 W RMS								
External Control	RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack				RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack				
Extra Connectors	mPCIe slot, WiFi, USB 2.0, micro SD, micro USB				mPCIe slot, micro SD, micro USB, USB power outlet (5 V, 2 amp), OPS		Micro SD, Micro USB, mPCIe, USB 2.0, OPS		
Dimensions (W x H x D)	1239.2 x 711.6 x 62.7 mm	1458.7 x 834.7 x 89.6 mm	1679.6 x 955.4 x 73.8 mm	1927.9 x 1139.8 x 85.9 mm	1098.9 x 619.9 x 62.4 mm	1239.2 x 711.6 x 62.7 mm	1458.7 x 834.7 x 89.6 mm	1679.6 x 955.4 x 73.8 mm	1927.9 x 1139.8 x 85.9 mm
Bezel Width	(T/L/R) 9.5 mm / (B) 14.7 mm	(T/L/R) 9.5 mm / (B) 14.9 mm	(T/L/R) 9.5 mm / (B) 14.9 mm	(T/L/R) 9.5 mm / (B) 14.9 mm	(T/L/R) 5.2 mm	(T/L/R) 5.9 mm	(T/L/R) 5.9 mm	(T/L/R) 5.9 mm	(T/L/R) 5.9 mm
Vesa Mount	400 x 400 mm, M6	400 x 400 mm, M6	600 x 400 mm, M8	600 x 400 mm, M8	200 x 200 mm, M6	200 x 200 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6
Smart Insert Mount	100 x 100 mm, 100 x 200 mm		100 x 200 mm, 100 x 200 mm	100 x 200 mm, 100 x 200 mm	N/A			100 x 100 mm, 100 x 200 mm	
Weight (in KG)	15.5 kg		19 kg	25.2 kg	15.6 kg	19.2 kg	24.35 kg	24.35 kg	24.5 kg

Model	55BDL3802H	75BDL3802H	65BDL4980UC	80.5 55BDL	55BDL3005X	55BDL3007X	55BDL3425L	55BDL9018L
Diagonal Size	55"	75"	48"	55"	55"	55"	54.6"	54.6"
Backlight Type	Direct-Lit LED		Direct-Lit LED		Direct-Lit LED		LED	LED
Placement	Landscape & Portrait 24/7		Landscape & Portrait 24/7		Landscape & Portrait 24/7		Landscape 24/7	
Resolution	1920 x 1080p	3840 x 2160p	1920 x 1080p		1920 x 1080p		480 x 270p	640 x 360p
Panel Technology	SVA	IPS	IPS	IPS	IPS	IPS	LED	LED
Contrast Ratio	5000:1	1200:1	1300:1	1400:1	1200:1	1200:1	5000:1	5000:1
Dynamic Contrast Ratio	5000,000:1		5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1
Response Time	6 ms	8 ms	8 ms	12 ms	8 ms	8 ms	7680 Hz	7680 Hz
Viewing Angles	178 / 178 degree		178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	160 / 140 degree	
Display Colors	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	262 thousand	16.7 Million
Brightness	2500 cd/m2	3000 cd/m2	450 cd/m2	500 cd/m2 (700 cd/m2 in BDL5506QL)	500 cd/m2	700 cd/m2	300 cd/m2	450 cd/m2
Protective Glass							N/A	N/A
Touch Technology							N/A	N/A
Touch Points							N/A	N/A
Power Consumption	368 W (typ)	TBD	110 W (EPA 7.0) / 125 (EPA 7.0) (BDL5506QL)		175 W	175 W	162 W (typ)	89.9 W (typ)
Video Input	VGA (Analog D-Sub), DisplayPort (1.2), DVI-D, HDMI (v.2), Component (BNC), Composite (BNC)	VGA (Analog D-Sub), DisplayPort (1.2), DVI-D, HDMI (v.2), Component (RCA), Composite (RCA)	VGA, HDMI (2), DVI, DP, Component, Composite, HDBaseT, USB, OPS		Component (RCA), Composite (RCA), DVI-D, HDMI (v.2), VGA (Analog D-Sub), DisplayPort (1.2)		HDMI (2x)	
Video Output	DisplayPort, DVI-I, VGA (via DVI)	DisplayPort	VGA (via DVI), DVI, DP, OPS HDMI (via DVI)		DisplayPort, DVI-I, VGA (via DVI-I)		HDMI (2x)	
Audio Input	Audio Left/Right (3.5 mm jack)	3.5 mm jack, Audio Left/Right (RCA)			3.5 mm jack, Audio Left/Right (RCA)			
Audio Output	3.5 mm jack, External speaker connector	3.5 mm jack, External speaker connector, SPDIF			Audio Left/Right (RCA), External speaker connector			
Internal Speaker	2 x 10 W RMS							
External Control	RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack		IR (in/out) 3.5 mm jack, RJ45, RS232C (in/out) 2.5 mm jack, OPS		IR (in/out) 3.5 mm jack, RJ45, RS232C (in/out) 2.5 mm jack		RJ45 / RJ25	RJ45 / RJ25
Extra Connectors	OPS, USB	AC-out, OPS, USB	AC out	AC out	OPS		Power daisy chain	Power daisy chain
Dimensions (W x H x D)	1681.2 x 955.6 x 142.4 mm		1077.6 x 607.8 x 103.8 mm	1213.4 x 684.2 x 103.35 mm	1211.6 x 682.2 x 98.5 mm	1211.4 x 682.2 x 98.5 mm	1200.0 x 675.0 x 99.0 mm	1200.0 x 675.0 x 99.0 mm
Bezel Width	(T/L/R) 5.9 mm		(T/L/R) 23 mm / (B) 12 mm	(T/L/R) 23 mm / (B) 12 mm	23 mm (Even Bezel)	23 mm (Even Bezel)	N/A	N/A
Vesa Mount	600 x 400 mm, M8		400 x 400 mm, M6		400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6
Smart Insert Mount	300 x 156 mm		N/A	N/A	N/A	N/A	N/A	N/A
Weight (in KG)	35.6 kg	54.1 kg	21.6 kg	29.2 kg	24.35 kg	24.35 kg	24.5 kg	24.5 kg

Model	10BDL3057T	43BDL4051T	55BDL4051T	65BDL3952T	75BDL3957T	85BDL6470QT
Diagonal Size	10"	43"	55"	65"	75"	84"
Backlight Type	Edge-Lit LED	Edge-Lit LED	Edge-Lit LED	Direct-Lit LED	Direct-Lit LED	Edge-Lit LED
Placement	Landscape & Portrait 16/7	Landscape & Portrait 16/7		Landscape (16/7) & Portrait (12/7)	Landscape (16/7)	Landscape 16/7
Resolution	1280 x 800p	1920 x 1080p	1920 x 1080p	3840 x 2160p	3840 x 2160p	3840 x 2160p
Panel Technology	VA	IPS	IPS	VA	IPS	IPS
Contrast Ratio	8000:1	1100:1	1100:1	4000:1	1200:1	1400:1
Dynamic Contrast Ratio	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1	5000,000:1
Response Time	35 ms	12 ms	12 ms	8 ms	8 ms	12 ms
Viewing Angles	170 / 170 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree	178 / 178 degree
Display Colors	262 thousand	16.7 Million	16.7 Million	16.7 Million	1.07 Billion	1.07 Billion
Brightness	300 cd/m2	450 cd/m2	450 cd/m2	350 cd/m2	400 cd/m2	350 cd/m2
Protective Glass	Anti-reflective / Anti-glare security glass					
Touch Technology	Pcap 5 touch points	IR HID 10 touch points	IR HID 10 touch points	IR HID 10 touch points	IR HID 10 touch points	IR HID 10 touch points
Touch Points		10	10	10	10	10
Power Consumption	6 W	59 W	76 W	165 W	200 W	400 W
Video Input	N/A	DisplayPort, HDMI (v.2), DVI-D, USB, VGA (via DVI)	DisplayPort (1.2), HDMI (v.2), DVI-D, USB, VGA (via DVI)	DisplayPort (1.2), HDMI (v.2), DVI-D, VGA (Analogue D-Sub), Component (RCA), Composite (RCA), HDMI (v.3)	VGA (Analogue D-Sub), DisplayPort (1.2), DVI-D, HDMI (v.2), Component (RCA), Composite (RCA), DP, Component, Composite	
Video Output	HDMI	DisplayPort, DVI-I, VGA (via DVI-I)	DisplayPort, DVI-I, VGA (via DVI-I)	DisplayPort		
Audio Input	3.5 mm jack, Audio Left/Right (RCA)					
Audio Output	Audio Left/Right (RCA), External speaker connector					
Internal Speaker	2 x 10 W					
External Control	RJ45, IR (in/out) 3.5 mm jack, RS232C (in/out) 2.5 mm jack					
Extra Connectors				SD, micro SD, micro USB, mPCIe, OPS, USB power outlet	USB, OPS, AC-out	
Dimensions (W x H x D)	26 x 167.2 x 29 mm	1000.2 x 590.8 x 91.4 mm	1219.0 x 718.8 x 91.4 mm	1453.43 x 856.7 45 x 98.85 mm	1708.70 x 1006.93 x 121.50 mm	1936.5 x 1112.0 x 54.9 mm
Bezel Width	(T/L/R) 3.2 mm	(T/L/R) 3.2 mm	(T/L/R) 3.2 mm	(T/L/R) 3.2 mm	(T/L/R) 3.2 mm	(T/L/R) 3.6 mm
Vesa Mount	75 x 75 mm, M4	400 x 400 mm, M6	400 x 400 mm, M6	400 x 400 mm, M6	600 x 400 mm, M8	600 x 550 mm, M8
Smart Insert Mount	N/A	-	-	100 x 100 mm, 100 x 200 mm	100 x 100 mm, 100 x 200 mm	100 x 100 mm, 100 x 200 mm, M6
Weight (in KG)	7.1 kg	19.4 kg	31 kg	43.1 kg	75 kg	98.3 kg

Signage Features

*Features may not be available on all models

Model	3012 Line	3012 Lite	3x Line	3x Lite	X Line	E Line	T Line
CMND	√		√	√	√	√	√
Android	-	√	√	√	√		√
Tizen			√	√	√		√
Clinical D Image	√		√	√	√		√
SmartPlayer	√		√	√	√		√
SmartInset			√	√	√		√
SmartPower	√		√	√	√	√	√
SmartBrowser	√		√	√	√		√
WiFi	√ (Optional)		√ (Optional)				√
Memory Cache	√		√	√ (Only 3T)			√
QuadViewer			√	√ (Only 3T)			√
4G/LTE			√	√			√
High-Refresh Rate						√	

*Requires optional CM250 OPS module

Signage Accessories

Type Number	Ambient Sensor CIR04	Color Calibration Kit CCK4002	Edge Finishing Kit
Compatible Models	All models	All models	EFN4730 (Top Bottom), EFN4830 (Left/Right), EFN4930 (Top Bottom), EFN4930 (Left/Right), EFN5530 (Top Bottom), EFN5530 (Left/Right)

Model	Studio				EasySuite				MediaSuite				Signature				Heartline			
	HFL2869				HFL3010T				HFL5201				HFL7011				HFL3010W		HFL4010W	
Model	32HFL2869/F	26HFL2869/T	32HFL2869/T	39HFL2869/T	43HFL3010T/T	49HFL3010T/T	43HFL3010T/T	49HFL3010T/T	32HFL5201/T	43HFL5201/T	49HFL5201/T	55HFL5201/T	49HFL7011/T	55HFL7011/T	65HFL7011/T	75HFL7011/T	32HFL3010W/T	43HFL3010W/T	55HFL4010W/T	75HFL4010W/T
Screen Size	55 cm (22")	66 cm (24")	80 cm (32")	98 cm (39")	108 cm (43")	121 cm (48")	121 cm (48")	125 cm (49")	139 cm (55")	164 cm (65")	80 cm (32")	102 cm (40")	108 cm (43")	123 cm (49")	139 cm (55")	164 cm (65")	80 cm (32")	102 cm (40")	41 cm (19")	
Resolution	1920x1080p	1366 x 768p	1366 x 768p	1360 x 768p	1920x1080p	1920x1080p	1920x1080p	3840x2160p	1366 x 768p	1920 x 1080p			3840 x 2160p				1366 x 768p	1920 x 1080p	1366 x 768p	
Wide Colour Gamut	N/A							N/A	N/A				N/A				Yes (BT.709)		N/A	
Memory	N/A							N/A	8 GB				16 GB				N/A		N/A	
Antiglight	N/A							N/A	N/A				3-sided				N/A		N/A	
PWR	100				200			200	800				200				200		200	
Picture Enhancement	LED Full HD	LED HD	LED HD	LED HD	LED Full HD	LED Full HD	LED Full HD	4K Ultra HD LED	Pixel Plus HD				Picture Precise Ultra HD				Pixel Plus HD		Pixel Plus HD	
Sound Output power	5 W	5 W	12 W	12 W	16 W	16 W	16 W	16 W	5 W	16 W	16 W	16 W	16 W	16 W	16 W	45 W	16 W	16 W	5 W	
Colour cabinet	Black, transparent backcover				Black			Black	Black				Black			Silver	Dark Grey Aluminum		White	
Wireless	N/A							N/A	N/A				Wireless LAN: 802.11 b/g/n, Wi-Fi Direct, Bluetooth 4.0				N/A		N/A	
Ethernet LAN RJ45 (Rear/Side/Bottom)	N/A							N/A	N/A				0/1/1				0/1/1		N/A	1/0/0
HDMI (Rear/Side/Bottom)	2/0/0 HDMI 2.0 with HDCP 2.2	2/0/0	2/0/0	2/0/0	2/1/0	2/1/0	2/0/0	2/0/0 (HDMI 2.0 with HDCP 2.2)	2/1/0				0/2/2 (v.1.4 HDMI, on side)				0/2/2 (v.1.4 HDMI, on side) (HDMI 2.0)		2/1/0	1/1/0
USB (Rear/Side/Bottom)	0/1/0				1/1/0			0/1/0	0/2/1				0/2/1				0/2/1		1/1/0	0/1/0
SVP + IR IN OUT RJ45 (Rear)	N/A				1			N/A	1				1				1		1	1
DC 12V out (rear)	N/A				N/A			N/A	1				N/A				N/A		N/A	N/A
Headphone-Mini Jack (Side)	1				1			1	1				1				1		1	1
Speaker out Mini Jack (Rear)	N/A				1			N/A	1				1				1		1	1
DVI Audio in (Rear)	N/A				1			N/A	1				1				1		1	N/A
Digital Audio OUT (Rear/Bottom)	1/0 Coaxial (SPDIF)	1/0 Coaxial (SPDIF)	1/0 (Optical)	1/0 (Optical)	1/0 (Optical)	1/0 (Optical)	1/0 (Optical)	1/0 (Optical)	1/0 (Optical)				0/1 (Optical)				0/1 (Optical)		1/0 (Optical)	N/A
VGA (Rear)	1				N/A			1	N/A				N/A				N/A		N/A	N/A
Component IN + L/R (Rear/side)	N/A				1/0 (shared with YPbPr)			N/A	1/0 (shared with YPbPr)				1/0 (shared with YPbPr)				1/0 (shared with YPbPr)		1/0 (shared with YPbPr)	N/A
Antenna IN (IEC) (Rear/Bottom)	1/0 (DVB-T/T2/C HEVC)				1/0 (DVB-T/T2/C HEVC)			1/0 (DVB-T/T2/C HEVC)	0/1 (DVB-T/T2/C HEVC)				0/1 (DVB-T/T2/C HEVC)				1/0 (DVB-T/T2/C HEVC)		1/0 (DVB-T/T2/C)	
CI Slot (Side)	1	1	1	1	1	1	1	1	1				1				1		1	N/A
Set Dimensions (ex. Stand)	5.8 x 37.1 x 35.4 cm	15.4 x 33.6 x 15.6 cm	19.5 x 43.8 x 17.9 cm	88.9 x 52.1 x 78.1 cm	9.8 x 57.2 x 64.1 cm	10.9 x 63.1 x 64.1 cm	11.2 x 63.2 x 92.1 cm	12.48 x 70.1 x 92.96 cm	14.9 x 84.1 x 73.5 cm	56.0 x 3.6 x 35 mm	72.1 x 4.25 x 64.7 mm	91.8 x 5.2 x 64.7 mm	96.6 x 5.8 x 80 mm	121.1 x 4.25 x 64.7 mm	91.8 x 5.2 x 64.7 mm	72.1 x 4.25 x 64.7 mm	91.8 x 5.2 x 64.7 mm	121.1 x 4.25 x 64.7 mm	91.8 x 5.2 x 64.7 mm	121.1 x 4.25 x 64.7 mm
Vesa Compatible	75 x 75 mm, M4	75 x 75 mm, M4	200 x 100 mm, M4	200 x 200 mm, M6	200 x 200 mm, M6	200 x 200 mm, M6	200 x 200 mm, M6	400 x 200 mm, M6	400 x 400 mm, M6	75 x 75 mm, M4	100 x 100 mm, M4	200 x 200 mm, M6	100 x 100 mm, M4	200 x 200 mm, M6	400 x 200 mm, M6	400 x 200 mm, M6	100 x 100 mm, M4	200 x 200 mm, M6	400 x 200 mm, M6	75 x 75 mm, M4
Product weight (ex. Stand)	3.5 kg	3.5 kg	5.1 kg	6.6 kg	8.3 kg	10.1 kg	10.6 kg	13.8 kg	23.5 kg	3.3 kg	4.9 kg	8 kg	8.3 kg	5 kg	8.2 kg	14.5 kg	8.1 kg	28.35 kg	4.9 kg	8 kg
Typical Power Consumption	19 W	19 W	31 W	31 W	37 W	45 W	42 W	60 W	82 W	19 W	31 W	45 W	42 W	28 W	45 W	43 W	32 W	67 W	31 W	46 W
Energy Label	A+	A+	A+	A++	A++	A++	A++	A++	A+	A+	A+	A+	A+	A+	A+	A+	A+	A+	A+	A+
Stand	Fixed stand							Fixed stand	Edge Stand	Fixed stand				Swivel stand			Swivel stand		Fixed stand	Fixed stand
Included Remote Control	22AV4U/12				22AV4S/12			22AV4S/12		22AV5S/12				22AV5S/12			22AV5S/12		22AV4S/A (Hygienic)	N/A
Optional Remote control	22AV4U/12				22AV4U/12			22AV4U/12		22AV4U/12	22AV4S/A (Hygienic), 22AV5S/A (Easy)			22AV5S/A (12 BT + Keyboard), 22AV4S/A (Hygienic), 22AV5S/A (Easy)			22AV5S/A (12 BT + Keyboard), 22AV4S/A (Hygienic), 22AV5S/A (Easy)		22AV4S/A (Easy)	22AV4S/A (Standard), 22AV5S/A (Hygienic), 22AV5S/A (Easy)

Professional TV Accessories

Type	22AV5S/A	22AV5S/A	22AV5S/A	22AV5S/A
Quantity	25 pcs	1pcs	1pcs	1pcs
Dimensions (WxDxH)	18.4 x 48 x 2.0 mm	20.3 x 48 x 2.0 mm	2.7 x 52 x 2.9 mm	2.05 x 51.5 x 2.0 mm
Battery	2 x AAA (Not included)	2 x AAA (Not included)	2 x AAA (Not included)	2 x AAA (Not included)
Compatible Models	Multi-RC Compatible Studio, ES/MS/Sig	Multi-RC Compatible Studio, ES/MS/Sig	miniHFL3201 miniHFL7011	Studio, ES/MS/Sig
Features	Glow-in-the-Dark buttons, RC Battery Door Lock, Cable Strap Ready, Low Battery Detection	Top surface cleanable with Alcohol, RC Battery Door Lock, Cable Strap Ready, Low Battery Detection	QWERTY Keyboard, Bluetooth, Top/Bottom detection, Glow-in-the-Dark Clock Button, RC Battery Door Lock, Low Battery Detection	Professional Set-up Remote Control

Professional TV Features

Model	HFL7011	HFL5201	HFL3010T	HFL2869 - HFL2869	HFL3010W	HFL4010W
	Signature	MediaSuite	EasySuite	Studio	Heartline	Bedside TV
Features						
Android OS	√	√				
Antilight	√	√				
CMND&Control	√	√	√		√	√
CMND&Create	√	√	√	eff-free channel editor	√	√
IPTV Channels	√	√				√
IPTV System	√	√				√
Customizable Dashboard (HTML5)	√	√				√
Welcome logo	√	√	√	√	√	√
Cloud-Based Apps	√	√				√
Android Apps	√	√				
AppControl	√	√				√
PTA app, Directshare & Miracast	√	√				
MHL	√	√				
USB Playback	√	√	√	√	√	√
Serial Xpress Pertocol	√	√	√		√	√
My Choice	√	√	√		√	√
Theme TV	√	√	√		√	
Wake-up on LAN	√	√				√
Wake-up on Wireless LAN	√	√				
8 day EPG, Now + Next	√	√	√	√	√	√
Weather forecast	√	√				
Facility Name	√	√				
On-screen clock & alarm	√	√	√		√	√
Time Saver for Installer						
Nurse call system Compatible	√	√	√		√	√
Multi-remote control	√	√	√	√	√	√
Headphone out	√	√	√	√	√	√
Wireless Headphone support	√	√				
Independent main speaker mute	√	√			√	√
Double isolation class II	√	√	√		√	√
Galvanically isolated headphone out						√
IXS2360 Anti-microbial housing						√
IEC 60601-1						
Ease of Installation						
Hotel Mode (Menu, Volume and Local Control locking)	√	√	√	√	√	√
Prison Mode	√	√	√	√	√	√
Single Channel list analog/digital	√	√	√	√	√	√
Cloning	√	√	√	√	√	√
Instant initial cloning	√	√	√	√	√	√
Anti-Theft						
RC Battery Lock	√	√	√	√	√	√
Kensington Lock	√	√	√	√	√	√

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660