

ViTAM-119P/R/G(H)	19" IP66 / IP69	9K Stainless Steel Dis	splay		Industrial Panel PC		Industrial play Monitor Box PC	
	Features Prove Generation Stainless Steel Display Prove Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure ages 316 for Option) Prove Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure Prove Tesistive Touch, Projected Capacitive Touch, and Glass Duport Resistive Touch, Projected Capacitive Touch, and Glass Duport Resistive Touch, Projected Capacitive Touch, and Glass Duport Ergonomic Versatile Mounting: Yoke Mounting / space-saving VESA 100 x 100 mm Mounting Specifications Value <l< td=""><td colspan="4"></td><td></td></l<>							
								· ·
	Dispalay	Standard	High Brightness Optional				UNII: mm Tolerance: 0.5	
	Display Type	19" TFT-LCD	19" TFT-LCD					
	Max. Resolution	1280 x 1024	1280 x 1024					
	Max. Color	16.7M	16.7M					
	Luminance (cd/m ²)	350	1000					
	View Angle	170(H) /165(V)	170(H) /160(V)					
	Contrast	1000:1	1000:1					
	Backlight Lifetime	50,000 hrs	50,000 hrs	Environmenta				
	Option	Optical Bonding	Optical Bonding	Operating Terr	•			
				Storage Tempe				
	Touch Screen			Storage Humic		n- condensing		
	Туре	Resistive Touch (For R model) Projected Capacitive Touch (F		Certificate	CE/FCC Class A			
		Glass (For G model)		Ordering Info				
	Interface Light Transmission(%	Iterface USB Ight Transmission(%) Resistive Touch : 80% / Projected Capacitive : 90%			the rear side, projected capacitive Adapter	teel display, VGA/HDMI input, OSD on touch, 9~36V DC power input with		
		Dennes			19" SXGA IP66/IP69K stainless st	teel panel display, VGA/HDMI input, OSD		
	Power	DC 9~36V		ViTAM-119R	on the rear side, 5 wire resistive to Adapter	buch window, 9~36V DC power input with		
	Power Consumption	ViTAM-119P: 16.3W ViTAM-119PH: 29.5W		ViTAM-119G	19" SXGA IP66/IP69K stainless steel display, VGA/HDMI input, OSD on the rear side, protection glass, 9~36V DC power input with Adapter			
	Mechanical				19" SXGA IP66/IP69K stainless st	teel display, VGA/HDMI input, OSD on		
	Construction 304 Stainless steel chassis(default), 316 Stainless steel chassis(optional)		VITAW-TI9PH	the rear side, projected capacitive touch, 9~36V DC power input with Adapter, 1,000 nits LCD 19 SXGA IP66I/P69K stainless steel panel display, VGA/HDMI input, OSD				
	Mounting	VessA Mount 100 x 100, Yoke mount (option) P Rating Total IP66/IP69K		ViTAM-119RH	on the rear side, 5 wire resistive to			
	IP Rating				Adapter, 1,000 nits LCD 19" SXGA IP66/IP69K stainless steel display, VGA/HDMI input, OSD on the rear side, protection glass, 9–36V DC power input with Adapter, 1,000			
	Dimensions							
	Net Weight	8.8 kg		VITAM-119GH	the rear side, protection glass, 9~3 nits LCD	boy Do power input with Adapter, 1,000		
	-	-					V 1.1	_

Industrial Panel PC

Industrial Panel PC

All specifications and photos are subject to change without notice.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660