

AI Vehicle Computer

COMPACT AI Vehicle Series

Intelligent Machine Learning Unit with NVIDIA Jetson TX2



AI Vehicle Computer

IPC/COMPACT A2 - RM

This fanless RM COMPACT-A2 generation is based on the NVIDIA Jetson TX2 processor module and offers a wide range of interface options. The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- 6 LAN Interfaces w/ individual NIC's
- Power over Ethernet (PoE+), 48VDC out
- Long term availability with fixed BOM

 **NVIDIA. Linux for Tegra (L4T)**

Product Highlights

Maintenance free
Goldcap instead of battery backup
No moving parts / passive cooling
ARM CPU core
Hardware watchdog
Temperature supervision
ESD- protection on all interfaces
Long term availability (fixed BOM)
Shock and vibration resistant

Product Features

256-core NVIDIA Pascal™ GPU
Dual-Core NVIDIA Denver 2 64-Bit CPU
Quad-Core ARM® Cortex®-A57 MPCore
8GB 128-bit LPDDR4 RAM soldered on board
Socket for CFast
Ethernet, USB, Passive or Active CAN
Optional 4G LTE connectivity
Aluminum & Stainless steel housing
Protection class IP40

Markets / Applications

Automated Guided Vehicle (AGV)
Transportation
Construction Vehicles



Order Code IPC/RMA2I20-A2035¹ IPC/RMA2I20-B2035¹

Processor module / Performance		
NVIDIA Jetson TX2 256-core NVIDIA Pascal™ GPU	•	•
NVIDIA Jetson TX2 4GB 256-core NVIDIA Pascal™ GPU	optional	optional
NVIDIA Jetson TX2i 256-core NVIDIA Pascal™ GPU	optional	optional
Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore	•	•
AI Performance	1.3 TOPs	1.3 TOPs
Memory / Storage		
Data Cache Size	2MB	2MB
4ch x 32-bit LPDDR4 RAM soldered on board	8GB	8GB
eMMC 5.1 Flash Storage on board	32GB	32GB
microSD Card socket ²	1	1
CFast socket with retention frame ²	1	1
Features		
Inertial measurement unit (IMU) STMicroelectronics ISM330DLC	•	•
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Real time clock (RTC) with Goldcap backup (48h)	optional	optional
Hardware Watchdog & Temperature supervisor	•	•
Intelligent power management	•	•
Communication Interfaces		
Graphic interface	DisplayPort 1.2	DisplayPort 1.2
USB version 3.0 (Type A)	2	2
Internal USB version 2.0 OTG ^{behind the cover} (micro USB Type AB)	1	1
Ethernet 10/100/1000Mbit (1x native, 1x I210-IT) (M12 female x-coded)	2	2
Power over Ethernet - IEEE802.3at 10/100/1000Mbit (M12 female x-coded / RJ45)	4x M12 (total max power: 39W)	4x RJ45 (total max power: 39W)
PSE - Power sourcing equipment, producing 48VDC out		
Active/passive-CAN ESD protected, isolated (1x DSUB9)	2	2
RS232 / RS422/485 ESD protected (DSUB9)	optional	optional
Mini PCIe socket ²	1	1
I2C bus ²	•	•
Buzzer	•	•
MIPI CSI-2 Camera Interface ²	•	•
Wireless Connectivity		
Cellular Module (LTE/UMTS/GSM) with GNSS positioning functionality Sierra Wireless MC7455 - M2M only! (3x SMA)	•	•
Dual SIM Support (nanoSIM to mPCIe slot ²)	•	•
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 4.1 (2x RP-SMA)	•	•
Technical Data		
Dimensions w174 x h82 x d127 mm (housing without mounting bracket)	•	•
Net weight in gram	~1100	~1100
Non isolated input voltage, with Ignition controller, reverse polarity protected (M12 4P male A-coded)	9... 45VDC	9... 45VDC
Current consumption typ. in mA @ 24V without Add-Ins, idle	~625	~625
Power consumption typ. in Watt @ 24V without Add-Ins, idle	~15	~15
Environmental Conditions		
Operating temperature ³	-25°C ... +65°C	-25°C ... +65°C
Storage temperature	-25°C ... +80°C	-25°C ... +80°C
Protection standard	IP40	IP40
UN/ECE R10 (E-mark) certification	on request	on request
Conformal coating ⁴	on request	on request
Shock (designed to meet)	EN60068-2-27	EN60068-2-27
Vibration (designed to meet)	EN60068-2-64	EN60068-2-64
EMI-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	RED	RED
MTBF @ 25°C ambient ^{according to Telcordia SR-332, Environment GB, excluding battery}	~390 000h	~390 000h

¹Please contact factory for minimum order quantities

²Internal connector

³Depending on installation situation and interface connection. Please see user documentation.

⁴On all possible components (excl. TX2(i) Module, connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2020 Syslogic Datentechnik AG
All rights reserved

Syslogic Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 1.2 | November 2020

For further information and support:
info@syslogic.com
support@syslogic.com
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)
+49 7741 9671-420 Germany and Austria



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660