

L1565S-PCT

Specification

Plastic case, 15.6" LCD monitor, 1366x768, 250nits



Features

- Foldable stand adds flexibility and comfort to your viewing preferences
- The extra-small footprint creates more work space on the desk
- Integrated amp and stereo speakers give you a complete multimedia experience
- 1366 x 768 pixels resolution provides sharp and brilliant images of text and graphics

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size	wide / 15.6" viewable diagonal area		
	Active Area / Pixel Pitch	344.23(H) x 193.54(V) mm / 0.252(H) x 0.252(V) mm		
	Native Resolution / Colors	1366(H) x 768(V) / 16.7 Million		
	Brightness / Contrast	250 cd/m ² (typ) / 500 : 1		
	Response Time	≤ 8 ms		
	Viewing Angle (typical)	H. 90° (- 45° ~ + 45°) , V. 65°(- 45° ~ + 20°)		
	Light Source	CCFL , Long life, 50,000 hrs (typ)		
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F _h : 30 - 82KHz , F _v : 50 -75Hz	
	Audio System	2W speaker x 2		
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Jack			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)			
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz			
Power Consumption	Operation / Power Saving	15 watt , < 1 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)		
Certification	FCC , CE			
Dimensions	Physical	With Base(W x H x D) : 387 x 314.76 x 240.86 (mm)		
		Without Base(W x H x D) : 387 x 244 x 56 (mm)		
	Carton	W x H x D = TBD		
Weight	N.W. / G.W.	4.0 Kgs / 5.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)		

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	DVI	Panel with LED backlight	Digital Signage(Stand alone)
	Project capacitive touch	HDMI	Sun Light Readable	Motion Sensor
	Protected glass	SV + AV	Wide Temperature	Auto-Dimming Light Sensor

Winsonic[®]

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download www.ewinsonic.com

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660