

# iiyama

#### PROLITE TE8612MIS-B1AG



#### 86" Interactive 4K UHD Touchscreen featuring a 4K interface with User Profiles

Collaboration for education and enterprise made simple. The TE8612MIS-B1AG from iiyama inspires all possibilities in all stages for education, start-up and large-scale businesses. With our hybrid interactive solution, you can smoothly annotate in 4K and control any content on the display from any source.

This PureTouch-IR 40-point Touchscreen with iiWare 10 (Android 11 OS) features Note, Browser, Cloud Drive and the option for you to sideload relevant apps you require for your organisation. It comes with dual functionTouch pens, and you can easily save your notes and on-screen content directly to a USB device, 32GB internal memory or a selected cloud drive. Including an additional USB-C connection, the display supports the latest in video, audio and Touch signal via a single port and even charge your device with 65W power delivery.

With a 4K UHD resolution (3840x2160) and 400cd/m² brightness this 86" IPS LCD screen provides vibrant, detailed, and high-quality images from anywhere in the class or meeting room. The anti-glare coating drastically reduces ambient reflection in high-brightness environments without compromising the sharpness and clarity of the image.

You can be sure that no matter what your Interactive aspiration, iiyama has the simplified solution just for you. Boasting a new 4K Interface with User Profiles for simple login and access to your very own bespoke menu and Cloud Drives, the TE8612MIS-B1AG becomes a highly personalised device within a busy hybrid environment for multiple users.







#### PureTouch-IR

PureTouch-IR from iiyama delivers 1mm touch accuracy for the smoothest and fastest annotation.

#### iiWare

iiWare 10 features Note, Browser, Cloud Drive and the option for you to sideload relevant apps you require for your organisation.



# 01

#### DISPLAY CHARACTERISTICS

| Design                           | Thin bezel  |
|----------------------------------|---|
| Diagonal                         | 85.6", 217.4cm  |
| Panel                            | IPS, direct LED, AG coated glass, zero air-gap, haze 28%              |
| Native resolution                | 3840 x 2160 (8.3 megapixel 4K UHD)                                    |
| Aspect ratio                     | 16:9  |
| Panel brightness                 | 400 cd/m <sup>2</sup>   |
| Light transmittance              | 88%   |
| Static contrast                  | 1200:1  |
| Response time (GTG)              | 8ms   |
| Viewing zone                     | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support                   | 1.07B 8bit+FRC  |
| Horizontal Sync                  | 30 - 135kHz   |
| Viewable area W x H              | 1895 x 1066mm, 74.6 x 42"   |
| Bezel width (sides, top, bottom) | 16.5mm, 16.5mm, 31mm  |
| Pixel pitch                      | 0.4935mm  |
| Bezel colour and finish          | black, matte  |



## TOUCH

| Touch technology            | PureTouch-IR  |
|-----------------------------|---|
| Touch points                | 40, 5pt writing (HID, only with supported OS)   |
| Touch accuracy              | +- 1.5mm  |
| Touch method                | stylus, finger, glove   |
| Touch interface             | USB   |
| Supported operating systems | All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section. |



#### INTERFACES / CONNECTORS / CONTROLS

| Analog signal input   | VGA x1 (max. 1920x1080 @60Hz)  |
|-----------------------|--|
| Digital signal input  | HDMI x3 (v.2.0, max. 3840x2160 @60Hz, YUV444)<br>USB-C x1 (3.1, 3840x2160 @60Hz - RGB444 - (65W charging, Touch) |
| Audio input           | Mini jack x1   |
| Monitor control input | RS-232c x1<br>RJ45 (LAN) x1<br>IR x1   |
| Digital signal output | HDMI x1 (3840x2160 @60Hz)  |
| Audio output          | S/PDIF (Optical) x1<br>Mini jack x1<br>Speakers 2 x 16W (Front)  |
| HDCP                  | HDMI 1: 2.1, USB-C: 2.2  |
| USB ports             | x5 (media playback / peripherals / storage – front side: 2x 3.0, 1x USB-C 3.1 (65W PD), right side: 2x 3.0)      |
| RJ45 (LAN)            | x2 (Auto switch for PC & Android, 1000MB)  |





| Integrated software          | iiWare 10 (Android 11 OS) featuring iiyama DMS, Note, web browser, file manager, cloud drives, WPS office, iiyama Share and EShare for wireless connection with Windows/iOS/Android devices |
|------------------------------|---|
| WiFi                         | yes (WiFi Module OWM002 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: IIEEE 802.11 a/b/g/n/ac, Bluetooth Support: 2.1/3.0/4.2/5.0)   |
| Hardware                     | Quad core A55 CPU, Mali G52 GPU, 4GB RAM, 32GB internal memory  |
| Extra                        | WiFi Module (OWM002), Slot for optional OPS Slot PC, 4x Touch pen   |
| Kiosk mode                   | yes   |
| Max. non-stop operating time | 16/7  |
| Media playback               | yes   |
| Glass thickness              | 3mm   |
| Glass hardness               | 7H  |
| Housing (bezel)              | metal   |
| OSD key lock                 | yes   |



#### **GENERAL**

| OSD languages      | EN, DE, FR, ES, IT, RU, CZ, NL, PL   |
|--------------------|--|
| Control buttons    | Power, Power Indicator, Remote Sensor, Light Sensor  |
| User controls      | general settings (input, volume, backlight), audio settings (volume, bass, treble, balance, sound mode, mute), screen settings (aspect ratio, pixel shift), display settings (brightness, contrast, hue, sharpness, display mode, colour temp.), adjust settings (H-position, V-position, clock, phase, auto), settings (wireless & networks, personal, input & output, application, system) |
| Blue light reducer | yes  |
| Plug&Play          | DDC2B  |
| Warranty           | 5 years (for details and eligible countries please check the Warranty section of our website)  |



## MECHANICAL

| Orientation                 | landscape                          |
|-----------------------------|------------------------------------|
| Fanless design              | yes                                |
| VESA mounting               | 800 x 600mm                        |
| Operation temperature range | 0°C - 40°C                         |
| Storage temperature range   | - 20°C - 60°C                      |
| MTBF                        | 50.000 hours (excluding backlight) |



## ACCESSORIES INCLUDED

| Cables         | USB, HDMI   |
|----------------|---|
| Touch pen      | x4  |
| Guides         | quick start guide, safety guide   |
| Other          | WiFi Module (OWM002), Mounting bracket for NUC, Mounting bracket for webcam |
| Remote control | yes (batteries included)  |



## POWER MANAGEMENT

| Power supply unit | internal                                   |
|-------------------|--|
| Power supply      | AC 100 - 240V, 50/60Hz                     |
| Power usage       | 215W typical, 0.5W stand by, 0.3W off mode |






CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH (RoHS) Regulations above 0.1%: Lead

REACH SVHC

# **DIMENSIONS / WEIGHT**

| Product dimensions W x H x D | 1957 x 1160 x 100mm |
|------------------------------|---------------------|
| Box dimensions W x H x D     | 2110 x 1283 x 225mm |
| Weight (without box)         | 58.6kg              |
| Weight (with box)            | 75.9kg              |
| EAN code                     | 4948570121854       |



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660