

# DK SERIES DK651DR5

65" 4000 nits Dual-Sided Ultra-High Brightness Outdoor Kiosk





DUAL-SIDED DESIGN



SUNLIGHT VIEWABLE IMAGE



VANDAL RESISTANT



**VIEWABLE WITH** 

POLARIZED LENSES

WEATHER PROOF

#### FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



V0.09




### SPECIFICATION


MODEL		DK651DR5
	LCD Panel Size	65 inches LCD (x2)
	Native Resolution	1920 x 1080
	Brightness (w/o glass)	4,000 nits
	Color Depth	10 bits
DISPLAY	Contrast Ratio	4000:1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
	Polarized Sunglasses Support	Yes
	Detection method	Projected Capacitive Touch Technology
тоисн	Input method	Finger and gloved finger
(Optional)	Noise Shielding	Yes
	Number of simultaneous touch	es Max. 40 points
	Power Supply	Internal
POWER	Rated Voltage	100-120V ~ 50/60Hz
		200-240V ~ 50/60Hz
	Power Consumption (Typ./ Ma	x) 1400 W / 2200 W [TBD]
	Bezel Width (T/B/L/R)	80.0 / 65.3 / 65.3 / 65.3 mm
	Cabinet Color	Black
	Kiosk Dimension (LxHxD)	2200.0 x 953.8 x 317.4 mm
MECHANICAL	Monitor Weight	380 kg
SPECS	Orientation	Portrait
	Glass	Double Laminated Tempered
	Air Vent	Top & Bottom
	Base	539.0 mm H
FEATURE	Language	English
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x6 (1080p recommended)
	DisplayPort 1.2	х2
	USB 3.0	х2
	Micro SD Slot	×2
OUTPUT	Audio	х2
EXTERNAL CONTROL	RJ-45	x4 (LAN)
	Operating Temperature	-30° C ~ 50° C
ENVIRONMENT	Storage Temperature	-20° C ~ 60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust Resistant Desig	gn IP56
	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
INTERNAL	Main Memory Interface	DDR4, 2G
PLAYER	Graphics	Quad-core MaliG51
	Storage	Internal: 16GB eMMC Flash
		External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
	Multimedia	4K 10bits VP9/H265/H264 video decoders, up to 60fps
		1080P other video decoders (VC-1, MPEG-1/2/4, VP8)
PLAYER	Storage	Internal: 16GB eMMC Flash External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32) 4K 10bits VP9/H265/H264 video decoders, up to 60fps


CERTIFICATION CE/FCC/RoHS


### DIMENSIONS


Unit: mm [inch]











DynaScan



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660